

Maximum Productivity

Full production speeds of up to 135ppm are achieved across all media types and weights from $52g/m^2$ up to $300g/m^2$, whilst a maximum paper size of $330mm \times 487mm$ is supported.

A sizeable 14,000 sheets paper supply from up to 3 POD decks with multiple sources is complemented by air-assisted feeding, for exceptional reliability and almost 1.5 hours of uninterrupted production.

Class leading quality

1,200dpi print resolution and an innovative twin sleeve print process combine to deliver outstanding sharp text and images.

Precision printing

Accurate registration, which is actively adjusted during print runs, ensures consistency at high speeds for non-stop operation.

Highly innovative

New micro toner technology developed for this imagePRESS range delivers consistently high quality output across a wide range of media.

Exceptional finishing

Choose from a huge diversity of in-line finishing possibilities including perfect binding, multi-folding, saddlestitching, punching, one or three edge trimming, and up to 2 high capacity stackers. Intelligent Registration technology also ensures impressive results print after print.

imagePRESS 1135

Effortless quality black and white.

For the ultimate in high-end monochrome mid-volume production, turn to our flagship imagePRESS 1135. Offering unbeatable productivity, exceptional media handling and impressive print quality, it's the production engine to keep you well ahead of schedule.

At a glance...

- Maximum Productivity 8,100 impressions per hour, across all media types and weights from 52g/m² up to 300g/m².
- The ability to produce beautiful halftones, rich deep blacks, and holds very thin lines as well as perfectly defined text.
- Air feeding technology ensures reliable feeding of a variety of paper styles and weights.
- Exceptional Finishing a range of finishing options to compliment existing offline facilities maximise production efficiencies.
- Easy to Service Operator Maintenance all key parts can be replaced easily and quickly, maximising up-time.





canon.com.au/pps canon.co.nz

imagePRESS imagePRESS 1135 Specifications

300,000 to 1,000,000

3 million per month

500,000 per month

Canon advanced simplicity®

PRINTING ENGINE Recommended Monthly Print Volume 30 Recommended Maximum Monthly Print Volume Targeted Average Monthly Print Volume Resolution

| rargotoa / trorago ritoriarity / title / tolarito | ooo,ooo por monar |
|---|---------------------------|
| Resolution | 1,200 x 1,200dpi |
| Registration Accuracy | +/- 0.5mm (front to back) |
| HDD Capacity | 80GB |
| Memory | 512+512MB |
| Media Weight | 52 to 300g/m ² |
| Paper Feeding Capacity | |
| Standard: | 2,000 |
| Maximum: | 14,000 |
| Paper Finishing Capacity | 27,000 |
| Dimensions (W x D x H) | 1387 x 809 x 1040mm |
| | (excluding Control Panel) |
| Weight | Approx 500kg |
| Power | 230V x 32A + 230V x 15A |

PRODUCTIVITY

Speed

| opoou | |
|-------------------------|-----|
| Simplex Plain | |
| A4 | |
| 80g/m ² | 135 |
| 81-105g/m ² | 135 |
| 106-180g/m ² | 135 |
| 181-300g/m ² | 135 |
| A3 | |
| 80g/m ² | 79 |
| 81-105g/m ² | 79 |
| 106-180g/m ² | 70 |
| 181-300g/m ² | 70 |
| Simplex Coated | |
| A4 | |
| 90g/m² | 135 |
| 91-120g/m ² | 117 |
| 121-128g/m ² | 78 |
| 129-150g/m ² | 58 |
| 151-180g/m ² | 39 |
| 181-240g/m ² | 29 |
| A3 | |
| 90g/m ² | 70 |
| 91-120g/m ² | 59 |
| 121-128g/m ² | 39 |
| 129-150g/m ² | 29 |
| 151-180g/m ² | 19 |
| 181-240g/m ² | 14 |
| POP DECK-C1 | |
| SECONDARY PAPER DECK-C1 | |
| 3 drawers | |
| 4 000 sheets capacity | |

4,000 sheets capacity 52-300g/m² sheets B5 - 482mm x 335mm Up to 3 decks can attach Power Source/Consumption 230V x 10A Dimension 745 x 792 x 1095mm (1 deck) 1561 x 792 x 1095mm (3 decks) Weight Approx 226kg (1 deck) Approx 452kg (2 decks) Approx 678kg (3 decks)

MULTI DOCUMENT INSERTION UNIT-A1

| 3 drawers | |
|-------------------------------|---------------------|
| 4,000 sheets capacity | |
| 52-300g/m ² sheets | |
| B5 - 13 x 19.2 inch | |
| Power Source/Consumption | 230V x 10A |
| Dimension | 1182 x 792 x 1095mm |
| Weight | Approx 251kg |
| | |

COLOUR IMAGE READER-L1

| | I-L1 |
|--|--|
| 1-pass duplex | |
| Scan Speed | |
| BW – Simplex/Duplex | 120/120ipm (600dpi) |
| | 120/200ipm (300dpi) |
| Colour – Simplex/Duplex | 40/40ipm (600dpi) |
| 0.1.1.1.1.1.0.1.1.1 | 80/80ipm (300dpi) |
| Original Tray Capacity | 300 sheets |
| Power Source/Consumption fro Dimension | 633 x 588 x 179mm |
| Weight Approx | Approx 26.9kg |
| | |
| HIGH CAPACITY STACKE | |
| Stack Tray Capacity | 10,000 sheets / A4 5,000 sheets / A3 with 80g/m ² sheets |
| Top Tray Capacity | 1,000 sheets with 80g/m ² sheets |
| Acceptable Paper Weight | 52-300g/m ² |
| Acceptable Paper Size | B5 - 13 x 19.2 inch |
| Up to 2 stacker can connect | 50 10 X 10.2 mon |
| Power Source/Consumption | 230V x 10A |
| | acker can get power from 1st Stacker) |
| Dimension | 997 x 792 x 1362mm |
| Weight | Approx 210kg |
| PERFECT BINDER-C1 | , pp.o. 210kg |
| | D/ 400 |
| Maximum Cover Size | B4 - 482mm x 335mm |
| Cover weight | 91-300g/m ² |
| Inner Size | B5 - 228.6 x 320mm |
| Inner Weight | 52-105g/m ² Top/Bottom 13 to 79mm |
| Cutting Range | ' |
| Booklet thickness | Fore-edge 6.5 to 49.5mm |
| Power Source | Up to 25mm 230V x 10A |
| Dimension | 922 x 783 x 1300mm |
| | |
| Weight | Approx 306kg |
| PAPER FOLDING UNIT-F1 | 1 |
| V-Fold | |
| Z fold | |
| C Fold | |
| Zigzag Fold | |
| Double Parallel | 52-105g/m ² |
| Power Source | From Finisher-AF1 or Saddle |
| | Finisher-AF2 |
| Dimension | 336 x 793 x 1190mm |
| Weight | Approx 65kg |
| FINISHER-AF1 | |
| Number of trays | 2 |
| Top Tray | 3,000 sheets |
| Below Tray | 2,000 sheets |
| Stapling position | |
| | Corner, Double |
| Acceptable Paper Weight | 52-300g/m ² |
| | 52-300g/m ² 5,000 sheets stock capacity |
| Acceptable Paper Weight | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled |
| Acceptable Paper Weight Power Source | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A |
| Acceptable Paper Weight Power Source Dimension | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm |
| Acceptable Paper Weight Power Source | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A |
| Acceptable Paper Weight Power Source Dimension | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm |
| Acceptable Paper Weight Power Source Dimension Weight | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg 2 |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230Vx 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray | 52-300g/m² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position | 52-300g/m² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets Corner, Double |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets Corner, Double 52-300g/m ² |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets 52-300g/m ² 5,000 sheets stock capacity |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets Corner, Double 52-300g/m ² 5,000 sheets stock capacity Up to 100 sheets staple |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stock capacity 230Vx 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets 52-300g/m ² 5,000 sheets stock capacity Up to 100 sheets staple Up to 100 sheets staple |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position Acceptable Paper Weight | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230Vx 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets 52-300g/m ² 5,000 sheets stock capacity Up to 100 sheets staple Up to 100 sages booklet available (2-25 sheets) |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position Acceptable Paper Weight Available Saddle Size | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets 52-300g/m ² 5,000 sheets stock capacity Up to 100 sheets staple Up to 100 sheets staple available (2-25 sheets) B5 - 13 x 19.2 inch |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position Acceptable Paper Weight Available Saddle Size V-Folding | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stapled 230V x 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets 52-300g/m ² 5,000 sheets stock capacity Up to 100 pages booklet available (2-25 sheets) B5 - 13 x 19.2 inch |
| Acceptable Paper Weight Power Source Dimension Weight SADDLE FINISHER-AF2 Number of trays Top Tray Below Tray Stapling position Acceptable Paper Weight Available Saddle Size V-Folding Power Source | 52-300g/m ² 5,000 sheets stock capacity up to 100 sheets stock capacity 230V x 10A 800 x 792 x1180mm Approx 130kg 2 3,000 sheets 2,000 sheets 2,000 sheets Corner, Double 52-300g/m ² 5,000 sheets stock capacity Up to 100 sheets staple Up to 100 sheets staple E Up to 100 sheets staple Up to 5 sheets 230V x 10A |

BOOKLETTRIMMER-D1 One Edge Trimming (Fore-edge) Trim Width 2-20mm Up to 50 sheets Trim Thickness (includes Cover, by half hold) Acceptable Paper Weight 52-300g/m² Output Tray Capacity 30 booklets Power Source Saddle Finisher-AF2 1575 x 770 x 1040mm Dimension Weiaht Approx 152kg **TWO-KNIFE BOOKLET TRIMMER-A1** Top and Bottom Edge trim Trim Width 2-15mm Up to 50 sheets Trim Thickness (includes Cover, by half hold) Acceptable Paper Weight 52-300g/m² Output Tray Capacity 30 booklets Power Source 230V x 10A Dimension 536 x 770 x 1040mm Weight Approx Approx 145kg PROFESSIONAL PUNCHER-B1 External In-line Punch Unit Acceptable Punch Paper Weight 75-216g/m² Acceptable Punch Paper Size A4 + Tabs Punch Tools Plastic Comb 21-Hole 23-Hole(Round) Twin Loop 34-Hole(Round) Twin Loop Color Coil 47-Hole Velo Bind 12-Hole 4-Hole Punch Loose Leaf Loose Leaf 2-Hole Punch 4-Hole(Swedish) Loose Leaf Loose Leaf 3-Hole Pro Click 34-Hole Power Source From Integration Unit-A1 Dimension 305 x 792 x 1040mm Weiaht Approx 80kg **PROFESSIONAL PUNCHER INTEGRATION UNIT-A1** Mandatory for Professional Puncher-B1 Power Source 230V x 10A Dimension 250 x 792 x 1040mm Weight Approx 80kg **3 SERVER OPTIONS** imagePRESS Server J200 imagePRESS Server J100 imagePRESS Printer Kit-A1

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change. ™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Australia call: 1800 444 199

New Zealand call: 0800 222 666

canon.com.au/pps canon.co.nz