

The easy to use, stylish and compact, laser fax machine



Super G3 laser fax machine, with handset.

This compact Super G3 fax is effortless to use and maintain. Offering superb energy efficiency with a range of professional fax features it's the ideal solution for small and medium-sized businesses.

Key features

- Super G3 fax modem (33.6kbps) - 3 seconds per page* transmission
- Stylish, minimal, space-saving design
- Ultra High Quality 256 greyscale imaging for faxing fine details
- 512-page* transmit and receive fax memory
- 30 one-touch and 100 coded speed dials
- Convenient, easy to use All-in-One cartridge
- 150-sheet paper capacity
- 30-page Automatic Document Feeder
- Intuitive LCD display for a better user experience
- Copying: 12 copies per minute – fast warm up time from sleep mode
- Class leading energy efficiency
- Handset as standard

*Based on ITU-T Standard Chart No. 1.

What's in the Box

Main unit (with Handset), Cartridge 328 starter, power cord, telephone line cable, document tray, destination labels, starter guide - with user software and manual CDs.

Dimensions (WxDxH)

372 mm x 303 mm x 303 mm

Supported OS

Windows 2000/XP/ VISTA/7

Mac OS X 10.4.9 - 10.7

(Web distribution only)

Linux (Web distribution only)

Achieve more. Beyond technology.

Canon

Specifications

- 1 ADF
- 2 5-line LCD
- 3 150-sheet paper cassette
- 4 Cartridge 328
- 5 Handset



FAX Unit Type

Type	Standalone facsimile & Laser printer
Compatibility	Group 3
Applicable line	PSTN
Modem speed	33.6K bps (Super G3)
Print technology	Laser beam printing
Scanner type	Sheet fed

FAX Scanning Features

Automatic document feeder	30 sheets
Document size	Width - 216mm(Max), 139.7mm(Min) Length - 356mm(Max), 127mm(Min)
Effective scanning width	214mm
Scanning speed	Approx. 3.4 sec/page Approx. 15.8 pages/minute
Fax resolution	Up to 200 x 400 dpi
Image processing system	UHQ (Ultra High Quality)
Halftone	256 shades of grey scale

FAX Printing Features

Printing method	Laser Beam Printing
Print speed	18 pages per minutes
First Print Out Time	7.8 secs
Print resolution	600 x 400 dpi
Print Quality	Up to 1200 x 600 dpi
Paper capacity	150 sheet
Print cartridge	CRG328 All in One cartridge
Cartridge Yield	Approx. 2100 pages ^{1,2}
Page collated print	Yes (Face down print)
Paper output tray capacity	100 sheets
Media Types	Plain, heavy, Recycled, Transparency, Label, Envelope
Media Sizes:	Cassette: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, Postcard, Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 127mm to Max. 216 x 356mm) ADF: A4, B5, A5, B6, Letter, Legal, Statement, Min. 127 x 139.7mm to Max. 216 x 356mm
Printing width	206mm
Toner save mode	Yes
Auto image reduction on reception	Yes (100 to 75% 1% increments)

Transmission and Reception Features

Transmission speed	3 seconds per page with 33.6K bps modem ³
Compression method	MH, MR, MMR
Memory transmission	Yes
FAX memory	512 pages ³
Memory backup	5 mins
Memory reception	Yes
Dual access	Yes
Error correction mode (ECM)	Yes
Delayed transmission	Yes (140 locations)
Sequential broadcast	Max. 140 destinations
Reception	Yes
Sub-address transmission	Yes
Error re-transmission	Yes
Fax transfer	Yes

Security and Management Features

Forced memory reception	Yes
Reports	Activity Management Report (TX/RX), Activity Result Report
Transmission header	Yes
Reception footer	Yes

Telephony Features

One-touch dials	30
Coded dials	100
Group dials	Max. 129 dials
Program dial	Yes
Redial	Yes (automatic and manual)
Dial search	Yes
FAX/TEL auto switch	Yes
Answering machine Hook-up	Yes
Remote reception	Yes
On Hook key	Yes
Telephone handset	Yes
Type	Standard

Copier Features

Copy resolution	TEXT/PHOTO mode, TEXT mode, PHOTO mode: 600 dpi x 600 dpi
Copy speed (Mono)	11.8 pages per minutes
Multiple copy	Up to 99 copies
Zoom	50% - 200% in 1% increments
First copy output time (FCOT)	Less than 22.3 secs

Other Features

Type	5 lines
LCD Display Languages	23 languages: (English/Spanish/French/Italian/ Hungarian/Dutch/Norwegian/Polish/Greek/ Estonian/ Croatian/ Bulgarian/Portuguese/Slovene/ Slovak/ Finnish/Swedish/Turkish/Russian/Czech/ Danish/German/Romanian)
Energy saver key	Yes

Printer Features

Interface	USB 2.0 Hi-Speed
Printer Language	UFR II-LT
Memory	64MB
Printer	Windows 2000/XP/VISTA/7 MAC OS X 10.4.9 - 10.7 ⁴ Linux ^{4,5}
Supplied Drivers	Printer Driver, FAX Driver

General Features

Duty Cycle	Max 8,000 pages per month (TBD)
Warm-Up time	Approx. 14 seconds or less from power on
Recovery time	Approx. 3.5 seconds (TBD)
Dimensions (cassette closed)	
W x H x D	372 x 303 x 303 mm
Installation space	572 x 724 x 520 mm (including trays)
Weight	Approx. 8.8kg
Power consumption	Maximum: 1020W Active: 400W Standby: 10W Sleep: 1.5W Typical Electricity Consumption (TEC): 0.6 kWh/w
Noise Levels	Sound Power: Active: 6.5 B Standby: 4.3 B or less Sound Pressure: Active: 53 dB Standby: Inaudible
Operating Environment	Temperature: 50 to 86°F (10 to 30°C) Humidity: 20% to 80% RH (no condensation)
Power Source	220-240 V (±10%), 50/60 Hz (±2 Hz)

Standard disclaimers. All specifications subject to change without notice

- [1] Based on ISO/IEC 19752
- [2] Ships with 1,000 pages starter cartridge
- [3] Based on ITU-T Standard Chart No. 1
- [4] Web distribution only
- [5] Linux support printing only.



Australia: call 1800 444 199 or visit canon.com.au

New Zealand: call 0800 222 666 or visit canon.co.nz

Achieve more. Beyond technology.