

Fast, efficient and affordable fax for every business



The robust and compact L410 Super G3 laser fax machine, with its large LCD display, fast performance and automatic duplex ADF, is ideal for everyday use within any business.

Key features

- Industry-fastest Super G3 fax modem (33.6kbps)
– 3 seconds per page* transmission
- Space-saving design with large LCD display
- Ultra High Quality 256 grayscale imaging for clearer detail on faxes
- Large 512-page* transmit and receive fax memory
- 39 one-touch and 200 coded speed dials
- 50-sheet Duplex ADF for automatic double-sided copying and faxing
- Fast laser print and copy speed of 25ppm
- No waiting with Quick First-Print from sleep mode
- High energy efficiency
- Handset as standard

*Based on ITU-T Standard Chart No. 1

What's in the Box

Main unit, handset, handset cradle, handset clamp, starter cartridge, power cord, telephone line cable, destination labels, starter guide and warranty card – with user software and manual CDs.

Dimensions (WxDxH)

390mm x 445mm x 358mm

Supported OS

Windows 7 / XP / Vista

Mac OS Version 10.5.8 and up
(Web distribution only)

Linux (Web distribution only)

Achieve more. Beyond technology.

Canon

Specifications

- 1 ADF
- 2 5-line LCD
- 3 250-sheet paper cassette
- 4 Starter Cartridge 328



FAX Unit Type

Type	Standalone facsimile & Laser printer
Compatibility	Group 3
Applicable line	PSTN
Modem speed	33.6K bps (Super G3)
Print technology	Laser beam printing
Scanner type	Duplex Sheet fed

FAX Scanning Features

Automatic document feeder	50 sheets (ADF)
Document size	Width - 216mm (Max), 140mm (Min) Length - 356mm (Max), 127mm (Min)
Effective scanning width	214mm
Scanning speed	Approx. 2.5 sec/page Approx. 20 pages/minute
Fax resolution	Up to 200 x 400 dpi
Image processing system	UHQ (Ultra High Quality)
Halftone	256 shades of grayscale

FAX Printing Features

Printing method	Laser Beam Printing
Print speed	25 pages per minutes
First Print Out Time	5.8 secs
Print resolution	600 x 600 dpi
Print Quality	Up to 1200 x 600 dpi
Paper capacity	250 sheets
Print cartridge	CART328 All in One cartridge
Cartridge Yield	Approx. 2100 pages ^{1,2}
Page collated print	Yes (on reception)
Paper output tray capacity	100 sheets
Media Types	Plain, heavy, Recycled, Transparency, Label, Envelope
Media Sizes:	Cassette: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard, Envelope: COM10, Monarch, C5, DL Min. 76.2 x 148mm to Max. 216 x 356mm ADF: A4, B5, A5, B6, LTR, LGL, STMT Min. 127 x 140mm to Max. 216 x 356mm
Printing width	206mm
Toner save mode	Yes
Auto image reduction on reception	Yes (100 to 75% in 1% increments)

Transmission and Reception Features

Transmission speed	3 seconds per page with 33.6K bps modem ³
Compression method	MH, MR, MMR
Memory transmission	Yes
FAX memory	512 pages ³
Memory backup	Unlimited
Memory reception	Yes
Dual access	Yes
Error correction mode (ECM)	Yes
Delayed transmission	Yes (250 locations)
Sequential broadcast	Max. 249 destinations
Reception	Yes
Sub-address transmission	Yes
Error re-transmission	Yes
Fax transfer	Yes

Security and Management Features

Password user restriction	Yes
Forced memory reception	Yes
Reports	Activity Management Report (TX/RX), Activity Result Report
Transmission header	Yes
Reception footer	Yes

Telephony Features

One-touch dials	39
Coded dials	200
Group dials	Max. 238 dials / Max. 238 destinations
Program dial	Yes
Redial	Yes (automatic and manual)
Dial search	Yes
FAX/TEL auto switch	Yes
Answering machine Hook-up	Yes
Remote reception	Yes
On Hook key	Yes
Telephone handset	Yes
Type	Standard

Copier Features

Copy resolution	TEXT/PHOTO mode, TEXT mode, PHOTO mode: 600 dpi x 600 dpi
Copy speed (Mono)	25 pages per minutes
Multiple copy	Up to 99 copies
Zoom	25% - 400% in 1% increments
First copy output time (FCOT)	Less than 9.0 secs

Other Features

Type	LCD
Size	5 lines
LCD Display Languages	23 languages: (English/Spanish/French/Italian/Hungarian/Dutch/Norwegian/Polish/Greek/Estonian/Croatian/Bulgarian/Portuguese/Slovene/Slovak/Finnish/Swedish/Turkish/Russian/Czech/Danish/German/Romanian)
Energy saver key	Yes

Printer Features

Interface	USB 2.0 Hi-Speed
Printer Language	UFR II-LT
Memory	128MB
Printer	Windows 7/XP/VISTA MAC OS X 10.5.8 and up ⁴ Linux ^{4,5}
Supplied Drivers	Printer Driver, FAX Driver, Address Book Tool

General Features

Duty Cycle	Max 10,000 pages per month
Warm-Up time	Approx. 13.5 seconds or less from power on
Recovery time	Approx. 2.0 seconds
Dimensions (W x D x H)	390 x 445 x 358 mm
Installation space	672 x 904 x 706 mm (including trays)
Weight	Approx. 13.9kg
Power consumption	Maximum: 1320W Active: 560W Standby: 4.5W Sleep: 1.4W Typical Electricity Consumption (TEC): 0.6 kWh/w
Noise Levels	Sound Power: Active: 6.5 B Standby: 4.3 B or less Sound Pressure: Active: 50 dB Standby: Inaudible
Operating Environment	Temperature: 50 to 86°F (10 to 30°C) Humidity: 20% to 80% RH (no condensation)
Power Source	220-240 V (±10%), 50/60 Hz (±2 Hz)

Standard disclaimers. All specifications subject to change without notice

- [1] Based on ISO/IEC 19752
- [2] Ships with 1,000 pages starter cartridge
- [3] Based on ITU-T Standard Chart No. 1
- [4] Web distribution only
- [5] Linux support printing only.



Australia: call 1800 444 199 or visit canon.com.au

New Zealand: call 0800 222 666 or visit canon.co.nz

Achieve more. Beyond technology.

Canon