



imageRUNNER  
ADVANCE  
8505i / 8595i  
8585i **II**

## imageRUNNER ADVANCE 8500 II Series

Black-and-White | High-Volume | Multifunction

Print up to 105 ppm (BW)

Scan up to 240/220 ipm (300 dpi) (BW, color, duplex)

Print up to 13" × 19"

7,700-sheet maximum paper capacity



Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology; better **control** sensitive information and print-related costs; and help ensure that technology investments proactively **evolve** with changing needs.



### WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences with My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive and Box.<sup>1</sup>
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



### SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control who has access to the device, and to which features, using a host of flexible authentication methods – picture login, PIN code, user name/password, or card access.<sup>2</sup>



### COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.<sup>3</sup>
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



## DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



## QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.†



### STAPLE FINISHER-W1 PRO

- 2-tray, 5,000-sheet capacity
- Corner and double stapling up to 100 sheets
- Supports optional internal 2/3-hole puncher (Puncher Unit-BS1)
- Precise output stacking alignment
- Enhanced durability for high volumes



### STAPLE FINISHER-X1

- 3-tray, 4,250-sheet capacity
- Corner and double stapling up to 100 sheets
- Supports optional internal 2/3-hole puncher (Puncher Unit-BF1)



### STAPLE FINISHER-V2 (iR ADV 8585i II only)\*

- 3-tray, 3,500-sheet capacity
- Corner and double stapling up to 65 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



### BOOKLET FINISHER-W1 PRO

- 2-tray, 5,000-sheet capacity
- Corner and double stapling up to 100 sheets
- Booklet-making up to 25 sheets and saddle-folding up to 5 sheets
- Supports optional internal 2/3-hole puncher (Puncher Unit-BS1) and optional booklet trimming (Booklet Trimmer-D1)
- Precise output stacking alignment
- Enhanced durability for high volumes



### BOOKLET FINISHER-X1

- 3-tray, 4,250-sheet capacity
- Corner and double stapling up to 100 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 5 sheets
- Supports optional internal 2/3-hole puncher (Puncher Unit-BF1) and booklet trimming (Inner Booklet Trimmer-A1)



### BOOKLET FINISHER-V2 (iR ADV 8585i II only)\*

- 3-tray, 3,500-sheet capacity
- Corner and double stapling up to 65 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



### DOCUMENT INSERTION UNIT-N1\*

- Insert preprinted sheets
- Up to 13" x 19-1/4"
- Two trays
- 400-sheet total capacity



### MULTI FUNCTION PROFESSIONAL PUNCHER-A1\*

- Supports various die sets
- Up to 140 lb. Index
- Supports 12" x 18", 11" x 17", Legal, Letter, Letter-R, and more
- 70,000-sheet punch tray capacity
- Enhanced die durability



### PAPER FOLDING UNIT-J1\*

- Z-fold, C-fold, Half-fold, Accordion Z-fold, Double-parallel Fold



UPRIGHT CONTROL PANEL\*\*

UTILITY TRAY-BI



### PAPER DECK UNIT-E1

- 3,500-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports LTR



### POD DECK LITE-C1

- 3,500-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports up to 13" x 19"
- User adjustable



### imagePASS-Y2

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalized printing with the built-in, entry-level Fiery FreeForm™ or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI™ management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules

\* Staple Finisher-V1 and Booklet Finisher-V1 are not compatible with Document Insertion Unit-J1, Multi Function Professional Puncher-A1, and Paper Folding Unit-J1.

\*\* Upright control panel standard on imageRUNNER ADVANCE 8505i/8595i models. The imageRUNNER ADVANCE 8585i comes standard with a flat control panel. An optional upright control panel is available.

# SPECIFICATIONS

## Main Unit

**Type**  
Monochrome Laser Multifunctional

### Core Functions

Standard: Print, Copy, Scan, Send, Store  
Optional: Fax

### Processor

Canon Dual Custom Processor (Shared)

### Control Panel

Standard for  
iR ADV 8585i II: 10.1" TFT LCD WSVGA Color Flat-panel  
Standard for  
iR ADV 8595i II, 8505i II: 10.4" TFT LCD SVGA Color Upright-panel  
Optional for  
iR ADV 8585i II: 10.4" TFT LCD SVGA Color Upright-panel

**Memory:** 3.0 GB RAM

### Hard Disk Drive

Standard: 250 GB  
Maximum: 1 TB

### Interface Connection

Network 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)

### Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

### Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 1,500-sheet Paper Drawers, Dual  
550-sheet Paper Cassettes, 100-sheet  
Stack Bypass

Optional: 3,500-sheet Paper Deck (POD DECK  
LITE-C1 or PAPER DECK UNIT-E1)

### Paper Capacity (LTR, 20 lb. Bond)

Standard: 4,200 Sheets  
Maximum: 7,700 Sheets

### Paper Output Capacity (LTR, 20 lb. Bond)

With External  
Finishers (-V1): 3,500 Sheets

With External  
Finishers (-X1): 4,250 Sheets

With External  
Finishers (-WI PRO): 5,000 Sheets

### Finishing Capabilities

With External  
Finishers: Collate, Group, Offset, Staple,  
Booklet, Booklet Trimming, Hole Punch,  
Professional Hole Punch, Document  
Insertion, Folding (C, Z,  
Half, Accordion Z, Double-parallel)

### Supported Media Types

Paper Drawers (1/2): Thin, Plain, Recycled, Color, Heavy,  
Pre-punched, Letterhead, Bond  
Paper (3/4): Thin, Plain, Recycled, Color, Heavy,  
Cassettes (3/4): Pre-punched, Letterhead, Bond, Tab<sup>5</sup>  
Stack Bypass: Thin, Plain, Recycled, Color, Heavy,  
Pre-punched, Bond, Transparency,  
Labels, Letterhead, Tab, Tracing<sup>5</sup>

POD DECK LITE-C1: Thin, Plain, Recycled, Color, Heavy,  
Pre-punched, Letterhead, Bond,  
Transparency, Labels, Tab

PAPER DECK  
UNIT-E1: Thin, Plain, Recycled, Color, Heavy,  
Pre-punched, Letterhead, Bond

### Supported Media Sizes

Paper Drawers (1/2): Letter  
Paper Cassettes (3/4): 13" x 19", 12-5/8" x 17-11/16", 12" x 18",  
11" x 17", Legal, Letter, Letter-R,  
Executive, Statement-R, Custom  
Size (5-1/2" x 7-1/8" to 13" x 19-1/4")  
13" x 19", 12-5/8" x 17-11/16", 12" x 18",  
11" x 17", Legal, Letter, Letter-R,  
Executive, Statement-R, Custom  
Size (5-1/2" x 7-1/8" to 13" x 19-1/4")

Stack Bypass: 13" x 19", 12-5/8" x 17-11/16", 12" x 18",  
11" x 17", Legal, Letter, Letter-R,  
Executive, Statement-R, Custom  
Size (4 x 5-7/8" to 13" x 19-1/4"),  
Free Size (4" x 7-1/4" to 13" x 19-1/4")

POD DECK LITE-C1: 13" x 19", 12-5/8" x 17-11/16", 12" x 18",  
11" x 17", Legal, Letter, Letter-R,  
Executive, Statement-R, Custom  
Size (5-1/2" x 7-1/8" to 13" x 19-1/4")  
Letter

PAPER DECK  
UNIT-E1: Letter

### Supported Media Weights

Paper Decks/ Cassettes: 14 lb. Bond to 80 lb. Cover  
(52 to 220 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 140 lb. Index  
(52 to 256 g/m<sup>2</sup>)  
Duplexing: 14 lb. Bond to 80 lb. Cover  
(52 to 220 g/m<sup>2</sup>)

### Warm-up Time<sup>7</sup>

From Power On: 60 Seconds or Less  
From Sleep Mode: 60 Seconds or Less

### Dimensions (W x D x H)

8505i II/ 8595i II: 58-3/8" x 30-3/8" x 49-1/4"  
(1481 mm x 770 mm x 1252 mm)  
8585i II: 26-3/8" x 30-5/8" x 48"  
(670 mm x 779 mm x 1220 mm)

### Installation Space (W x D)

Fully Configured: 161-3/8" x 63-5/8" (4098 mm x 1617  
mm) (POD DECK LITE-C1 + BOOKLET  
FINISHER-W1 PRO + DOCUMENT  
INSERTION UNIT-N1 + PAPER FOLDING  
UNIT-J1 + BOOKLET TRIMMER-D1)

### Weight

8505i II/ 8595i II: Approx. 529.1 lb. (240 kg)<sup>8</sup>  
8585i II: Approx. 520.3 lb. (236 kg)<sup>8</sup>

## Print Specifications

### Print Speed

8505i II: Up to 105 ppm (Letter)  
Up to 81 ppm (Letter-R)  
Up to 63 ppm (Legal)  
Up to 53 ppm (11" x 17")  
8595i II: Up to 95 ppm (Letter)  
Up to 73 ppm (Letter-R)  
Up to 60 ppm (Legal)  
Up to 49 ppm (11" x 17")  
Up to 85 ppm (Letter)  
Up to 67 ppm (Letter-R)  
Up to 57 ppm (Legal)  
Up to 43 ppm (11" x 17")  
8585i II: Up to 85 ppm (Letter)  
Up to 67 ppm (Letter-R)  
Up to 57 ppm (Legal)  
Up to 43 ppm (11" x 17")

### Print Resolution (dpi)

1200 x 1200, 600 x 600

### Standard Page Description Languages

UFR II, PCL6, Adobe PS 3

### Direct Print

Available from USB, Advanced Box, Remote UI,  
and Web Access<sup>9</sup>

### Supported File Types

PDF, TIFF, JPEG, EPS,<sup>10</sup> XPS

### Printing from Mobile and Cloud

A range of software and MEAP-based solutions are  
available to provide printing from mobile devices or  
Internet-connected devices and cloud-based services  
depending on your requirements.

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR  
fonts, Andalé Mono WT J/K/S/T  
(Japanese, Korean, Simplified  
and Traditional Chinese)<sup>11</sup>

PS fonts: 136 Roman

### Operating System<sup>12</sup>

UFR II: Server 2008/Windows 7/Server 2008 R2/  
Server 2012/Windows 8.1/  
Server 2012 R2/Windows 10/Server 2016,  
MAC OS X (10.7 or later)  
PCL: Server 2008/Windows 7/Server 2008 R2/  
Server 2012/Windows 8.1/  
Server 2012 R2/Windows 10/Server 2016  
PS: Server 2008/Windows 7/Server 2008 R2/  
Server 2012/Windows 8.1/  
Server 2012 R2/Windows 10/Server 2016,  
MAC OS X (10.7 or later)

## Copy Specifications

### Copy Speed

8505i II: Up to 105 ppm (Letter)  
Up to 81 ppm (Letter-R)  
Up to 63 ppm (Legal)  
Up to 53 ppm (11" x 17")  
8595i II: Up to 95 ppm (Letter)  
Up to 73 ppm (Letter-R)  
Up to 60 ppm (Legal)  
Up to 49 ppm (11" x 17")  
8585i II: Up to 85 ppm (Letter)  
Up to 67 ppm (Letter-R)  
Up to 57 ppm (Legal)  
Up to 43 ppm (11" x 17")

**First-Copy-Out Time:** As Fast as 2.7 Seconds

### Copy Resolution (dpi)

Reading: 600 x 600  
Printing: 1200 x 1200

**Multiple Copies:** Up to 9,999

**Magnification:** 25%-400% (1% Increments)

**Preset Reductions:** 25%, 50%, 64%, 73%, 78%

**Preset Enlargements:** 121%, 129%, 200%, 400%

### Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper  
Setting, Previous Settings, Favorite Settings, Finishing, Two-  
Sided, Density Adjustment, Original Type Selection, Interrupt  
Mode, Setting Confirmation/Cancel

### Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet,  
Job Build, N on 1, Add Cover, Insert Sheets, Different-size  
Originals, Density Adjustment, Original Type Selection,  
Transparency Cover Sheets, Page Numbering, Copy Set  
Numbering, Sharpness, Erase Frame, Secure Watermark,  
Print Date, Shift, Gutter, Print & Check, Negative/Positive,  
Repeat Images, Merge Job Blocks, Job Done Notice, Mirror  
Image, Print on Tab, Store in Mail Box, Superimpose Image,  
Cascade Copy, Copy ID Card, Multi Sheet Feed Detection,  
Free Size Original

## Scan Specifications

### Type

Color Platen and Single-pass Duplexing Automatic Document  
Feeder

### Document Feeder Paper Capacity

300 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

### Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 80 lb. Cover (50 to 220 g/m<sup>2</sup>)  
Color Original: 17 lb. Bond to 80 lb. Cover (64 to 220 g/m<sup>2</sup>)

### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

### Pull Scan

Color Network ScanGear2 for both Twain and WIA  
Supported Windows Vista/7/8.1/10  
OS: Server 2008/Server 2008 R2/Server 2012/  
Server 2012 R2/Server 2016

### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400,  
200 x 200, 200 x 100, 150 x 150, 100 x 100

### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to  
mobile devices or and cloud-based services depending  
on your requirements.

### Scan Speed (Letter)

Single-sided Scanning  
BW: 120 ipm (300 dpi)/120 ipm (600 dpi)  
Color: 120 ipm (300 dpi)/60 ipm (600 dpi)  
Double-sided Scanning  
BW: 240 ipm (300 dpi)/150 ipm (600 dpi)  
Color: 220 ipm (300 dpi)/60 ipm (600 dpi)

## Send Specifications

### Destination

E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box,  
Super G3 Fax (Optional), IP Fax (Optional)

### Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

### Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,  
200 x 100, 150 x 150, 100 x 100

### Communication Protocol

File: FTP, SMB v3.0, WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

### File Format

Standard: TIFF, JPEG, PDF (Encrypted, Compact,  
Searchable, Apply Policy, Optimize for Web,  
PDF A/1-b), Encrypted XPS (Compact,  
Searchable), Office Open XML (PowerPoint,  
Word), Digital Signature (PDF/XPS)

Optional: PDF (Trace & Smooth)

## Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

## Fax Specifications (Optional)

### Modem Speed

Super G3: 33.6 Kbps  
G3: 14.4 Kbps

**Compression Method:** MH, MR, MMR, JBIG

### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

**Sending/Recording Size:** Statement-R to 11" x 17"

**Fax Memory:** Up to 30,000 Pages

**Speed Dials:** Max. 200

**Group Dials/Destinations:** Max. 199 Dials

**Sequential Broadcast:** Max. 256 Addresses

**Memory Backup:** Yes

### Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Multi Sheet Feed Detection

## Store Specifications

### Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows (Windows Vista/7/8/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)

Approx. 480 GB (Optional 1TB HDD)

### Advanced Box Features

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

### Memory Media

Standard: USB

## Security Specifications

### Authentication

**Standard:** Universal Login Manager, Cloud Authentication,<sup>13,14</sup> User Authentication, Department ID Authentication, (Device and Function Level Log-in), Access Management System  
**Optional:** uniFLOW

### Data

**Standard:** Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated)  
**Optional:** Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

**Standard:** Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

### Document

**Standard:** Secure Watermark, Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature,  
**Optional:** User Signatures, Document Scan Locking

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86 °F  
Humidity: 20 to 80 % RH (no condensation)

### Power Requirements

120-127 V AC, 60 Hz, 16 A

### Plug (Main Unit)

NEMA 5-20P

### Power Consumption

Maximum: Approx. 2.1 KW

Standby: Approx. 239 Wh

Energy Saver

Mode: Approx. 202 Wh

Sleep Mode: Approx. 0.9 W or less<sup>15</sup>

Typical Electricity Consumption (TEC) Rating:

iR ADV 8505i II: 10.5 kWh

iR ADV 8595i II: 9.8 kWh

iR ADV 8585i II: 9.0 kWh

### Standards

ENERGY STAR® Certified

Rated EPEAT® Gold<sup>4</sup>

EU RoHS Compliant

Ecomark

## Consumables

**Toner:** GPR-37 BLACK TONER

**Toner Yield (Estimated @ 6% Coverage):** 70,000 Images

<sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

<sup>2</sup> Requires additional option.

<sup>3</sup> Available 2Q 2018.

<sup>4</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit [www.epeat.net](http://www.epeat.net).

<sup>5</sup> Tab paper can be fed from Paper Cassettes (3/4) when the optional Tab Feeding Attachment Kit-B1 is installed.

<sup>6</sup> Some types of tracing paper cannot be used.

<sup>7</sup> Warm-up time shown for when "Quick Startup Settings for Main Power" is set to "OFF". For significantly faster warm-up set "Quick Startup Settings for Main Power" to "ON".

<sup>8</sup> Including the toner bottle.

<sup>9</sup> PDF print from Websites is supported.

<sup>10</sup> EPS can be printed directly only from the Remote User Interface.

<sup>11</sup> Requires the optional PCL International Font Set-A1.

<sup>12</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>13</sup> No charge for this solution; however activation is required.

<sup>14</sup> Check for availability.

<sup>15</sup> 0.9 W sleep mode not available in all circumstances due to certain settings.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE 8500 Series Specifications document.

 USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. It indicates that this model has been upgraded to new system software and includes additional security features as standard. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.  
©2018 Canon U.S.A., Inc. All rights reserved.

0210W709  
0418R1-iRA8500IISRSB-PDF-IH

 UNIFIED FIRMWARE PLATFORM



 CANON  
GENUINE  
TONER, CARTRIDGE  
& PARTS

