

geRUNNER 1643IF

FAST SCANNING AND Advanced mobile Connectivity

imageRUNNER 1643iF II

Black & White Multifunction Laser Printer 🔘 🗨

Small businesses and corporate workgroups depend on solutions that help maximise resources, boost productivity, and are easy to manage. The cost-efficient imageRUNNER 1643iF II can do all that, and more. With fast output, scanning, faxing, and high reliability, this multifunction device helps you accomplish a lot in a small space.

E V PERFORMANCE

With a first-copy-out time as fast as 6.3 seconds and output up to 43 ppm, the imageRUNNER 1643iF II is a quick performer. Scan documents in black and white and colour to email addresses or networked locations. The 5" intuitive, colour touchscreen display has smartphone-like usability. The standard 650-sheet capacity can be increased to 2,300 sheets to handle many jobs without interruption.

SECURITY

Canon's uniFLOW® solution lets users securely retrieve documents from any networked device after authentication. Standard security features include the ability to send encrypted PDFs and add a digital device signature to PDF files. The imageRUNNER 1643iF II also has TLS 1.3 support which uses the latest encryption technology to protect data on the network from leaking, tampering and spoofing.



Canon

Designed with your bottom line in mind, the Canon imageRUNNER 1643iF II helps minimise costs and maximise reliability while the robust design helps ensure dependable operation. Canon's uniFLOW® software can help control costs by managing, tracking, and charging back usage. And simple-to-replace, high-yield consumables help keep work moving while achieving a low cost per page.





imageRUNNER 1643iF II SPECIFICATIONS

| Printing Method | Monochrome Laser Beam Printing |
|---|---|
| Print Speed | Single sided: Up to 43 ppm (A4) |
| | Double sided: Up to 36 ppm (A4) |
| Print Resolution (Max.) | 600 × 600 dpi |
| Print Quality with Image Refinement Technology | Up to 1200 × 1200 dpi |
| Narm-up Time (from Power On) | Quick startup OFF: 30 sec or less Quick startup ON: 3 sec or less |
| First Printout Time (FPOT) | Approx: 6.2 sec or less |
| Recovery Time (From Sleep Mode) | 3 sec or less |
| Print Language | UFRII, PCL 5e, PCL6, Adobe® PostScript |
| Auto Duplex Print | Standard |
| Available Paper Size for Auto Duplex Print | A4, Legal, Letter, Foolscap, Indian Legal |
| JSB Direct Print | Supported File Format: JPEG, TIFF, PDF |
| Print Margins | 5 mm – top, bottom, left and right (Envelope: 10 mm) |
| Print Features | Poster, Booklet, Watermark, Page Composer, Toner Saver |
| Advanced Printing Features | Secure Print; Print from USB memory key (JPEG/TIFF/PDF); Barcode Print; iOS: AirPrint, Canon PRINT Business app; Android; Mopria certified, Canon PRINT Business app, Canon Print Service Plug-in |
| Сору | |
| Copy Speed | Single sided (A4): Up to 43 ppm Double sided (A4): Up to 34.4 ppm |
| Copy Resolution | 600 × 600 dpi |
| First Copy Time (FCOT) | ADF (A4): Approx. 6.4 sec or less; Platen (A4): Approx. 6.3 sec or less |
| Maximum Number of Copies | Up to 999 copies |
| Reduce/Enlargement | 25–400% in 1% increments |
| Copy Features | Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy |
| Scan | |
| Scan Resolution | Laser Resolution: Up to 600 × 600 dpi Smoothing Resolution: 1200 × 1200 dpi |
| Scan Type | Colour Contact Image Sensor |
| Maximum Scan Size | Platen Glass: Up to 215.9 × 355.6 mm Feeder: Up to 215.9 × 355.6 mm |
| Scan Speed | Single sided mono: 38 ipm (300 × 600 dpi) Single sided colour: 13 ipm (300 × 600 dpi) Double sided mono: 70 ipm (300 × 600 dpi) Double sided colour: 26 ipm (300 × 600 dpi) |
| Colour Depth | 24-bit |
| Pull Scan | Yes, USB and Network |
| Push Scan (Scan to PC) with MF Scan Utility | Yes, USB and Network |
| Scan to USB (via USB Host 2.0) | Yes |
| Scan to Cloud | Through MF Scan Utility, TIFF/JPEG/PDF/PNG |
| Scan Driver Compatibility | TWAIN, WIA |
| Scan to E-Mail | TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF3/PDF (Digital signature) |
| Send | |
| Send Method | SMB, Email, FTP, iFAX Simple |
| Colour Mode Scan Resolution | Full Colour, Grayscale, Monochrome |
| | Stream Reading: 300 × 600 dpi No Stream Reading: 600 dpi × 600 dpi |
| File Format | JPEG, TIFF, PDF, Compact PDF, PDF (OCR) |
| Fax | |
| Modem Speed | Up to 33.6 Kbps |
| Fax Resolution | Standard: 200 × 100 dpi Fine: 200 × 200 dpi Super fine: 200 × 400 dpi Ultra fine: 400 × 400 dpi |
| Compression Method | MH, MR, MMR, JBIG |
| Memory Capacity | Up to 512 pages |
| avourite Dials (in Address Book) | 19 dials |
| Speed Dials (Coded Dials) | Up to 281 dials |
| Group Dials/Destination | Max. 299 dials/Max. 299 destinations |
| Sequential Broadcast | Max. 310 destinations |
| Receive Mode | Fax Only, Manual, Answering, Fax/Tel Auto Switch |
| Memory Backup Fax Features | Permanent fax memory backup. (Backup with flash memory) Fax Forwarding, Dual Access, Remote Reception, PC Fax |
| | (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports |
| Transmission Time | Approx. 2.6 sec |
| | |

| Paper Input (Based on 80 gsm) | 550-sheet cassette |
|---------------------------------|---|
| | 100-sheet multi-purpose tray 50-sheet ADF |
| Maximum Paper Capacity | 2,300 sheets |
| Paper Output | 250 sheets |
| Paper Size | Cassette (standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, LTR, LGL, Foolscap, Custom sizes: Min. 105 × 148 mm; Max. 216.0 × 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, GLTR, GLGL, Foolscap, Post card, Index card, Envelope (COM10, Monarch, C5, DL); Custom sizes: Min. 76.2 × 127 mm; Max. 216.0 × 355.6 mm. DF: A4, A5, A6, B5, Legal, Letter, Statement; Custom sizes: Min. 105 × 128 mm Max. 215.9 × 355.6 mm. |
| Paper Type | Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope |
| Paper Weight | Cassette (standard and optional): 60 to 120 gsm Multi-purpose tray: 60 to 199 gsm ADF: 50 to 105 gsm |
| Connectivity and Software | |
| Standard Interfaces | USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection |
| Network Protocol | Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPv4, IPv6) Scan: Email, SMB, WSD-Scan (IPv4, IPv6), FTP-Scan, IFAX TCP/IP Application Services: Bonjour (mDNS), HTTP, HTTP, S POP before SMTP (IPv4, IPv6), DHCP, ARP+PING, Auto IP, WINS (IPv4), DHCPv6 (IPv6) Management: SNMPv1, SNMPv3 (IPv4, IPv6) |
| Network Security | Wired: IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS) Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AES) TLS 1.3 Support |
| One-Push Wireless Configuration | Wi-Fi Protected Setup (WPS) |
| Other Features | Department ID, Secure Print, Application Library |
| Mobile Solution | Canon PRINT Business, Canon Print Service, Google Cloud Print™, Apple® AirPrint™, Mopria® Print Service |
| Address Book | LDAP |
| Compatible Operating Systems | Windows® 10/Windows® 8.1/Windows® 7/Server® 2019/ Server® 2016/Server® 2012 R2/Server® 2012/Server® 2008 R2/Server® 2008 Mac OS X version 10.9.5 and up/Mac OS 10.14; Linux |
| Software Included | MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager/uniFLOW online/uniFLOW online Express/ uniFLOW Compatibility, Application Library |
| General | |
| Device Memory | 1GB |
| LCD Display | WVGA Colour LCD 5.0" Touch Screen Display |
| Dimensions (W × D × H) | 494 mm × 464 mm × 452 mm |
| Weight | 19.8 kg |
| Power Consumption | Maximum: Approx. 1420 W or less Standby: Approx. 13.6 W Sleep mode: Approx. 0.7 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V) |
| Noise Level | Sound Pressure: Active: 54 dB; Standby: 24 dB Sound Power: Active: 72.9 dB; Standby: Inaudible |
| Operating Environment | Temperature: 10–30°C Humidity: 20–80% RH (No Condensation) |
| Power Requirement | AC 220–240 V(±10%), 50/60 Hz(±2 Hz) |
| Optional Accessories | |
| Paper Feeder | Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1, Barcode Printing Kit-E1 |
| | |



Canon Australia Pty Ltd 1800 444 199 canon.com.au/business Canon New Zealand Ltd 0800 222 666

