

No one does it
like *you*

Canon

OUR CLEVER PRINT AND SCAN SOLUTION JUST GOT SMARTER AND MORE SECURE

CANON imageRUNNER ADVANCE
8505 / 8595 / 8585



The Canon imageRUNNER ADVANCE 8500 Series is one of the first in our Gen III portfolio and introduces print and scan capabilities that are powerful, intuitive and highly secure.

Expanding on the scan and print capabilities of previous versions, these easy-to-use models save time and resources, increase productivity and offer advanced user authentication to better manage print and document costs.

The latest models come complete with enhance **security features**, such as System verification and secure boot from start up, that checks for modifications to boot code, OS, firmware and MEAP applications once device is on. As well as a **superior user interface**, with the Main menu and quick menu screens combined into one home screen, comprising on integrated menu and timeline, for enhanced operability.



COST CONTROL

- Standard Universal Login Manager (NEW)
- Forced reservation printing
- Skips blank pages from printing



SUSTAINABILITY

- Remote shutdown/weekly timer
- More energy efficiency
- Reduced CO² emissions
- 100% recycled plastics
- ENERGY STAR rating



AT A GLANCE

- Motion sensor technology with three sensitivity settings
- New user interface with smartphone technology
- Up to 105 prints per minute



SECURITY

- Standard HDD Data Encryption (NEW)
- HDD Data Erase
- International standard for MFD security
- Standard HDD Encryption works to prevent data leaks and keep confidential information protected
- Security settings have been consolidated to reduce administration
- Security policy support is also available



PERFORMANCE

- New user interface
- High print volume
- Enhanced scan/fax capabilities
- Simple consumable replacement with video guide



INTEGRATION

- Collaborates with key Canon software solutions
- Scanning to Office Open XML
- New Standard Universal Login Manager with Access Management System integration



imageRUNNER ADVANCE 8505 / 8595 / 8585 SPECIFICATIONS



Main Unit	
Machine type	A3 Monochrome Laser Multifunctional
Core functions	Print, Copy, Scan, Send, Store and Optional Fax
Processor Speed	Canon Dual Custom Processor (Shared)
Control Panel	Standard: 25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel Optional: 26.4 cm (10.4 inch) TFT LCD SVGA Colour Upright Touch panel
Memory	Standard: 3.0 GB RAM
Hard Disk Drive	Standard: 250 GB, Maximum: 1TB
Mirroring Hard Disk Drive	Optional: 250 GB, 1TB
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy Others Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device), Optional: Serial Interface, Copy Control Interface
Paper Supply Capacity (A4, 80 gsm)	Standard: 4,200 sheets 1,500-sheet Paper Deck x 2, 550-sheet Paper Cassette x 2, 100-sheet Multi-purpose tray Maximum: 7,700 sheets (with 3,500 sheets POD Deck Lite-C1 or Paper Deck Unit-E1)
Paper output capacity (A4, 80 gsm)	250 sheets (with Copy Tray-R2). Maximum: 5,000 sheets (High-Volume Stack mode "ON" with Staple Finisher-W1 PRO or Booklet Finisher-W1 Pro)
Finishing capabilities	Standard: Collate, Group With External finisher: Collate, Group, Offset, Staple, Staple On Demand, Staple-free Staple ^{*1} , Saddle Stitch ^{*2} , Trimming ^{*3} , Hole Punch ^{*4} , Professional Hole Punch (multiple patterns) ^{*5} , Document Insertion ^{*6} , Fold ^{*7} (C, Z, Half, Accordion Z, Double-parallel) ^{*1} Requires Staple Finisher-V2 or Booklet Finisher-V2 ^{*2} Requires Booklet Finisher-V2, Booklet Finisher-X1 or Booklet Finisher-W1 Pro ^{*3} Requires Inner Booklet Trimmer-A1 (with Booklet Finisher-X1) or Booklet Trimmer-F1 (with Booklet Finisher-W1 Pro) ^{*4} Requires 2/3 Hole Puncher Unit-A1, 2/4 Hole Puncher Unit-A1 or 4 Hole Puncher Unit-A1 (with Staple Finisher-V2/Booklet Finisher-V2), Puncher Unit-BF1, Puncher Unit-BG1 or Puncher Unit-BH1 (with Staple Finisher-X1 or Booklet Finisher-X1), Puncher Unit-BS1, Puncher Unit-BT1 or, Puncher Unit-BU1 (with Staple Finisher-W1 Pro or Booklet Finisher-W1 Pro) ^{*5} Requires Multifunctional Professional Puncher-B1 (with Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 Pro or Booklet Finisher-W1 Pro) ^{*6} Requires Document Insertion Unit-N1 (with Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 Pro or Booklet Finisher-W1 Pro) ^{*7} Requires Paper Folding Unit-J1 (with Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 Pro or Booklet Finisher-W1 Pro) Note: Staple Finisher-V2/Booklet Finisher-V2: imageRUNNER 8585i III only
Supported media types	Upper Left/Right Decks (1/2): Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond Lower Cassettes (3/4): Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Tab* *Requires Tab Feeding Attachment-B1 Multi-purpose tray: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Bond, Transparency, Labels, Letterhead, Tab, Tracing* * Some types of tracing paper cannot be used.
Supported media sizes	Upper Left/Right Deck (1/2): Standard size: A4, B5 Paper Cassettes (3/4): Standard size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R Custom size 139.7 x 182.0 mm to 330.2 x 487.7 mm Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 100.0 x 148.0 mm to 330.2 x 487.7 mm Free size: 100.0 x 182.0 mm to 330.2 x 487.7 mm
Supported media weights	Paper Decks/ Paper Cassettes: 52 to 220 gsm Multi-purpose tray: 52 to 256 gsm Duplex: 52 to 220 gsm
Warm-up Time	From Power On: 60 Seconds or Less* *Time from device power-on, until copy ready (not print reservation) From Sleep Mode: 60 Seconds or Less
Dimensions (W x D x H)	Standard: 670 x 779 x 1,220 mm With optional Upright touch panel: 1,481 x 770 x 1,252 mm
Installation Space (W x D)	Basic: 1,533 x 1,353 mm (with Multi-purpose tray/upper-right cover open + Front cover open + Copy Tray) Fully configured: 5,068 x 1,400 mm (with POD Deck Lite-C1 + Document Insertion Unit-N1 + Multi Function Professional Puncher-B1 + Paper Folding Unit-J1 + Booklet Finisher-W1 Pro + Booklet Trimmer-F1)
Weight*	Standard (with flat touch panel): Approx. 236 kg With optional Upright touch panel: Approx. 240 kg * Including toner

Print Specifications

Print Speed* (ppm)	iR-ADV 8505 III up to 105 (A4), up to 54 (A3), up to 76 (A4R), up to 105 (A5R) (*simplex) iR-ADV 8595 III up to 95 (A4), up to 50 (A3), up to 69 (A4R), up to 95 (A5R) iR-ADV 8585 III up to 85 (A4), up to 44 (A3), up to 63 (A4R), up to 85 (A5R)
Print Resolution (dpi)	1,200 x 1,200* *Laser resolution
Page description languages	Standard: UFR II, Optional: PCL 6, Adobe PS 3
Direct Print	Available from USB memory, Advanced box, Remote UI and Web Access* Supported file types: PDF, TIFF, JPEG, EPS and XPS. *Only PDF print from websites is supported.
Printing from mobile and cloud	A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information

Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT/J/K/S/T ^{*1} (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts ^{*2} PS fonts: 136 Roman ^{*1} Requires optional PCL International Font Set-A1 ^{*2} Requires optional Barcode Printing Kit-D1
Print Features	Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/ Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing
Operating System	UFR II: Windows 7 / 8.1/10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.9 or later) PCL: Windows 7 / 8.1/10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 PS: Windows 7 / 8.1/10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.9 or later) PPD: MAC OS X (10.3.9 or later), Windows 7 / 8.1/ 10

Copy Specifications

Copy Speed (ppm)	iR-ADV 8505 III up to 105 (A4), up to 54 (A3), up to 76 (A4R), up to 105 (A5R) iR-ADV 8595 III up to 95 (A4), up to 50 (A3), up to 69 (A4R), up to 95 (A5R) iR-ADV 8585 III up to 85 (A4), up to 44 (A3), up to 63 (A4R), up to 85 (A5R)
First-Copy-Out Time (A4)	Approx. 2.7 seconds
Copy resolution (dpi)	600 x 600
Multiple Copies	Up to 9,999 copies
Copy Exposure	Automatic or Manual (9 Levels)
Magnification	25% - 400% (1% Increments)
Preset Reductions	25%, 50%, 61%, 70%, 81%, 86%
Preset Enlargements	115%, 122%, 141%, 200%, 400%
Basic Copy Features	Preset R/E Ratios by Area, Paper Setting, Previous Setting, Favourite Setting, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel
Special Copy Features	Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Cascade Copy, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original

Scan Specifications

Type	Colour flatbed plus Single-pass duplex automatic document feeder* (1-Pass duplex scan) [2-sided to 2-sided (Automatic with DADF)] * Detect Feeder Multi Sheet Feed is supported.
Document Feeder Paper Capacity(80gsm)	300 Sheets
Acceptable originals and weights	Platen: Sheet, Book, 3-Dimensional Objects (Height: Up to 50 mm, Weight: up to 2kg) Document Feeder media weight: 1-sided scanning: 38 to 220 g/m ² (BW), 64 to 220 g/m ² (CL) 2-sided scanning: 50 to 220 g/m ² (BW), 64 to 220 g/m ² (CL)
Supported media sizes	Platen: max. scanning size: 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R, Custom size: 128.0 x 139.7 mm to 304.8 x 431.8 mm
Scan Speed (ipm; BW/CL; A4)	1-sided Scanning: 120/120 (300 dpi, Send), 120/- (600 dpi, Copy) 2-sided Scanning: 240/220 (300 dpi, Send), 150/- (600 dpi, Copy)
Scan Resolution (dpi)	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
Pull Scan Specifications	Colour Network ScanGear2. For both Twain and WIA Supported OS: Windows 7/8.1/10/ Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016
Scan Method	Send functionality available on all models Scan to USB Memory Key: Available on all models Scan to Mobile Devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices or cloud-based services depending on your requirements. Please contact your sales representative for further information. TWAIN/WIA Pull scanning available on all models

Send Specifications

Destination	E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (optional), IP Fax (optional)
Address Book	LDAP (2,000)/Local (1,600)/ Speed dial (200)
Send resolution (dpi)	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
Communication protocol	File: FTP(TCP/IP), SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3
File Format	Standard: TIFF, JPEG, PDF (Compact, Apply Policy, Optimise for Web, PDF A/1-b, Encrypted, Device Signature), XPS (Compact, Device Signature) Optional: PDF (Trace & Smooth, Searchable, User Signature), XPS (Searchable, User Signature), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages, Detect Feeder Multi Sheet Feed

Fax Specifications

Maximum Number of Connection Lines	4
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size	A3, A4, A4R, A5 ^{*1} , A5R ^{*1} , B4, B5 ^{*2} , B5R ^{*1} ^{*1} Sent as A4 ^{*2} Sent as B4
FAX memory	Up to 30,000 pages
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
Fax Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density (for Scanning), Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line , Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

Store Specifications

Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows 7/8.1/10) Concurrent Connections (Max.): SMB: 64, WebADV: 3 (Active Sessions)
Advanced Box Available Disc Box	Approx. 16GB (Standard HDD) Approx. 480GB (Optional: 1TB HDD)
Advanced Box Features:	Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support
Memory Media	Standard: USB Memory

Security Specifications

Authentication	Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in, uniFLOW Online Express Optional: uniFLOW, uniFLOW Online
Data	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)
Network	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME
Document	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks Optional: User signature, Document Scan lock

Environmental Specifications

Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH
Power source	220-240 V (±10 %), 50/60 Hz (±2 Hz), 10 Amp
Power consumption	Maximum: Approx. 2,400 W Standby: Approx. 219.8 W ^{*1} Sleep mode: Approx. 0.9 W or less ^{*2} ^{*1} Reference value: measured one unit ^{*2} 0.9W sleep mode may not be possible in all circumstances due to certain settings

Consumables

Toner Cartridge/s	NPG-53 TONER BLACK
Toner (Estimated Yield @6% Coverage)	NPG-53 TONER BK: 70,000 pages

Software and Printer Management

Tracking and reporting	Universal Login Manager (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device. uniFLOW Online Express: Combining with ULM you can gain further control and highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud based location.
Remote management tools	iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUJ) Web based interface to each device that helps to provide remote device management and control
Scanning software	Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device
Optimisation tools	Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers NetSpot Device Installer: Simple utility software that allows you to make network protocol settings for Canon devices connected to your network.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services
Document Publishing	IW DESKTOP: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation

Fiery Print Controller Specification

Optional/Standard	Optional on all models
Name	imagePASS-Y3 (External)
Print Resolution (dpi)	1200 x 1200, 600 x 600

Standard Page Description Language(s)	PCL6, Adobe PostScript 3
Memory	8GB (2 x4GB)
Hard Disk Drive	500 GB SATA
Processor	Intel Pentium G4400 (3.3 GHz)
System	Fiery FS350Pro
Fonts	PS: 138 Fonts PCL: 113 Fonts

Supported Operating Systems	Windows 7 32 and 64 bit / Windows 8.1 32 and 64 bit / Windows 10 32 and 64 bit / Windows Server 2012 64bit only / Windows Server 2012 R2 64bit only / Windows Server 2016 R2 64 bit only, MAC OS (10.11, 10.12, 10.13, 10.14)
-----------------------------	---

Interface	2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB 3.0 x 2 (rear), x 3 (front on Fiery Quick Touch TM), USB 2.0 x4 (rear)
-----------	---

Network protocols	TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNT, 802.1X, DHCP, DNS, NTP)
-------------------	---

Direct Print	PDF1.7, EPS, TIFF6, JDF1.4/JMF(OP)
--------------	------------------------------------

VDP	FreeForm v1, v2.1, PPML, PDF/VT-1, PDF/VT-2, Creo VPS
-----	---

Standard Features	Fiery Command WorkStation6 / Paper Catalog, Fiery Remote Scan / Fiery Hot Folders & Virtual Printers / Fiery JDF
-------------------	--

Fiery Print Controller Options	Fiery Impose / Fiery Compose / Fiery Impose and Compose / Removable HDD kit / Fiery Image Viewer
--------------------------------	--

HW Platform	NX One
-------------	--------

Base OS	Windows 10 IoT Enterprise 2016 LTSB
---------	-------------------------------------

Maximum Power consumption	53 W
---------------------------	------

Dimensions (W x D x H)	203 x 248 x 384 mm
------------------------	--------------------

Weight	Server unit only: 5.9 kg
--------	--------------------------

Paper Supply Options

PAPER DECK UNIT-E1	Paper Capacity: 3,500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond Paper Size: A4, B5 Paper Weight: 52 to 256 gsm Power Source: From the Main Unit Dimensions (W x D x H): 340 x 630 x 572 mm (attached to the main unit) Weight: Approx. 34 kg
POD DECK LITE-C1	Paper Capacity: 3,500 sheets (80 g/m ²) Paper Type: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Transparency, Labels, Tab Paper Size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R, and Custom Size (139.7 x 182.0 mm to 330.2 x 487.7 mm) Paper Weight: 52 to 256 g/m ² Power Source: 220-240V/1.2A 50/60Hz Dimensions (W x D x H): 633 x 686 x 574 mm (attached to the main unit) Weight: Approx. 68 kg

Output options	
COPY TRAY-R2	Provides a simple tray for basic output needs. Capacity: 250/100 sheets (1-sided/2-sided, 80 gsm)
STAPLE FINISHER-V2 (External) (iR-ADV 8585i III only)	Number of Trays: 3 Upper Tray Capacity*: A4, A5, A5R, A6R, B5: 250 sheets, SRA3, A3, A4R, B4, B5R: 125 sheets Mid Tray Capacity*: A4, A5, A5R, A6R, B5: 250 sheets, SRA3, A3, A4R, B4, B5R: 125 sheets Lower Tray Capacity*: A4, A5R, B5: 3,000 sheets, SRA3, A3, A4R, A5, B4, B5R: 1,500 sheets, A6R: 250 sheets * with 81.4 gsm paper Paper Weight: 52 to 256 gsm Staple Position: Corner, Double Staple Capacity: Corner and Double Stapling: A4, B5: 65 sheets (90 gsm), A3, A4R, B4: 30 sheets (90 gsm) Staple-Free Staple: A3, A4 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm) Staple On Demand: 65 sheets (90 gsm) Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended) Weight: Approx. 35 kg

BOOKLET FINISHER-V2 (External) (only for iR-ADV 8585i III)	(Includes the above basic Staple Finisher-V2 basic specifications.) Saddle Stitch paper size: A3, A4R, B4, Custom Size (195.0 x 270.0 mm to 304.8 x 457.2 mm) Saddle Stitch Staple Capacity: 20 Sheets x 10 sets (52 to 81.4 g/m ²) including 1 cover sheet up to (256 g/m ²) Non Staple Folded Bunch Capacity: up to 3 sheets (52 to 105 gsm) Power Source: From the main unit Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended) Weight: Approx. 58 kg
STAPLE FINISHER-X1 (External)	Number of Trays: 3 Upper Tray Capacity*: A4, A5R, B5: 1,500 sheets, SRA3, A3, A4R, A5, B4, B5R: 750 sheets, A6R: 250 sheets Mid Tray Capacity*: A4, A5R, B5 250 sheets, A3, A4R, A5, A6R, B4, B5R 125 sheets, Lower Tray Capacity*: [Cascade-Load mode] A4, B5: 2,500 sheets, [Random-Load mode] A4, A5R, B5: 1,500 sheets, SRA3, A3, A4R, A5, B4, B5R: 750 sheets, A6S: 250 sheets * with 81.4 gsm paper Paper Weight: 52 to 256 gsm Staple Position: Corner, Double Staple Capacity: Corner and Double Stapling: A4/B5: 100 sheets (80 gsm), A3/A4R/B4: 50 sheets (80 gsm) Power Supply: 100-240V AC, 50-60 Hz, 2.8A Dimensions (W x D x H): 782 x 765 x 1,040mm (when the extension tray is extended) Weight: Approx. 64 kg

BOOKLET FINISHER-X1 (External)	(Includes the above basic Staple Finisher-X1 basic specifications.) Saddle Stitch paper size: SRA3, A3, A4R, B4, Custom Size (210.0 x 279.4 mm to 330.2 x 487.7 mm) Saddle Stitch Staple Capacity: 20 sheets x 5 sets (60 to 81 gsm) (including 1 cover sheet up to 256 gsm) Non Staple Folded Bunch Capacity: up to 5 sheets (60 to 105 gsm) Power Source: 100-240V AC, 50-60 Hz, 2.8A Dimensions (W x D x H): 896 x 765 x 1,040 mm (when the extension tray is extended) Weight: Approx. 110 kg
--------------------------------	---

STAPLE FINISHER-W1 PRO (External)	Number of Trays: 2 Upper Tray Capacity*: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R: 1,000 sheets, Lower Tray Capacity*: If the High-Volume Stack Mode is set to "OFF": A4, B5: 2,000 Sheets, SRA3, A3, A4R, B4, B5R: 1,000 Sheets If the High-Volume Stack Mode is set to "ON": A4, B5: 4,000 Sheets, A4R, B5R: 2,000 Sheets, A3, B4: 1500 Sheets, SRA3: 1,000 Sheets * with 81.4 gsm paper Paper Weight: 52 to 256 gsm Staple Position: Corner, Double Staple Capacity: Corner and Double Stapling: A4, B5: 100 sheets (52 to 80 gsm), A3, A4R, B4, B5R: 50 sheets (52 to 80 gsm) Power Supply: 220-240V, 50-60 Hz, 8A Dimensions (W x D x H): 890 x 792 x 1,239 mm (when the extension tray is extended) Weight: Approx. 130 kg	INNER BOOKLET TRIMMER-A1	(Requires Booklet Finisher-X1) Acceptable Paper Weight 60 to 256 g/m ² Trim Amount: 2 to 20 mm Waste Tray Capacity: Approx. 1,500 Sheets Acceptable Paper Size: 210.0 x 279.4 to 330.2x 487.7mm
BOOKLET FINISHER-W1 PRO (External)	(Includes the above Staple Finisher-W1PRO basic specifications.) Saddle Stitch paper size: SRA3, A3, A4R, B4, Custom Size (210.0 x 279.4 mm to 330.2 x 487.7 mm) Saddle Stitch Staple Capacity: 25 sheets x 10 sets (52 to 80 gsm) [including 1 cover sheet up to 256 gsm] Non Staple Folded Bunch Capacity: up to 5 sheets (up to 209 gsm) Dimensions (W x D x H): 1,060 x 792 x 1,239 mm (when the extension tray is extended) Weight: Approx. 182 kg	BOOKLET TRIMMER- F1	(Requires Booklet Finisher-W1 PRO) Acceptable Paper Size: SRA3, A3, A4R, B4, Custom size: 210.0 x 279.4 mm to 330.2 x 487.7 mm) Booklet Capacity: 15 booklets (booklet size: A4, 80 gsm, 20 mm trim amount) Acceptable Paper Weight: 52 to 256 gsm, 64 to 300gsm (cover sheet only) Trim Amount: 2 mm to 20 28 mm Waste Tray Capacity: Approx. 1,500 5,000 Sheets Acceptable Paper Size: SRA3, A3, A4, B4, Custom Size: 210 x 279.4 mm to 330.2 x 487.7mm Power Source: From the Booklet Finisher-W1 PRO Dimensions: 2,095 x 790 x 1,040 mm (including joint) Weight: Approx. 178 kg
2/3 HOLE PUNCHER UNIT-A1	(Requires either the Staple Finisher-V2 or Booklet Finisher-V2) Two or Three Holes Acceptable Punch Paper Weight: 52 to 256 gsm Acceptable Punch Paper Size: Two holes: A3, A4, A4R, A5, B4, B5, B5R Three holes: A3, A4, B4, B5 Power Source: From the Main Unit	DOCUMENT INSERTION UNIT-N1	(Requires either the STAPLE FINISHER-X1, BOOKLET FINISHER-X1, STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO) Number of insertion trays: 2 trays Insertion Tray Capacity: 200 sheets x 2 (80 gsm) Acceptable Insertion Paper Type: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Coated, Tab, Tracing Acceptable Insertion Paper Size SRA3, A3, A4, A4R, B4, B5, B5R, Custom size: 182.0 x 182.0 mm to 330.2 x 487.7 mm Acceptable Insertion Paper Weight: 52 to 256 gsm Dimensions (W x D x H): 336 x 793 x 1,407 mm (width: excluding document tray) Power Supply: 100-240V, 50/60Hz, 1.0 Amp Weight: Approx. 61 kg
2/4 HOLE PUNCHER UNIT-A1	(Requires either the Staple Finisher-V2 or Booklet Finisher-V2) Two or Four Holes Acceptable Punch Paper Weight: 52 to 256 gsm Acceptable Punch Paper Size: Two holes: A3, A4, A4R, A5, B4, B5, B5R ; Four holes: A3, A4 Power Source: From the main unit	PAPER FOLDING UNIT-J1	(Requires either the STAPLE FINISHER-X1, BOOKLET FINISHER-X1, STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO) Supported Folding Types: C-Fold, Z-Fold, Accordion Z-Fold, Double-parallel Fold, Half-Fold Acceptable Paper Type: Thin, Plain, Recycled, Colour, Bond Acceptable Paper Size C-Fold: A4R Z-Fold: A3, A4R, B4 Accordion Z-Fold: A4R Double-parallel Fold: A4R Half-Fold: A: A4R Acceptable Paper Weight: C-Fold / Z-Fold / Accordion Z-Fold / Half-Fold : 52 to 105 gsm Double-parallel Fold: 52 to 90 gsm Power Source: From the Finisher Dimensions (W x D x H): 336 x 793 x 1,190 mm Weight: Approx. 71 kg
4 HOLE PUNCHER UNIT-A1	(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2) Four Holes Acceptable Punch Paper Weight: 52 to 256 gsm Acceptable Punch Paper Size: Four holes: A3, A4, A4R, A5, B4, B5, B5R Power Source: From the main unit		
PUNCHER UNIT-BF1	(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1) Two or Three Holes Acceptable Punch Paper Weight: 52 to 256 g/m ² Acceptable Punch Paper Size: Two holes: A3, A4, A4R, A5 Three holes: A3, A4 Power Source: From the Finisher		
PUNCHER UNIT-BG1	(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1) Two or Four Holes Acceptable Punch Paper Weight: 52 to 256 g/m ² Acceptable Punch Paper Size: Two holes: A3, A4, A4R, A5, B5R Four holes: A3, A4 Power Source: From the Finisher		
PUNCHER UNIT-BH1	*Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1 Four Holes Acceptable Punch Paper Weight: 52 to 256 g/m ² Acceptable Punch Paper Size: Four holes: A3, A4, A4R, B4, B5, B5R Power Source: From the Finisher		
PUNCHER UNIT-BS1	(Requires either the STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO) Two or Three Holes Acceptable Punch Paper Weight: 52 to 256 g/m ² Acceptable Punch Paper Size: Two holes: Custom size (182.0 x 182.0 mm to 297.0 x 432.0 mm) Three holes: A3, A4, Custom size: (240.0 x 182.0 mm to 297.0 x 432.0 mm) Power Supply: From the Finisher		
PUNCHER UNIT-BT1	(Requires either the STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO) Two or Four Holes Acceptable Punch Paper Weight: 52 to 256 g/m ² Acceptable Punch Paper Size: Two holes A3, A4, A4R, A5, B4, B5, B5R, Custom size (182.0 x 182.0 mm to 297.0 x 432.0 mm) Four holes A3, A4, Custom size (257.0 x 182.0 mm to 297.0 x 432.0 mm) Power Supply: From the Finisher		
PUNCHER UNIT-BU1	Requires either the STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO) Four Holes Acceptable Punch Paper Weight: 52 to 256 g/m ² Acceptable Punch Paper Size: Four holes A3, A4, A4R, A5, Custom size (257.0 x 182.0 mm to 297.0 x 432.0 mm) Power Supply: From the Finisher		
Multi Function Professional Puncher-B1	(Requires either the STAPLE FINISHER-X1, BOOKLET FINISHER-X1, STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO) Acceptable Punch Paper Weight: Bypass: 52 to 300 g/m ² , Punch: Plain: 75 to 300 g/m ² , Coated: 118 to 300 gsm Acceptable Punch Paper Size: Bypass: 100 x 148 mm to 330.2 x 487.7 mm, Punch: SRA3, A3, A4, A4R Supported Punch Dies (optional): A4: Loose Leaf (2- or 4- hole), Velo Bind (12-hole), Plastic comb (21-hole), Twin Loop (23- or 34- hole), Colour Coil (47-hole) Letter: Loose Leaf (4-hole), Twin Loop (21- or 32- hole) Dimensions (W x D x H): 445 x 795 x 1,040 mm Weight: 102 kg Power Supply: 230V/50Hz/1.9 A		

For information and services contact

Canon Australia Pty Ltd 1800 444 199 canon.com.au
Canon New Zealand Ltd 0800 222 666 canon.co.nz

*No one does it
like you*

Canon