

Compact workgroup productivity.

imageRUNNER
2520/i, 2525/i, 2530/i,
2535/i, 2545/i

you can

A RANGE OF SPEEDS FROM 20 TO 45 PPM / CPM, A3 BLACK-AND-WHITE

UP TO 2,300 SHEET PAPER CAPACITY

SEND DIRECT TO EMAIL AND NETWORK FOLDER

5.7 INCH / 14.47 CM TOUCH SCREEN DISPLAY

CLASS-LEADING ENERGY EFFICIENCY

COMPACT DESIGN

Ideal for busy, small and medium workgroups, this versatile range provides for everyday black-and-white printing, copying, colour scanning and advanced send direct to email and network folder. With a variety of speeds up to 45 ppm, excellent responsiveness and energy efficiency these devices will save you time, money and energy.



Productivity and efficiency

- Easy-to-use touch-screen display saves time
- Fast output speeds up to 45 ppm
- Send in colour to network folders or email in a variety of formats*
- Fewer interruptions with up to 2,300 sheet paper capacity
- Simple, hassle-free integration – Network ready, PCL* and optional PostScript Support
- Optional inner staple finisher
- e-Maintenance service provides remote diagnostics, automated meter readings and toner management.

Environmental

- Exceptional energy efficiency – as little as 1.5 watts power consumption in sleep mode, saves energy and cost
- Save paper – automatic double-sided output.

Cost-effective

- Low cost of ownership
- Enhanced productivity and class-leading energy efficiency maximises value
- Compatibility with uniFLOW solution offers Cost Centre selection and reporting for cost control and monitoring
- Accurate billing through e-Maintenance.

Security

- Secure Print** keeps documents confidential during printing
- Department ID secures access to the device
- uniFLOW compatibility offers the flexibility and convenience of My Print Anywhere secure release with job selection.

* Standard on i models, optional on non i models
** RAM-based secure print for up to 100 jobs

imageRUNNER

Canon

Specifications: imageRUNNER 2500 Series

Type	Desktop or Free-standing (Reader-Printer Combined)	
Maximum Original Size	A3	
Copy Sizes	Cassette 1, 3, 4 A3, A4, A4R, A5R. Custom size: 139.7 to 297mm x 182 to 432mm	
	Cassette 2	A3, A4, A4R, A5R
	Stack Bypass	A3, A4, A4R, A5R
Resolution	Custom Size	99 to 297mm x 148 to 432mm
	Reading	600dpi x 600dpi
	Copying	600dpi x 600dpi
	Printing	600dpi x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)
	No. of Tones	256 Gradations
COPY/PRINT SPEED		
	A4	imageRUNNER 2545i / 2545: 45ppm (BW) imageRUNNER 2535i / 2535: 35ppm (BW) imageRUNNER 2530i / 2530: 30ppm (BW) imageRUNNER 2520i / 2520: 25ppm (BW)
	A3	imageRUNNER 2545i / 2545: 22ppm (BW) imageRUNNER 2535i / 2535: 22ppm (BW) imageRUNNER 2530i / 2530: 15ppm (BW) imageRUNNER 2520i / 2520: 15ppm (BW)
Magnification	Zoom	25-400%; Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400%
First Copy Time	Black & White	3.9 sec (45 / 35ppm model), 5.4 sec (30 / 25ppm model), 6.4 sec (20ppm model)
Warm-Up Time	Duplexing	1 to 999 sheets
Multiple Copies/Prints	Duplexing	Standard
Paper Weight	Cassette	64 to 90g/m ² ; Stack Bypass: 64 to 128g/m ² ; Duplex: 64 to 80g/m ²
Paper Capacity	Cassette 1	550 sheets (80g/m ²) (250 sheets for the imageRUNNER 2520i / 2520)
	Cassette 2	550 sheets for imageRUNNER 2525i, 2530i/i, 2535i/i, 2545i/i
	Stack Bypass	100 sheets (A4, A4R, A5; 80g/m ²), 50 sheets (A3; 80g/m ²)
	Optional	550 sheets x 2 cassettes (80g/m ²) 550 sheets x 1 cassette for imageRUNNER 2520 / 2520i only
	Paper Deck	None
	Total Capacity	2,300 sheets. (2,000 sheets for the imageRUNNER 2520i / 2520) Canon Custom Processor, 400MHz
CPU	Memory	512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)
Hard Disk Drive	Interface	None
	Power Supply	Ethernet (100Base-TX / 10Base-T), USB Host1 / F 2.0 x 1 port, USB Device 1.0 x 1 port
Max. Power Consumption		220-240V AC, 50/60Hz, 4.2A (45 / 35ppm model), 220-240V AC, 50/60Hz, 3.3A (30 / 25 / 20ppm model)
Dimensions (W x D x H)		1.827kW (45 / 35ppm model), 1.345kW (30 / 25ppm), 1.542kW (20ppm model)
	Weight	imageRUNNER 2545i / 2545 / 2535i / 2535: 565 x 680 x 806mm (with the platen cover), 565 x 689 x 907mm (with the DADF) imageRUNNER 2530i / 2530 / 2525i / 2525: 565 x 680 x 806mm (with the platen cover), 565 x 689 x 896mm (with the DADF) imageRUNNER 2520i / 2520: 565 x 680 x 681mm (with the platen cover), 565 x 689 x 771mm (with the DADF) imageRUNNER 2545i / 2535i: Approx. 78.4kg, imageRUNNER 2545 / 2535: Approx. 70.5kg, imageRUNNER 2530i / 2525i: Approx. 77.5kg, imageRUNNER 2530 / 2525: Approx. 68.0kg, imageRUNNER 2520i: Approx. 56.0kg, imageRUNNER 2520: Approx. 50.5kg
PRINT SPECIFICATION		
PDL	UFRII-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional)	
Resolution	600 x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)	
Memory	512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)	
Hard Disk	None	
CPU	Canon Custom Processor, 400MHz	
Fonts	PS Fonts: Roman 136, PCL Fonts: Roman 93	
Supported OS	PCL: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Postscript level 3 emulation: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later) UFRII-LT: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later), Linux Mac-PPD: Mac OS X 10.4 or later	
Interface	Ethernet (100Base-TX / 10Base-T)	
Network Protocol	TCP / IP (LPD / Port9100, HTTP), SMB, SNMPv1, WSD, IPv4 / IPv6 support	
Pull Scan	Network TWIN Driver (75 / 100 / 150 / 200 / 300dpi 8bit colour / 75-600dpi 1bit Black-and-White)	
SEND SPECIFICATION/ CLR SEND KIT-Y1		
(standard on i models, optional on non i models)		
Scan Speed	BW	45 / 34ipm (45 / 35ppm model), 25 / 13ipm (30 / 25 / 20ppm model) 100 x 100dpi, 150 x 150dpi, 200 x 100dpi, 200 x 200dpi, 200 x 400dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi
Scan Resolution	CL	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 300 x 300dpi
Destinations	E-Mail / Internet FAX (SMTP), PC / Server (SMB,FTP), USB memory keys	
Address Book	Local (Max. 500)	
File Format	TIFF, JPEG, PDF, High compression PDF, Searchable PDF (optional with Searchable PDF-C1)	

DADF-AA1 for imageRUNNER 2545/2535		
Paper Size	A3, A4, A4R, A5, A5R	
Paper Weight	Single sided original: 42 to 128g/m ² , Double sided original: 50 to 128g/m ²	
Max. Number of Originals	100 sheets (A4, A4R, A5, A5R: 80g/m ²), 50 sheets (A3: 80g/m ²)	
Document Scanning Speed (max.)	Copy Scan	45ipm (A4, 600 x 600dpi: BW) 45 / 34ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour)
Dimensions (W x D x H)	565 x 540 x 137mm	
Weight	Approx. 7.9kg	
DADF-AB1 for imageRUNNER 2530/2525/2520		
Paper Size	A3, A4, A4R, A5, A5R	
Paper Weight	Single sided original: 37 to 128g/m ² , Double sided original: 50 to 128g/m ²	
Max. Number of Originals	50 sheets (A4, A4R, A5, A5R: 80g/m ²), 25 sheets (A3: 80g/m ²)	
Document Scanning Speed (max.)	Copy Scan	25ipm (A4, 600 x 600dpi: BW) 25 / 13ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour)
Dimensions (W x D x H)	565 x 544 x 126mm	
Weight	Approx. 7.0kg	
CASSETTE UNIT-W1 for imageRUNNER 2520/i		
Type	Front-loading adjustable drawers	
Paper Size	A3, A4, A4R, A5R	
Custom Size	139.7 to 297mm x 182 to 432mm	
Paper Weight	64 to 90g/m ²	
Paper Capacity	550 sheets (80g/m ²) x 1 cassette	
Dimensions (W x D x H)	565 x 680 x 97mm	
Weight	Approx. 12.8kg	
CST. FEEDING UNIT-AE1 for all models		
Type	2 Front-loading adjustable drawers	
Paper Size	A3, A4, A4R, A5R	
Custom Size	139.7 to 297mm x 182 to 432mm	
Paper Weight	64 to 90g/m ²	
Paper Capacity	550 sheets (80g/m ²) x 2 cassettes	
Dimensions (W x D x H)	565 x 680 x 248mm	
Weight	Approx. 24.0kg	
INNER FINISHER-B1 for all models		
Number of Trays	One stack tray (Optional 2nd Tray: INNER FIN ADD. TRAY-B1)	
Tray Capacity	A4, A5, A5R: 1,000 sheets (or 125mm in height) A3, A4R: 500 sheets (or 62.5mm in height)	
Staple Position	Corner, Double	
Staple Capacity	A4: 50 sheets x 30 sets; A4R / A3: 30 sheets x 15 sets	
Dimensions (W x D x H)	416 x 554 x 350mm, 703 x 554 x 350mm (with output tray extended)	
Weight	Approx. 12.5kg	
INNER 2-WAY TRAY-G1 for all models		
Number of Trays	2 stack tray	
Tray Capacity	Tray A: A4: 250 sheets, A3: 100 sheets Tray B: A4: 100 sheets, A3: 50 sheets	
Dimensions (W x D x H)	426 x 413 x 109mm	
Weight	Approx. 0.6kg	
OTHER ACCESSORIES		
Platen Cover Type P: for imageRUNNER 2525/2530 without DADF Platen Cover Type Q: for imageRUNNER 2535/2545 without DADF Stamp Ink Cartridge-C1 Stamp Unit-B ADF Access Handle-A1 PCL Printer Kit-AF1: Supports PCL5e and PCL6 printing for non-i Models PS Printer Kit-AF1: Supports PostScript Level 3 Emulation printing. Barcode Printing Kit-B1: Provides Barcode printing capability using Jet Caps technology Super G3 Fax Board-AG1: Add fax functionality FL Cassette-A11: This spare 550-sheet tray for cassette '1' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i FL Cassette-AK1: This spare 550-sheet tray for cassette '2' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i or for Cassette Feeding Unit-AE1 or Cassette Module-W1 FL Cassette-AL1: This spare 250-sheet tray for cassette '1' of imageRUNNER 2520 / 2520i allows you to swap paper sizes without changing the printer settings. Cassette Spacer-A1: Adjusts the height for 250-sheet cassette when combined with optional Cassette Feeding Unit-AE1 or Cassette Module-W1 on imageRUNNER 2520 / 2520i only. 2 Way Unit-B1: Enhances the double-sided print productivity up to 100% Reversal Pass Unit (2-Way Unit) option for imageRUNNER 2520 / 2520i / 2525 / 2530. Staple-J1: Staples for Inner Finisher-B1. Document Tray-J1: Handy tray that attaches to the side of the device. Power Supply Unit-U1. Card Reader Attachment-D3: Attachment kit for Card Reader-F1. Canon Card Reader-F1: Physical card access system that limits system access to authorised users. USB Application 3-Port Interface Kit-A1: 3-Port USB interface kit for USB memory. CCV1 I/F Cable-A1: Interface Kit for Coin-Vender. C-EXV33 TONER BK: Toner for imageRUNNER 2520 / 2520i / 2525 / 2525i / 2530 / 2530i. C-EXV32 TONER BK: Toner for imageRUNNER 2535 / 2535i / 2545 / 2545i		
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.		



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English Edition 0163W635
01/12/v1
© Canon Europa N.V., 2012

Canon (UK) Ltd
Woodhatch
Reigate
Surrey
RH2 8BF
Tel.: 01737 220000
Fax: 01737 220022
canon.co.uk

Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Tel.: 01 2052400
Fax: 01 2052525
canon.ie