500i Booklet System

SPECIFICATIONS

Number of Bins* 10, 20, 30, 40, 50, 60 (10 bins per tower)*

Paper Size Width: 4.1" - 14"

Length: 5.8" - 24" (width of paper must be within 7.88" - 9.05"

when paper length is greater than 20")

Paper Weight Fine quality paper: 52 - 157gsm (Cover: 52 - 300 gsm) Art coated paper: 79 - 157gsm (Cover: 79 - 300 gsm)

Bin Capacity

Bookletmaking: Up to 5,000 sets/hour¹ Collating: Up to 10,000 sets per hour¹

Feed System Patented dual fan feed system for each bin Controller PC Controller w/IMBF or Color Touch Screen LCD panel

(IMBF feature not available with LCD Panel)

120V 60Hz 7.9 - 8.4A 910 - 960W Power

Dimensions (WxDxH) 34" x 33" x 78"

Weight 674 lbs.

Options DSC-10/60D Bridge; LUR Lift Unit Right, D-Port Converter (required); DBM-400STR Right Exit Deep Pile Stacker, DCR-ST Left Exit Cross Stacker;

DCR-BP Bypass Bridge, DSC1060ENVLP Envelop Kit

DBM-500 PRO BOOKLETMAKER (Requires D-Port Converter)

CORNER/SIDE/TOP STITCHING APPLICATION

Sheet Size (Min./Max.) 4.72" x 5.52" to 13.82" x 14.33"

Paper Capacity Up to 30 sheets***

SIGNATURE BOOKLETMAKING APPLICATION

Sheet Size (Min./Max.) 4.72" x 6.7" to 14" x 20" Up to 25 sheets*** Paper Capacity

GENERAL Speed

Up to 5,000 sets per hour** Detections Wire draw detection

Number of Stitcher Heads 2 standard or 4 optional. Type: Hohner 43/6S

Stitch Positions Saddle, corner, side, none (fold only)

Programmable Memory Settings

Stitcher heads, back jogger, side guides, stitch stopper, fold stopper, **Automatic Functions**

fold-back stopper positions, small booklet adjustments, fold roller gap, conveyance roller position, center reference, disengage the

operator side stitching head when corner stitching

Power Requirements 120V 60Hz 6.5A Dimensions (LxWxH) 64" x 28" x 40" 908 lhs Weight

LCD touch panel and ten-key pad; DBM-500T settings adjustable Other Features

from DBM-500 Pro control panel; accepts set-by-set and sheet-bysheet; jam clearance accessibility; side and corner stitch catch tray; knife folder with four adjustable fold rollers and insert attachment for inserting loose sheets into booklets; adjustable control panel,

external fold skew adjustment

DSC-10/60i Intelligent Air Suction Feed Collator, DSC-10/20 Air **Connecting Devices**

Suction Feed Collator, DSF-2200 Document Sheet Feeder, DSF-5000 Document Sheet Feeder, DBM-500T Trimmer, DCR-ST Cross Stacker

DBM-400STR STACKER (Requires D-Port Converter)

Sheet Capacity (Min./Max.) 8.25" x 5.5" to 13.77" x 19.68"

Paper Capacity

Up to 9,800 sets per hour** Speed **Power Consumption** 120V 60Hz 2.2A Dimensions (LxWxH) 30" x 35" x 35"

Weight

Other Features Automatic size change; 13 programmable memory settings; straight or offset stacking; jam and door open detectors

DBM-500T TRIMMER (Requires D-Port Converter)

Trimming Mechanism Upper and lower shearing action Booklet Size (Min./Max.) 4.72" x 3.35" to 14" x 10" Trimmed Booklet Size (Min./Max.) 4.72" x 3" to 14" x 10" Trim Margin Up to 1"*** Speed Up to 5,000 sets per hour**

Power Consumption 120V 60Hz 10A Dimensions (LxWxH) 23" x 27.5" x 43" Weight 532 lbs.

Other Features Jam detectors; adjustable belt in-feed timing; inter-locking

safety covers; automatic setting exit rollers; auto knife up/ down; bypass for documents that do not need a face trim: trim/no trim; resettable output counter; compressed air to trimmings tray; trim scrap-box-full sensor; drop-away flap for trimmings; full-width head stop; spine compression;

DBM-LS1 Extended Conveyor with DBM-K Batch Kicker, DBM-SS1 Short Stacker, DKT-200 Two-Knife Trimmer

automatically adjustable in-feed roller gap

DKT-200 TWO-KNIFE TRIMMER (Requires D-Port Converter)

Connecting Devices

Trimming Width

4.72" x 2.95" to 14.02" x 10" Booklet Size (Min./Max.) When gutter cutter option used: 7.87" x 2.95" to 14.02" x 10" (gutter)

Finished Size (Min./Max.) 4.72" x 2.95" to 13.9" x 10" When gutter cutter option used: 3.54" x 2.95" to 6.85" x 10"

0.04 - 1.18" Gutter: 0.24"

Trimming Method 2 upper blades, 2 lower blades Within 5 mm (no gutter): fine 81.4 gsm/ Trimming Thickness

22 lb. 50 sheets

Within 2.4 mm (gutter): fine 81.4 gsm/

22 lb. 24 sheets

Up to 9,000 sets/hour with gutter cutter

Up to 4,500 sets/hour (fine 81.4 gsm/ 22 lb. within 20 sheets A5 finished) Up to 3,900 sets/hour (fine 81.4 gsm/ 22 lb. within 20 sheets A4 finished)

220 - 240 V 60Hz 4.1A 640W **Power Consumption** Dimensions (LxWxH) 37" x 32" x 46"

91" x 32" x 47" (including stacker) 1,040 lbs.

DCR-ST CROSS STACKER (Requires D-Port Converter)

Paper Size (Min./Max.) Trav L - 8.46" x 12.60" to 13.98" x 17.72" Tray S - 8.27" x 12.80" to 5.83" x 9.84"

Stack Height Tray L - 3.94" Tray S - 7.87"

Tray L - 3,000 sets/hour 11" x 17"**

Tray S - 4,000 sets/hour 8.5" x 11"** Other Features Cross and straight stacking, adjustable set interval

120V 60Hz 1.0A Power Consumption Dimensions (LxWxH) 28" x 27" x 25" Weight Main unit - 97 lbs.

Tray L - 18 lbs. Tray S - 18 lbs.

Note: Requires DCR-BP Bypass Conveyor when using in-line with bookletmaker

COMMON SYSTEM CONFIGURATIONS (Additional components may be required)

- DBM-LS1 + DBM-500T + DBM-500 Pro + PC Controller + DSC-10/60i
- DBM-LS1 + DBM-500T + DBM-500 Pro + PC Controller + DSC-10/60i + DBM-400STR • DKT-LS + DKT-200 + DBM-500T + DBM-500 Pro + PC Controller + DSC-10/60i
 - ** Dependent upon connected devices and number of bins in use *** Dependent upon paper weight and size

Production rates are based on optimal operating conditions and may vary depending on stock and environmental conditions. As part of our continuous product imp

program, specifications are subject to change without notice.






3050 S. Daimler Street, Santa Ana, CA 92705 (949) 752-8222 (800) 255-1933 (949) 851-3054 fax www.duplousa.com All rights reserved. No part of this document may be produced without permission of Duplo USA Corporation

0613AO

Duplo from print to documents

500i **Booklet System**

Intelligent, High Production Bookletmaking



^{*} Currently configurable with up to 40 bins (4 towers), 50 and 60 bins TBA

¹ Dependent upon connected devices and number of bins in use

Intelligent, igh Production Bookletmaking

The 500i Booklet System is Duplo's high production collating and bookletmaking system. Integrating the DSC-10/60i Suction Collators with the DBM-500 Pro Bookletmaker, the 500i Booklet System produces saddle, side, or corner-stitched applications at a production rate of up to 5,000 booklets per hour.

Ideal for both offset and digitally printed applications, the 500i Booklet System offers enhanced features for optimum efficiency and productivity. And by adding the optional 4-stitch head kit along with the DKT-200 Two-Knife Trimmer and gutter cutter, users can produce booklets with a full-bleed finish and process 2-up applications, increasing production up to 9,000 booklets per hour!

PC CONTROLLER: 60-SECOND CHANGEOVERS

Automatically change over from a catalog to a CD-size booklet in under a minute using the PC Controller software. The PC Controller makes it incredibly simple for operators of any skill level to operate, program new jobs, and manage the settings of the entire system. The intuitive software guides operators step-by-step throughout the process and gives them complete control over the job parameters and adjustments to allow them to precisely set the stitch, fold, and trim positions. And with the ability to store virtually an unlimited number of jobs in the hard drive, users can instantly recall and change over jobs in less than 60 seconds!

INTELLIGENT MULTI-BIN FEEDING

Perform custom feed applications and fulfill a variety of unique job requirements by using the IMBF (Intelligent Multi-Bin Feeding) feature that comes standard with the PC Controller software. Seamlessly merge black and white documents with color media, combine un-collated offset with collated digital output, and create one-to-one marketing booklets by inserting variable data material. Take full control of the feeding sequence, link bins, select the bins to feed from, and specify also be delivered set-by-set or sheet-by-sheet into the bookletmaker.

DSC-10/60i SUCTION COLLATORS: SUPERIOR FEEDING SYSTEM

The 500i Booklet System utilizes Duplo's DSC-10/60i Suction Collators. The unique 8-belt air suction feed system along with an Air Management System make these collators the most reliable in the industry. Incorporating Duplo's patented dual fan technology, each bin comes equipped with two individual fans – one to produce a stable flow of air for separation and the other to generate consistent suction for feeding. With adjustments conveniently located beside each bin, the Air Management System enables operators to easily fine-tune the amount and strength of air, if necessary.

High resolution optical sensors add an extra level of reliability by ensuring miss or double feed errors are identified. Faulty sets are diverted into a reject tray to allow continuous operation and can easily be recovered by simply correcting and inserting them into the hand marry station. Optional ultrasonic sensors can be added for feeding sheets with heavy coverage. Ultrasonic sensors use sound waves instead of light, making them impervious to paper thickness, variations in ink, toner and coverage.

The 500i Booklet System will be configurable with up to 6 towers for a total of 60 bins. The DSC-10/60i Collator offers flexibility for various application needs including Interleaf Modes to insert single or double sheets when stacking. 1/2, 1/3 and 1/4 block modes are provided for non-stop productivity.

DSS-350 Square Spine. paper stocks 52-300 ism and paper sizes





DBM-500 PRO BOOKLETMAKER: HIGH PRODUCTION BOOKLETMAKING

After sheets are collated by the DSC-10/60i Collator, sets are delivered into the DBM-500 Pro Bookletmaker for stitching, folding, and trimming. Booklets can be saddle, side, or corner-stitched without additional tools required. The bookletmaker utilizes heavyduty Hohner stitch heads and can switch from 2 (standard) or 4 (optional) stitches as the job requires. Sheet sizes of 14" x 20" down to 4.75" x 7.01" can be processed with equal ease. Up to 25-sheet booklets can be processed for signature bookletmaking or up to 30 sheets can be processed for side or corner-stitching.

With the 500i Booklet System, a wide range of applications can be produced and a number of options can be added to meet customer demands. Booklets can be face trimmed only with the DBM-500T Trimmer or for three-side trimming capabilities, the DKT-200 Two-Knife Trimmer can be added. With the DKT-200, booklets are trimmed at the head and foot for a full-bleed finish and with the gutter cutter, users can process 2-up applications, producing up to 9,000 booklets per hour.

Deliver booklets with a flatter, square spine finish by adding the ASM-500 SpineMaster option in-line with the 500i Booklet System or to enhance the quality off-line, use the





COLLATING AND STACKING

The DSC-10/60i Collators have the ability to feed to the left into the DBM-500 Pro Bookletmaker or to the right into a stacker. The DSC-10/60i collates up to 10,000 sets per hour depending upon connected devices and users can choose from two optional stackers:


- DBM-400STR High Capacity Stacker Ideal for high volume stacking jobs, the DBM-400STR Stacker can straight or offset stacks up to 17". The DBM-400STR is attached to the right of the collator, opposite side of the bookletmaker, to allow for quick change over from bookletmaking to stacking without having to remove any devices.
- DCR-ST Cross Stacker The DCR-ST can cross or straight stack up to 7.87". It connects between the collator and the bookletmaker. When the stacker is not being used, a bypass bridge redirects the paper to the bookletmaker for bookletmaking without having to remove any devices.



VALUE ADDED OPTIONS

Customize the 500i Booklet System to meet your needs.

- LCD color touchscreen panel option as an alternative to the PC Controller*
- Envelope Kit enables the feeding of #9 and #10 envelopes from bins 4 and 9 for insertion between certain sheets of the booklet.
- Ultrasonic Sensor Kit is an option that provides an enhanced level of double feed detection for documents with dark images or heavy ink or toner coverage. Each kit supports two bins; five kits are required to support all ten bins.
- Hohner 4-Stitch Head Kit required to produce 2-up applications.
- **DKT-200 Two-Knife Trimmer** adds three-side trimming capabilities to produce booklets with a full-bleed finish. Add the gutter cutter option to finish 2-up applications.
- ASM-500 SpineMaster or DSS-350 Square Spine give booklets a flat, square spine finish.
- DSF-2200 in configuration with the 500i Booklet System creates the versatile 500i Duetto Booklet System. Add value and productivity by processing both pre-collated digital print applications in the DSF-2200 and un-collated offset applications in the DSC-10/60i Collators using a single system!
- * Please note the IMBF feature is only available with the PC Controller and not with the LCD panel.



DKT-LS Long Stacker DKT-200 Two-Knife Trimmer DBM-500T Face Trimmer

DBM-500 Pro Bookletmaker

LUL-HM Hand Marry

DSC-10/60i Suction Collators

LDR Bridge

DBM-400STR Stacker