

www.fel.fujitsu.com



fi-4860C **A3 document scanner**

- 60ppm colour at 200dpi
- 60ppm mono at 200dpi
- Simplex/Duplex scanner
- 500 page ADF
- A7 – A3 scanning
- Optional Pre and Post imprinter

FUJITSU

THE POSSIBILITIES ARE INFINITE



Fujitsu's fi-4860C scanner brings high speed scanning to the mid-volume market.

The fi-4860C from Fujitsu provides users with a multifunctional, high quality image processing mid-volume scanner aimed at applications with scanning requirements of between 6,000-10,000 documents per day.

The scanner can scan in colour and mono at speeds of 60 pages per minute at 200 dpi (via an ultra wide SCSI EGSA board) through

the automatic document feeder, and also has manual feed capability. It can scan from A7 up to A3 and is equipped with a 500-sheet hopper.

The fi-4860C scanner uses high resolution CCD technology allowing the user to select resolutions up to 400dpi which is ideal for OCR applications that require high quality images for optimum recognition rates.

fi-4860C Specifications

| | | |
|-------------------------------------|----------------|--|
| Operating method | | ADF (automatic document feeder) and MF (manual feed) |
| Image sensor | | CCD (charge-coupled device) image sensor |
| Light source | | White fluorescent lamp |
| Output format | | 8 bit gray scale, 24 bit colour, bitonal |
| Document size | Minimum | A7 (74 mm x 105 mm) |
| | Maximum | A3 (297 mm x 420 mm) |
| Output resolution | | 400/300/240/200/150/100/dpi |
| Scanning speed | Colour simplex | 60 ppm for A4 portrait format at 200 dpi |
| | Colour duplex | 120 ipm for A4 portrait format at 200 dpi |
| | Mono simplex | 60 ppm for A4 portrait format at 200 dpi |
| | Mono duplex | 120 ipm for A4 portrait format at 200 dpi |
| Halftone patterns | | Dither; Error diffusion |
| Capacity of ADF | | Maximum 500 sheets, paper weight: 64 g/m ² , (17 lbs), A4 |
| Interface | | Ultra Wide SCSI |
| Memory | | 128MB |
| Power requirements | | 100-240 VAC ±10%, 50/60 Hz |
| Power consumption | | 160 VA or less |
| Operating environment | | Temperature: 15°C - 35°C (59°F-95°F) |
| Relative humidity | | 20% - 80% (noncondensing) |
| Dimensions (WxDxH) | | 520 x 431 x 523 mm |
| Weight | | 45 kg |
| Options | Imprinter | Pre and Post |
| Recommended daily throughput | | 10,000 pages |

Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative.

Fujitsu Europe Limited

Hayes Park Central
Hayes End Road
Hayes Middlesex UB4 8FE
England
Tel: (+44-(0)20) 8573 4444
Fax: (+44-(0)20) 8573 2643
www.fel.fujitsu.com

Fujitsu Italia S.p.A.

Via Nazario Sauro, 38
20099 Sesto San Giovanni (MI)
Italy
Tel: (+39) 0226294.1
Fax: (+39) 0226294.201
www.fis.fujitsu.com

Fujitsu Deutschland GmbH

Frankfurter Ring 21 I
80807 Munich
Germany
Tel: (+49-(0)89) 32378-0
Fax: (+49-(0)89) 32378-100
www.fdg.fujitsu.com

