HP LaserJet Managed MFP E72525dn

Businesses that stay ahead don't slow down. It's why HP built the next generation of HP LaserJet MFPs—to power productivity with a streamlined design that delivers premium quality, maximum uptime, and the strongest security.



PrintSpeed: Up to 25 ppm black; First Page Out: As fast as 7 3 sec black

PrintResolution: Black (best): Up to 1200 x 1200 dpi reduced speed

StandardConnectivity: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port StandardMemory: Standard: 6 GB; Maximum: 6 GB

MobilePrintingCapability:Yes PaperHandling: 100-sheet input tray, 520-sheet input tray, 520-sheet input tray, 100 sheet ADF; 500 sheet face-down

Display: 8.0-in (20.3 cm) touchscreen, SVGA Color Graphic Display (CGD)













High quality, low cost

- Print premium, professional-quality documents with sharp text and crisp graphics for a low cost.
- Get consistent, professional quality and performance you count on with Original HP toner cartridges and drums.
- Choose from a range of modular accessories designed to adapt to the needs of workgroups of all sizes.

Minimal interruptions. Maximum uptime.

- Avoid interruptions with an HP LaserJet Managed MFP designed to be streamlined for maximum productivity.
- Tailor this MFP to the needs of your business with a wide range of paper-handling accessories.
- Scan files directly to Microsoft® SharePoint, plus email, USB, and network folders.²
- Grab pages and go, without waiting. This HP LaserJet wakes up quickly and prints fast—up to 25 ppm.³

The world's most secure printing

- With HP Sure Start, each printer regularly checks its operating code and repairs itself from attempted hacks.
- Help protect information on your MFP and in transit over the network—store data on the encrypted hard
- Continually monitor to detect and stop attacks, then automatically reboot with run-time intrusion detection.
- Whitelisting checks firmware during startup to help ensure it's authentic, good code—digitally signed by HP.

1 Based on HP review of 2016 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit http://www.hp.com/go/PrintersThatProtect. For more information: http://www.hp.co agreements. For details, see http://www.hpconnected.com ³ Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. ⁴ Some features require additional purchase. A FutureSmart service pack update may be required to activate security features. Learn more at http://www.hp.com/go/printsecurity

HP LaserJet Managed MFP E72525dn Specifications Table

Functions / Multitasking Supported	Print, Copy, Scan (fax and wireless optional) / Yes	Media Weight Supported	Tray 1: 16 to 46 lb bond; Tray 2, 3: 16 to 58 lb bond
rint Speed	Letter: Up to 25 ppm black; ⁷ First Page Out: As fast as 7.3 sec black; ³	Media Sizes Supported	Tray 1: Letter, Letter R, Legal, Executive, Statement, Oficio, 11×17 , 12×18 , 4×6 , 5×7 , 5×8 , 10×15 ,
rint Resolution	Black (best): Up to 1200 x 1200 dpi reduced speed		8k, 16k, envelope #9, Envelope #10, Envelope Monarch; Tray 2: Letter, Letter R, Legal, Executive, Statement, Oficio, 4 x 6, 5 x 7, 5 x 8, 16k; Tray 3: Letter, Letter R, Legal, Executive, Statement, Oficio, 1
rint Technology	Laser		x 17, 12 x 18, 8k, 16k
Print Cartridges Number	1 (1 black cartridge)	Media Sizes Custom	Tray 1: 3.86 x 5.83 to 11.69 x 17 in; Tray 2: 5.48 x 8.27 to 11.69 x 14.33 in; Tray 3: 5.48 x 8.27 to 11.6 x 17 in
Standard Print languages	HP PCL 6, HP PCL 5c, HP Postscript level 3 emulation, PDF (v 1.7), AirPrint™ compatible	Paper Handling	100-sheet input tray, 520-sheet input tray, 520-sheet input tray, 100 sheet ADF; 500 sheet face-down
Printer Smart Software Features	NBusinesses that stay ahead don't slow down. It's why HP built the next generation of HP LaserJet MFPs—to power productivity with a streamlined design that delivers professional quality, maximum uptime, and the strongest security. Î quality printing for a great value is a smart choice for any business.	•	order thin Duplex Options: Automatic (standard); Auto Document Feeder Capacity: Standard, 100 sheets; Envelope Feeder: No; Standard Paper Trays; 3: Input Capacities: Up to 520 sheets; Output Capacities: Up to 500 sheets; Up to 40 envelopes
	Produce premium, professional-quality documents at a competitive low cost with an HP Laser let MFP built to make your work—and your business—look its best. Annoying interruptions and complex maintenance can slow down printing, and ultimately, the pace of business. Avoid pauses in productivity with an HP Laser let MFP designed for maximum uptime, so you can count on reliable, results day in and day out. Only HP Enterprise printers repair themselves from attacks in real time, delivering built-in security to help keep your network safe. Automatically monitor threats, detect intrusions, and validate operating software with security of freed only by HP. Accelerate workflow, improve accuracy, and easily connect people throughout your organization. Complete high-volume scan jobs fast—up to 180 ipm ¹⁰ —and avoid extra steps with a Flow MFP designed for maximum productivity.	What's in the box	Engine; TCU; Drums; Assy-Color WG Nameplate and Label; Power Cords; Assembly-CD WW; Hardware install and setup documentation; Support flyers (DOES NOT INCLUDE TONER) ¹
		Replacement Cartridges	HP Black Managed LJ Toner Cartridge (ISO Yield 48,000) W9005MC ⁸
		Product Dimensions	W x D x H : 22.3 x 28.5 x 32.6 in; Maximum : 47 x 50 x 30.5 in
		Product Weight	150.2 lb
		Warranty Features	90 day parts only. Extended Warranty and support options vary by product, country and local legal
Printer Management	Printer Administrator Resource Kit for HP Universal Print Driver (UPD Active Directory Administrator Template, Add Print Model to Comments, AutolugradeuPD, Driver Configuration Utility, Driver Deployment Utility, HP Managed Printing Administration, PRIXCDN DKE, HPPRIZO, Migrate-Server-Tools, UpdateNow, Remove Plug and Play Drivers); HP Web Jetadmin Software; Resource Kit for HP Web Jetadmin (HP SNMP Proxy Agent, HP MS Pro Proxy Agent); HP JetAdwantage Security Manager		requirements. Go to http://www.hp.com/support to learn about HP award winning service and support options in your region.
		Energy Efficiency Compliance	Energy Star; Blue Angel; EPEAT silver
		Control Panel	8.0-in (20.3 cm) Color Graphics Display (CGD) with touchscreen; rotating (adjustable angle) display;
Scan Type / Technology	Flatbed, ADF / Flatbed; ADF		illuminated Home button (for quick return to the Home menu); USB High-speed 2.0 port; Hardware
Scan Resolution	Hardware: Up to 600 x 600 dpi; Optical: Up to 600 x 600 dpi	Display Description	Integration Pocket; Extended Keyboard
Scan File Format	Digital Send: PDF, Hi-Compression PDF, JPEG, TIFF, MTIFF, XPS, PDF/A; Scan to easy access USB: PDF,	Software Included	8.0-in (20.3 cm) touchscreen, SVGA Color Graphic Display (CGD)
Scan Input Modes	JPEG, TIFF, MTIFF, XPS, DPI/A, Print from easy access USE: PDP, PS, Print Rade, files (p.m., p.d., cht) Front panel applications: Copy, E-mail; Fax; Save to Network Folder; Save to USE; Save to Device	Software included	HP Connected, HP Device Experience (DXP), HP PCL 6 Printer Driver, HP Software Installer/Uninstaller, Mac OS Welcome Screen (Directs users to 123.HP.com or OS App Source for printer software), Online user manuals
	Memory; Open Extensibility Platform (OXP) applications	Fonts and Typefaces	84 scalable TrueType fonts
Scan Size	ADF : 11 x 17 in Maximum; 5.5 x 8.5 in Minimum; Flatbed : 11 x 17 in	Compatible Operating Systems	Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3,
Scan Speed	Up to 80 ppm/160 ipm (b&w), up to 80 ppm/160 ipm (color) 9 Duplex: Up to 160 ipm (b&w), up to 160 ipm (color)		8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterp (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macoOS 11 Sierra, OS X 10.10 Yosemite, OS X 10.11 El Capitan, UNIX, Windows 10 all 32- & 64-bit editions
Scanner Advanced Features	Scan-to-E-mail; Scan-to-network folder (stand alone solution); Scan to Cloud; Scan to USB		(excluding RT OS for Tablets), Windows 7 all 32- & 64-bit editions, Windows 8/8.1 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows Vista all 32bit editions (Home Basic, Premium,
Bit depth / Grayscale levels	24-bit / 256		Professional, etc.), Windows XP SP3 32-bit editions (XP Home, XP Pro, etc.)
Digital Sending Standard Features	Scan to E-mail; Save-to-Network Folder; Save-to-USB drive; Send to Sharepoint; Send to FTP; Send to sFTP; Send to LAN Fax; Send to Internet Fax; Local Address Book; SMTP over SSL; Blank Page Removal; Edge Frase; Auto Color Sense; Auto Crop To Content; Compact PDF; Auto Tonescale; Auto Orientation; Multi-Pick Detect; Auto Straighten; Auto Crop To Page	Compatible Network Operating Systems	Citrix MetaFrame Presentation Server 3.0, Citrix MetaFrame XP Presentation Server (Feature Release 2, and 3), Citrix on Windows Server 2003/2003R2, Citrix on Windows Server 2008/2008R2/2008 R2. SP1, Citrix on Windows Server 2012/2012R2, Citrix Presentation Server 4.014, Citrix Xenapp 5.0 (P. Feature Pack 2.8.3) for Windows Server 2008 Terminal Services 32—and 64-bit, Citrix Xenapp 6.0 (6.5.1) (Feature Pack 2.8.3) for Windows Server 2008 Terminal Services 32—and 64-bit, Citrix Xenapp 6.0 (6.5.1) (Feature 2.2) and 64-bit). Citrix Xenapp 6.0 (6.5.1) (Feature 2.2) (Feature
Copy Speed	Black (letter): Up to 25 cpm		[for Windows Server 2008 R2 Terminal Services, 32- and 64-bit], Citrix XenApp 6.0/6.5/7.5 [for Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit], Citrix XenApp 7.5 [for Windows
Copy Resolution	Black (text and graphics): Up to 600 × 600 dpi; Up to 600 × 600 dpi		Server 2012 and 2012 R2 Terminal Services, 64-bit], Citrix XenDesktop 5.6 [for Windows Server 2008 R2 Terminal Services, 32- and 64-bit], Citrix XenDesktop 5.6/7.0/7.5 [for Windows Server 2008 R2 SP Terminal Services, 32- and 64-bit], Citrix XenDesktop 7.0/7.5 [for Windows Server 2012 and 2012 R2
Maximum Number Of Copies	Up to 999 copies		Terminal Services, 64-bit], Novell NetWare 6.5/SP8 Novell Clients www.novell.com/iprint, Novell iPrint Appliance v1.0, Novell Open Enterprise Server 11/SP1, Novell Open Enterprise Server 2 for Linux, Nove
pier Resize pier Settings	25 to 400%		Servers www.noell.com/printl, Windows Server 2003/2003 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Dataenter (* Lüster & Ferminal Services), Windows Server 2003/2003 R2 32-bit (SP1/SP2), Standard/Enterprise (* Cluster & Terminal Services), Windows Server 2008 32-/64-bit (SP2 Standard/Enterprise (* Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (* Cluster & Terminal Services), Windows Server 2008/2008 R2 32-/64-bit
copier Settings	Two-sided copying; scalability; image adjustments (darkness, contrast, background cleanup, sharpness); optimized text/picture (text, mixed, printed picture, photograph); N-Up; N or Z-ordering;		
	content orientation; collation; booklet; ID Scan; job build; job Storage; watermark; stamps; book mode scans; erase edges; automatically detect color/mono; image Preview		
Fax Speed	content orientation; collation; booklet; ID Scart, job build; job Storage; watermark; stamps; book mode scans; erase edges; automatically detect color/mono; image Preview Up to: 33.6 kbps; Letter: 3 sec per page ²		(SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Server
	scans; erase edges; automatically detect color/mono; image Preview	Minimum Cunham Danulaum ante	(SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 126 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services)
Fax Resolution	Scans; erase edges; automatically detect color/mono; image Preview Up to: 33.6 kbps; Letter: 3 sec per page ² Black (best): Up to: 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi Fax Memory: Up to: 500 pages; Auto Fax Reduction Supported: Yes; Auto-Redialing: Yes; Fax Delayed Sending: No: Distinctive Ring Detection Supported: No: Fax Forwarding Supported: Yes; Fax Phone TAM	Minimum System Requirements	(SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services) PC 2 GB available hard disk space; OS hardware requirements see microsoft.com; MAC 1.3 GB available hard drive space; Internet; OS hardware requirements see Apple.com for more info
Fax Resolution	scans; erase edges; automatically detect color/mono; image Preview Up to: 33.6 kbps; Letter: 3 sec per page ² Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi Fax Memory: Up to 500 pages; Auto Fax Reduction Supported: Yes: Auto-Redialing: Yes: Fax Delayed Sending: No; Distinctive Ring Detection Supported: No; Fax Forwarding Supported: Yes; Fax Phone TAM Interface Supported: No; Fax Polling Supported: Yes: Maximum Speed Dialing Numbers: Up to 1000 numbers Geach with 210 destinations; PC Interface Supported: Yes: Render Retrieval Capability Supported: No;	Power	(SPT/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve PC 2 GB available hard disk space; 05 hardware requirements see microsoft.com; MAC 1.3 GB available hard drive space; Internet, O5 hardware requirements see Apple com for more info Power Supply Type: Internal (Built-in) power supply; Power Requirements: Input voltage: 110 to 127Va (+/- 10%), 220 to 240Vac (+/- 10%), 50/60 Hz (*/- 3%); 6
Fax Resolution Fax Features	scans; erase edges; automatically detect color/mono; image Preview Up to: 33.6 kbps; Letter: 3 sec per page ² Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi Fax Memory. Up to 500 pages; Auto Fax Reduction Supported: Yes: Auto-Redialing: Yes: Fax Delayed Sending: No: Distinctive Ring Detection Supported: No: Fax Forwarding Supported: Yes: Fax Phone TAM Interface Supported: No: Fax Polling Supported: Yes (poll to receive only): Fax Telephone Mode Supported: No: Junk Barrier Supported: Yes: Maximum Speed Dialing Numbers: Up to 1000 numbers (each with 210 destinations): Pol Interface Supported: Yes: Remote Retrieval Capability Supported: No; Telephone Handset Supported: No		(SPT/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/ Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve PC 2 GB available hard disk space, 05 hardware requirements see microsoft.com; MAC 1.3 GB available hard drive space; Internet, O5 hardware requirements see Apple com for more info Power Supply Type: Internal (Built-in) power supply; Power Requirements: Input voltage: 110 to 127Ve (+/- 10%), 220 to 240Vac (+/- 10%), 50/60 Hz (*/- 3%); 6
Fax Resolution Fax Features Standard Connectivity	Up to 33.6 kbps; Letter. 3 sec per page ² Black (best)* Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi Fax Memory. Up to 500 pages; Auto Fax Reduction Supported. Yes; Auto-Redialing: Yes; Fax Delayed Fax Memory. Up to 500 pages; Auto Fax Reduction Supported. Yes; Auto-Redialing: Yes; Fax Delayed Interface Supported. No; Fax Polling Supported vise (poll to receive only); Fax Telephone Mode Supported: No; Junk Barrier Supported vise; Marium Speed Dillang Numbers: Up to 1000 numbers (each with 210 destinations); PC Interface Supported. Yes; Remote Retrieval Capability Supported. No; Telephone Handset Supported. No 2 Hi-Speed USB 2.0 Host: 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port	Power	(SPT/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016 (64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016 (64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services) PC: 2 GB available hard disk space; OS hardware requirements see microsoft.com; MAC: 1.3 GB available hard drive space; Internet, OS hardware requirements see Apple.com for more info Power Supply Type: Internal (Built-in) power supply; Power Requirements: Input voltage: 110 to 127Va (+1 10%), 220 to 240Vac (+1 10%), 50/G0 Hz (+1 3%); ⁵ Acoustic Power Emissions: 6.5 B(A), printing mono simplex, A4 at 25 ppm; Acoustic Pressure Emissions 49 dB(A), printing mono simplex, A4 at 25 ppm Operating Temperature Range: 59 to 86%; Recommended Operating Temperature: 59 to 86%; Storag Temperature Range: 14 to 104%; Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity
Fax Resolution Fax Features Standard Connectivity Network Capabilities	Up to 33.6 kbps; Letter. 3 sec per page ² Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi Fax Memory. Up to 500 pages; Auto Fax Reduction Supported. Yes; Auto-Redialing: Yes; Fax Delayed Fax Memory. Up to 500 pages; Auto Fax Reduction Supported Yes; Auto-Redialing: Yes; Fax Delayed Fax Memory. Up to 500 pages; Auto Fax Reduction Supported Yes; Fax Pelayed Fax Memory. Up to 500 pages; Auto Fax Reduction Supported Yes; Fax Pelayed Interface Supported No.: Fax Polling Supported Yes; Fax Telephone Mode Supported No.: Junk Barrier Supported Yes; Mawimum Speed Dillaing Numbers: Up to 1000 numbers (each with 210 destinations); PC Interface Supported: Yes; Remote Retrieval Capability Supported: No; Telephone Handset Supported: No. ZHi-Speed USB 2.0 Host; 11 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port Standard (built-in Gigabit 10/100/1000T Ethernet)	Power Acoustics Operating Environment	(SP1/SP2) Standard/Enterprise/Datacenter (- Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (- Cluster & Terminal Services), Windows Serve 2016 (64-bit Standard/Essential/Datacenter (- Cluster & Terminal Services), Windows Serve 2016 (64-bit Standard/Essential/Datacenter (- Cluster & Terminal Services). Windows Serve PC: 2 GB available hard disk space; OS hardware requirements see microsoft.com; MAC: 1.3 GB available hard drive space; Internet, OS hardware requirements see Apple.com for more info Power Supply Type: Internet (Built-in) power supply; Power Requirements: Input voltage: 110 to 127Ve (+/- 10%), 220 to 240Vac (+/- 10%), 50/G0 Hz (+/- 3%); ⁵ Acoustic Power Emissions: 6.5 B(A), printing mono simplex, A4 at 25 ppm; Acoustic Pressure Emission: 49 dB(A), printing mono simplex, A4 at 25 ppm Operating Temperature Range: 59 to 86%F; Recommended Operating Temperature: 59 to 86%; Storag Temperature Range: 14 to 104%; Non-Operating Humidity Range: 20 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Page: Pa
Fax Resolution Fax Features Standard Connectivity Network Capabilities Network Ready	Up to 33.6 kbps; Letter. 3 sec per page ² Black (best): Up to 300 x300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi Fax Memory. Up to 500 pages; Auto Fax Reduction Supported. Yes; Auto-Redialing: Yes; Fax Delayed Sending: No; Distinctive Ring Detection Supported No; Fax Forwarding Supported Yes; Fax Phone TAM Interface Supported. No: Fax Polling Supported Ves (poll to receive only): Fax Telephone Mode Supported No; Junk Barrier Supported Ves; Mawimum Speed Dialing Numbers: Up to 1000 numbers (each with 210 destinations); PC Interface Supported Ves; Remote Retrieval Capability Supported. No; Telephone Handset Supported. No 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port Standard (built-in Gigabit 10/100/1000T Ethernet)	Power	(SPT/SP2) Standar/Enterprise/Datacenter (- Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standar/Enudation/Essentials/Datacenter (- Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (- Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/ Essential/Datacenter (- Cluster & Terminal Services) PC 2 GB available hard disk space; OS hardware requirements see microsoft.com; MAC: 1.3 GB available hard drive space; Internet; OS hardware requirements see Apple.com for more info Power Supply Type: Internal (Built-in) power supply; Power Requirements: Input voltage: 110 to 127Ve (+-1 10%), 220 to 240Vac (+/- 10%), 50/G0 Hz (+/- 3%); ⁵ Acoustic Power Emissions: 6.5 B(A), printing mono simplex, A4 at 25 ppm; Acoustic Pressure Emission 49 dB(A), printing mono simplex, A4 at 25 ppm Operating Temperature Range: 59 to 86°F; Recommended Operating Temperature: 59 to 86°F; Storag Temperature Range: 14 to 104°F; Non-Operating Humidity Range: 20 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH Management security: SNMPV3, SSL/TLS, WPA2-Enterprise, 802.1X authentication, and Kerberos
Fax Resolution Fax Features Standard Connectivity Network Capabilities Network Ready	Up to 33.6 kbps; Letter. 3 sec per page ² Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi Fax Memory. Up to 500 pages; Auto Fax Reduction Supported. Yes; Auto-Redialing: Yes; Fax Delayed Fax Memory. Up to 500 pages; Auto Fax Reduction Supported Yes; Auto-Redialing: Yes; Fax Delayed Fax Memory. Up to 500 pages; Auto Fax Reduction Supported Yes; Fax Pelayed Fax Memory. Up to 500 pages; Auto Fax Reduction Supported Yes; Fax Pelayed Interface Supported No.: Fax Polling Supported Yes; Fax Telephone Mode Supported No.: Junk Barrier Supported Yes; Mawimum Speed Dillaing Numbers: Up to 1000 numbers (each with 210 destinations); PC Interface Supported: Yes; Remote Retrieval Capability Supported: No; Telephone Handset Supported: No. ZHi-Speed USB 2.0 Host; 11 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port Standard (built-in Gigabit 10/100/1000T Ethernet)	Power Acoustics Operating Environment Security Management	(SPT/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 2
Fax Resolution Fax Features Standard Connectivity Network Capabilities Network Ready Wireless Capability	Up to 33.6 kbps; Letter. 3 sec per page ² Black (best): Up to 300 x 300 dpi (400 x 400 bit for received faxes only); Black (standard): 203 x 98 dpi lex (best): Up to 300 x 300 dpi (400 x 400 bit for received faxes only); Black (standard): 203 x 98 dpi lex (best): Up to 500 pages; Auto Fax Reduction Supported. Yes; Auto-Redialing; Yes; Fax Delayed Sending; No. Distinctive Ring Detection Supported No: Fax Forwarding Supported. Yes; Fax Phone TAM Interface Supported. No. Fax Polling Supported Ves; Fax Telephone Mode Supported. Yes, Maximum Speed Dialing Numbers: Up to 1000 numbers (each with 210 destinations); PC Interface Supported. Yes; Remote Retrieval Capability Supported. No. Telephone Handset Supported. No. 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Handware Integration Pocket; 1 Fax modern port. Standard (built-in Gigabit 10/100/1000T Ethernet) Standard (built-in Gigabit 10/100/1000T Ethernet) No wireless capabilities standard. There are optional accessories (common to all current Jedi products)	Power Acoustics Operating Environment	(SPT/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), WAC: 1.3 GB available hard drive space; Internet, Ob Fardware requirements see emicrosoft.com; MAC: 1.3 GB available hard drive space; Internet, Ob Fardware requirements see polye com for more info Power Supply Type: Internal (Built-in) power supply; Power Requirements: Input voltage: 110 to 127Va (+/- 10%), 220 to 240Vac (+/- 10%), 50/60 Hz (+/- 3%); Acoustic Power Emissions: 6.5 B(A)), printing mono simplex, A4 at 25 ppm; Acoustic Pressure Emissions 49 d8(A), printing mono simplex, A4 at 25 ppm Operating Temperature Range: 91 to 86%; Recommended Operating Temperature: 59 to 86%; Storag Temperature Range: 14 to 104%; Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 80.2.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPSec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WAIA-10 IPsec Configuration using Pisec Plug-1 Cabinet Workgroup Y1G17A, Dual Cassette Feeder (2x520) Workgroup Y1F97A, 2000 Sheet HCl WG Y1F99A, Inner Finisher Hole Dunch Swelsth V1G04A, Stapler/Stacker Finisher Filoshe Puch Swelsth V1G04A, Stapler/Stacker Finisher Filoshe Puch Swelsth V1G04A, Stapler/Stacker Finisher FIG18A, Booklef Finisher
Fax Resolution Fax Features Standard Connectivity Network Capabilities Network Ready Wireless Capability Mobile Printing Capability	Up to 33.6 kbps; Letter. 3 sec per page? Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi lex (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi lex (best): Up to 500 pages; Auto Fax Reduction Supported. Yes; Auto-Redialing; Yes; Fax Delayed Sending; No. Distinctive Ring Detection Supported No: Fax Forwarding Supported. Yes; Fax Delayed Sending; No. Distinctive Ring Detection Supported No: Fax Forwarding Supported. Yes; Fax Delayed No. Take Telephone Mode Supported. Yes (make Take Supported. Yes; Remote Retrieval Capability Supported. No. Telephone Handset Supported. No. 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port Standard (built-in Gigabit 10/100/1000T Ethernet) No wireless capabilities standard. There are optional accessories (common to all current Jedi products) that support wireless. These are listed in the connectivity section, above. Management security. SNMPv3, SSL/TLS, WPA2-Enterprise, 802.11X authentication (EAP- PEAP, EAP-TLS, IPP Over TLS, IPSec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos	Power Acoustics Operating Environment Security Management	(SPT/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), WAC 1.3 GB available hard drive space; Internet, Ob Fardware requirements see microsoft.com; MAC 1.3 GB available hard drive space; Internet, Ob Fardware requirements see polye com for more info Power Supply Type: Internal (Built-in) power supply; Power Requirements: Input voltage: 110 to 127Va (+/- 10%), 220 to 240Vac (+/- 10%), 50/60 Hz (+/- 3%); Acoustic Power Emissions: 6.5 B(A)), printing mono simplex, A4 at 25 ppm; Acoustic Pressure Emissions 49 d8(A), printing mono simplex, A4 at 25 ppm Operating Temperature Range: 59 to 86%; Recommended Operating Temperature: 59 to 86%; Storag Temperature Range: 14 to 104%; Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 80.2.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPSec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WA1-10 IPsec Configuration using Pisec Plug-in Cabinet Workgroup Y1G17A, Dual Cassette Feeder (2x-S20) Workgroup Y1F97A, 2000 Sheet HCl WG Y1F99A, Inner Finisher V1G00A, Inner Finisher Hole Punch 2/3 Y1G02A, Inner Finisher Hole Punch 2/3 Y1G03A, Apple Y1G18A, Booklet Finishe Y1G07A, Stapler/Stacker Finisher Y1G18A, Booklet Finishe Y1G07A, Stapler/Stacker Finisher Y1G18A, Polket Finishe Y1G07A, Stapler/Stacker Finisher Y1G1A, Job Separator WG Y1G15A, Tay-Rader WG Y1G18A, Tay-Rader WG Y
Fax Resolution Fax Features Standard Connectivity Network Capabilities Network Ready Wireless Capability Mobile Printing Capability Memory Processor Speed	Up to 33.6 kbps; Letter. 3 sec per page ² Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard); 203 x 98 dpi lesk (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard); 203 x 98 dpi lesk (best): Up to 500 pages; Auto Fax Reduction Supported No; Fax Honor TAM interface Supported. No; Fax Polling Supported No; Tax Polling Supported No; Tax Polling Supported No; Telephone Mandset No; Telephone Mandset Supported No; Telephone Mandset No; Telephone No; Telephone Mandset No; Telep	Power Acoustics Operating Environment Security Management	(SPT/SP2) Standard/Enterprise/Datacenter (- Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essential/Datacenter (- Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (- Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (- Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 20
Fax Resolution Fax Features Standard Connectivity Network Capabilities Network Ready Wireless Capability Mobile Printing Capability Memory Processor Speed	Up to 33.6 kbps; Letter. 3 sec per page? Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi pi Fax Memory. Up to 500 pages; Auto Fax Reduction Supported: Yes; Auto-Redialing; Yes; Fax Delayed Sending; No. Distinctive Ring Detection Supported No; Fax Forwarding Supported: Yes; Fax Phone TAM Interface Supported: No. Fax Polling Supported: Yes; Gibbs; Tax Telephone Manigh Numbers: Up to 1000 numbers (each with 210 destinations); PC Interface Supported: Yes; Remote Retrieval Capability Supported: No. Telephone Handset Supported: No. 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port 2 Hardware Integration Pocket; 1 Fax modem port 3 Standard (built-in Gigabit 10/100/1000T Ethernet) No wireless capabilities standard. There are optional accessories (common to all current Jedi products) that support wireless. These are listed in the connectivity section, above. Management security: SNMPV3, SSL/TLS, WPA2-Enterprise, 802.11X authentication (EAP- PEAP, EAP-TLS, IPP Over TLS, IPSec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WIA-10 IPsec Configuration using IPsec Plug-in ⁴ Standard: 6 GB; Maxdmum; 6 GB 12 GHz; Hard dict. One 3 20 GB Standard, embedded HP High-Performance Secure Hard Disk; AES 256 hardware encyption or greater; Secure erase capabilities (Secure File Erase-Temporary Job Files, Secure Frase-1b Data, Secure AIA Erase-Disk), Note: U.S., government SKU uses 500GB Files 140-2 validated hard rids instead.	Power Acoustics Operating Environment Security Management	(SPT/SP2) Standard/Enterprise/Datacenter (- Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essential/Datacenter (- Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (- Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (- Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 26-bit Services, Windows Serve 2016/ 26-bit Services, Windows Serve 2016/ 26-bit Services, Windows Serve 2016/
Fax Resolution Fax Features Standard Connectivity Network Capabilities Network Ready Wireless Capability Mobile Printing Capability Memory Processor Speed Duty Cycle Recommended Monthly Page Volume	Up to 33.6 kbps; Letter. 3 sec per page ² Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi pi Fax Memory. Up to 500 pages; Auto Fax Reduction Supported. Yes; Auto-Redialing; Yes; Fax Delayed Sending; No. Distinctive Ring Detection Supported No. Fax Forwarding Supported. Yes; Fax Phone TAM Interface Supported. No. Fax Polling Supported Ves (poll to receive only); Fax Telephone Mode Supported: No. Interface Supported. Yes; Remote Retrieval Capability Supported. No. Telephone Handset Supported. No. Telephone Handset Supported. No. 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port. Standard (built-in Gigabit 10/100/1000T Ethernet) Standard (built-in Gigabit 10/100/1000T Ethernet) No wireless capabilities standard. There are optional accessories (common to all current Jedi products) that support wireless. These are listed in the connectivity section, above. Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.11X authentication (EAP- PEAP, EAP-TLS), IPP Over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WIA-10 IPsec Configuration using IPsec Plug-in ⁴ Standard: 6 GB; Maximum: 6 GB	Acoustics Operating Environment Security Management Accessories	(SPT/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/ 2
Fax Speed Fax Resolution Fax Features Standard Connectivity Network Capabilities Network Ready Wireless Capability Mobile Printing Capability Memory Processor Speed Duty Cycle Recommended Monthly Page Volume Media Types Supported	Up to 33.6 kbps; Letter. 3 sec per page? Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Black (standard): 203 x 98 dpi pi Fax Memory. Up to 500 pages; Auto Fax Reduction Supported: Yes; Auto-Redialing; Yes; Fax Delayed Sending; No. Distinctive Ring Detection Supported No; Fax Forwarding Supported: Yes; Fax Phone TAM Interface Supported: No. Fax Polling Supported: Yes; Gibbs; Tax Telephone Manigh Numbers: Up to 1000 numbers (each with 210 destinations); PC Interface Supported: Yes; Remote Retrieval Capability Supported: No. Telephone Handset Supported: No. 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket; 1 Fax modem port 2 Hardware Integration Pocket; 1 Fax modem port 3 Standard (built-in Gigabit 10/100/1000T Ethernet) No wireless capabilities standard. There are optional accessories (common to all current Jedi products) that support wireless. These are listed in the connectivity section, above. Management security: SNMPV3, SSL/TLS, WPA2-Enterprise, 802.11X authentication (EAP- PEAP, EAP-TLS, IPP Over TLS, IPSec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WIA-10 IPsec Configuration using IPsec Plug-in ⁴ Standard: 6 GB; Maxdmum; 6 GB 12 GHz; Hard dict. One 3 20 GB Standard, embedded HP High-Performance Secure Hard Disk; AES 256 hardware encyption or greater; Secure erase capabilities (Secure File Erase-Temporary Job Files, Secure Frase-1b Data, Secure AIA Erase-Disk), Note: U.S., government SKU uses 500GB Files 140-2 validated hard rids instead.	Acoustics Operating Environment Security Management Accessories	(SPI/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/201 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), Windows Serve 2016/64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services), WAC 1.3 GB available hard drive space; Internet, Os hardware requirements see environsoft.com; MAC 1.3 GB available hard drive space; Internet, Os hardware requirements see polye com for more info Power Supply Type: Internal (Built-in) power supply; Power Requirements: Input voltage: 110 to 127Va (+/- 10%), 220 to 240Vac (+/- 10%), 50/60 Hz (+/- 3%); S Acoustic Power Emissions 6, 5.8 (Al), printing mono simplex, A4 at 25 ppm; Acoustic Pressure Emissions 49 d8(Al), printing mono simplex, A4 at 25 ppm; Operating Temperature Range: 59 to 86%; Recommended Operating Temperature: 59 to 86%; Storag Temperature Range: 14 to 104%; Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Deprating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Operating Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Recommended Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Recommended Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Recommended Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80% RH; Recommended Humidity Range: 20 to 80% RH; Recommended Humidity Operating Range: 20 to 80

Learn more at hp.com

¹ No, please purchase USB cable separately (EMEA, Americas; AP) (Service Technician must install units) ² Based on standard ITU-T test image #1 at standard resolution and MMR encoding, the HP fax device can transmit at 3 sec/page for V.34 and 6 sec/page for V.17 ³ Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. ⁴ Optional Wireless Direct and Wireless ⁵ Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit http://www.hp.com/go/learnaboutsupplies ⁶ Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. ⁷ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. ⁸ Average color composite black declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/learnaboutsupplies ⁹ Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple inc., registered in the U.S. and other countries.

