



KONICA MINOLTA

Giving Shape to Ideas

PROJET® X60 SERIES PROFESSIONAL 3D PRINTERS

BRING A NEW DIMENSION TO YOUR IDEAS

COLOR 3D PRINTING THAT MAKES AN IMPACT

Get ready to put your ideas in the palm of your hand. The ProJet® x60 Series offers full color 3D professional printing, in large capacity and high resolution, that lets you think big and bold—and then brings it to life for you. It's fast—5x–10x faster than other technologies. It's full color. And its affordable for all environments.

Konica Minolta is setting the standard with dramatic full color 3D prints that communicate your best design ideas. Quickly. And accurately. Just another reason you can count on Konica Minolta.



SETTING THE STANDARD FOR

TRUE FULL COLOR 3D PRINTING, SPEED & AFFORDABILITY



PROJET X60 PROFESSIONAL 3D PRINTERS

UNIQUELY FULL COLOR

Color & high-quality dramatically communicate design intent

- Produce realistic or vivid color models in one step
- Better communicate the look, feel, and style of product designs
- 3D print text labels, logos, design comments, or images directly onto models
- A range of options, from monochrome printing to professional quality color
- Multiple print heads provide the best range of accurate and consistent colors

SAFE, OFFICE FRIENDLY & EASY TO USE

Ideal for everyday use in any office or school

- Quiet, safe, odor free
- Continuous negative pressure contains airborne particles
- Eco-friendly, non-hazardous build materials
- Zero liquid waste
- No support structures to remove, no cutting tools or toxic chemicals
- Requires minimal training and expertise
- Intuitive control panel for easy operation

FASTEST PRINT SPEED

High-speed and throughput for a range of applications

- 5x–10x faster than all other technologies
- Output models in hours, not days
- Build multiple models at the same time
- Support an entire department with ease

LOWEST OPERATING COST

Affordable for all environments

- Unused core material is recycled for the next build, eliminating waste
- No physical supports are necessary
- Part costs are a fraction of competitive technologies
- Based on reliable, affordable ColorJet Printing (CJP) technology



Easiest Connectivity

Tablet and smartphone connect remotely



Large Parts Capacity

High throughput for high volumes of prototypes or very large models

High Full Color Resolution

Realistic models, prototypes and precise details





Specialized Applications

- Mechanical Design
- Healthcare
- AEC
- Education
- Geospatial
- Entertainment
- Architecture
- Engineering
- Construction

Visijet® Material for ProJet X60 Series

The VisiJet® line of materials offers numerous capabilities to meet a variety of commercial applications. Using the ColorJet Printing (CJP) technology, 3D Systems' ProJet x60 3D Printers use the VisiJet® PXL™ material set to build strong, high-definition, full color concept models, assemblies and prototypes, for design realization, advanced communication, as well as development and production cost reduction.

Printed models benefit transportation, energy, consumer products, recreation, healthcare, education and other vertical markets. Parts can be sanded, drilled, tapped, painted and electroplated, which further expands the options available for finished part characteristics. Additionally, models have high-temperature resistance, ideal for digital manufacturing and molding applications.

Infiltrated Parts Properties

Infiltrant	ColorBond™	StrengthMax™	Salt Water Cure™
Composition	VisiJet PXL	VisiJet PXL	VisiJet PXL
Tensile Strength, MPa	14.2	26.4	2.38
Elongation at Break, %	0.23	0.21	0.04
Modulus of Elasticity, MPa	9,450	12,560	12,855
Flexural Strength, MPa	31.1	44.1	13.1
Flexural Modulus, MPa	7,163	10,680	6,355
Description	Instant-cure infiltrant ideal for color models to improve strength and color vibrancy and retention.	Two-part infiltrant ideal for functional models to dramatically improve the strength of the model.	Eco-friendly and hazard-free infiltrant. Ideal for monochrome models and draft-color. Provides additional surface hardness and modulus upon dipping, or spraying.

PROJET X60 SERIES

PROFESSIONAL 3D PRINTERS



ProJet 160

ProJet 260C

ProJet 360

ProJet 460Plus

ProJet 660Pro

ProJet 860Pro

Resolution	300 x 450 dpi	300 x 450 dpi	300 x 450 dpi	300 x 450 dpi	600 x 540 dpi	600 x 540 dpi
Color	White (monochrome)	Basic CMY	White (monochrome)	Full CMY	Full CMYK	Full CMYK
Pastel or Vibrant Color Options	–	–	–	–	•	•
Minimum Feature Size	0.016" (0.4 mm)	0.016" (0.4 mm)	0.006" (0.15 mm)	0.006" (0.15 mm)	0.004" (0.1 mm)	0.004" (0.1 mm)
Layer Thickness	0.004" (0.1 mm)	0.004" (0.1 mm)	0.004" (0.1 mm)	0.004" (0.1 mm)	0.004" (0.1 mm)	0.004" (0.1 mm)
Vertical Build Speed	0.8 inch/hour (20 mm/hour)	0.8 inch/hour (20 mm/hour)	0.8 inch/hour (20 mm/hour)	0.9 inch/hour (23 mm/hour)	1.1 inch/hour (28 mm/hour)	0.2–0.6 inch/hour* (5–15 mm/hour)*
Prototypes per Build**	10	10	18	18	36	96
Draft Printing Mode (monochrome)	–	–	–	–	•	•
Net Build Volume (xyz)	9.3 x 7.3 x 5" (236 x 185 x 127 mm)	9.3 x 7.3 x 5" (236 x 185 x 127 mm)	8 x 10 x 8" (203 x 254 x 203 mm)	8 x 10 x 8" (203 x 254 x 203 mm)	10 x 15 x 8" (254 x 381 x 203 mm)	20 x 15 x 9" (508 x 381 x 229 mm)
Build Materials	VisiJet PXL	VisiJet PXL	VisiJet PXL	VisiJet PXL	VisiJet PXL	VisiJet PXL
Number of Jets	304	604	304	604	1520	1520
Number of Print Heads	1	2	1	2	5	5
Automated Setup & Self Monitoring	•	•	•	•	•	•
Core™ Recycling	•	•	•	•	•	•
Automatic Build Platform Clearing	–	–	–	•	•	•
Fine Core™ Removal	Accessory	Accessory	Integrated	Integrated	Integrated	Accessory
Integrated Materials	•	•	•	•	•	•
Intuitive Control Panel	•	•	•	•	•	•
Email Notice Capability	•	•	•	•	•	•
Tablet/Smartphone Connectivity	•	•	•	•	•	•
Print3D App	Remote monitoring and control from tablet, computers and smartphones					
Input Data File Formats Supported	STL, VRML, PLY, 3DS, FBX, ZPR	STL, VRML, PLY, 3DS, FBX, ZPR	STL, VRML, PLY, 3DS, FBX, ZPR	STL, VRML, PLY, 3DS, FBX, ZPR	STL, VRML, PLY, 3DS, FBX, ZPR	STL, VRML, PLY, 3DS, FBX, ZPR
Client Operating System	Windows® 7 and Vista®	Windows® 7 and Vista®	Windows® 7 and Vista®	Windows® 7 and Vista®	Windows® 7 and Vista®	Windows® 7 and Vista®
Operating Temperature Range	55–75 °F (13–24 °C)	55–75 °F (13–24 °C)	55–75 °F (13–24 °C)	55–75 °F (13–24 °C)	55–75 °F (13–24 °C)	55–75 °F (13–24 °C)
Operating Humidity Range	20–55% – non-cond.	20–55% – non-cond.	20–55% – non-cond.	20–55% – non-cond.	20–55% – non-cond.	20–55% – non-cond.
Dimensions (WxDxH)						
3D Printer Crated	37 x 47 x 62" (94 x 119 x 158 cm)	37 x 47 x 62" (94 x 119 x 158 cm)	55 x 45 x 62" (140 x 114 x 158 cm)	55 x 45 x 62" (140 x 114 x 158 cm)	86 x 48 x 63" (218 x 122 x 160 cm)	64 x 58 x 73" (163 x 147 x 185 cm)
3D Printer Uncrated	29 x 31 x 55" (74 x 79 x 140 cm)	29 x 31 x 55" (74 x 79 x 140 cm)	48 x 31 x 55" (122 x 79 x 140 cm)	48 x 31 x 55" (122 x 79 x 140 cm)	74 x 29 x 57" (188 x 74 x 145 cm)	47 x 46 x 68" (119 x 116 x 162 cm)
Weight						
3D Printer Crated	437 lbs (198 kg)	437 lbs (198 kg)	553 lbs (251 kg)	602 lbs (273 kg)	1116 lbs (507 kg)	987 lbs (448 kg)
3D Printer Uncrated	365 lbs (165 kg)	365 lbs (165 kg)	395 lbs (179 kg)	425 lbs (193 kg)	750 lbs (340 kg)	800 lbs (363 kg)
Electrical	90–100V, 7.5A 110–120V, 5.5A 208–240V, 4.0A	90–100V, 7.5A 110–120V, 5.5A 208–240V, 4.0A	90–100V, 7.5A 110–120V, 5.5A 208–240V, 4.0A	90–100V, 7.5A 110–120V, 5.5A 208–240V, 4.0A	100–240V, 15–7.5A	100–240V, 15–7.5A
Noise						
Building	57 dB	57 dB	57 dB	57 dB	57 dB	57 dB
Core Recovery	66 dB	66 dB	66 dB	66 dB	66 dB	66 dB
Vacuum (open)	86 dB	86 dB	86 dB	86 dB	86 dB	86 dB
Fine Decoring	–	–	80 dB	80 dB	80 dB	–
Office Compatibility	•	•	•	•	•	–
Certifications	CE, CSA	CE, CSA	CE, CSA	CE, CSA	CE, CSA	CE, CSA

*Speed increases with volume of prototypes **Based on baseball-size geometry



KONICA MINOLTA

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive, Ramsey, NJ 07446

CountOnKonicaMinolta.com



© 2014 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, Count on Konica Minolta, and Giving Shape to Ideas are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products.

Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

