



KONICA MINOLTA

bizhub C3850FS

- ✓ Colour A4 multifunctional
- ✓ Up to 38 pages per minute

Functionality



Copying

- Colour
- Black & white



Printing

- Colour
- Black & white
- PCL/PS
- Local/Network
- USB



Scanning

- Colour
- Black & white
- Scan-to-eMail
- Scan-to-SMB
- Scan-to-FTP
- Scan-to-HDD
- Scan-to-USB
- Scan-to-WebDAV
- TWAIN Network



Faxing

- Super G3 Fax
- PC-Fax
- i-Fax




Giving Shape to Ideas

Technology

Emperon™ – print controller	Easily compatible with different users and IT environments through Konica Minolta's unified print technology	✓
Simitri® HD – polymerised toner	Delivers high print quality and yet ensures reduced print spending as well as lower environmental impact	✓
OpenAPI – solution platform	Server-based applications provide efficient workflows for the entire MFP fleet	✓
i-Option – special feature	Offers extended scope and advanced MFP functionality in line with individual requirements	✓
CSRC – remote service	Keeps productivity up with online monitoring of devices and consumables through the Konica Minolta service	✓
IWS – panel customisation	Improved user-device interaction and enhanced productivity through full MFP panel customisation	✓

Option diagram



Finishing functionalities



Descriptions

bizhub C3850FS	A4 multifunctional with 38 ppm b/w and colour. Standard Emperon™ print controller with PCL, PostScript and XPS support. Paper capacity of 550 sheets and 100-sheet manual bypass. Automatic duplex document feeder and duplex unit standard. Stapling inner finisher, 1 GB memory, 320 GB hard disk and Gigabit Ethernet standard.
PF-P13 Paper tray	A4, 500 sheets, 60–90 gsm
DK-P03 Copier desk	Provides storage space for print media, etc.
FS-P03 Off-line stapler	20-sheet corner stapling
KP-101 10-Key pad	For use instead of touchscreen
WT-P02 Working table	Off-line stapler placement, etc.
FK-512 Fax board	Super G3 fax, digital fax functionality
EK-P01 Interface cable for CSRC modem	GPRS modem connection for CSRC

Technical specifications

SYSTEM SPECIFICATIONS

System memory	1 GB (standard) 2 GB (optional)
System hard disk	320 GB (standard)
Interface	10-Base-T/100-Base-TX/1,000-Base-T Ethernet; USB 2.0
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTPS
Frame types	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Automatic document feeder	Up to 50 originals; A5–A4; 50–128 gsm; reverse automatic document feeder
Printable paper size	A6–A4, customised paper sizes
Printable paper weight	60–210 gsm
Paper input capacity	Standard: 650 sheets Max.: 1,650 sheets
Tray 1	550 sheets, A6–A4, 60–210 gsm
Tray 2 (optional)	500 sheets, A4, 60–90 gsm
Tray 3 (optional)	500 sheets, A4, 60–90 gsm
Manual bypass	100 sheets, A6–A4, custom sizes, 60–210 gsm
Automatic duplexing	A4; 60–210 gsm
Finishing modes	Staple, offset sorting, offset grouping
Output capacity	Max.: 250 sheets
Stapling	Max.: 50 sheets
Copy/print volume (monthly)	Rec.: 6,500 pages Max. ¹ : 120,000 pages
Toner lifetime	CMYK: 10,000 pages
Imaging unit lifetime	CMYK: 60,000 pages
Power consumption	220–240 V/50/60 Hz, Less than 1.7 kW
System dimensions (W x D x H)	555 x 584 x 603 mm
System weight	Approx. 53 kg

COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD polymerised toner
Copy/print speed A4 (mono/colour)	Up to 38 ppm
Autoduplex speed A4 (mono/colour)	Up to 38 ppm
1st copy out time (mono/colour)	9.3 sec. 10.2 sec.
Warm-up time	Approx. 30 sec. ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–999
Original format	Max. A4
Magnification	25–400% in 0.1% steps; auto-zooming
Copy functions	Electronic sorting; multi-job; adjustments (contrast, sharpness, image density); proof copy; interrupt mode; colour mode; separate scan; sort/group; combination; original selection; ID card copy; 2-in-1; 4-in-1

ID card reader	Various ID card technologies
LK-101v3 Web browser	Web browser and IWS
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-111 ThinPrint® client	Print data compression for reduced network impact
MK-738 Fax mount kit	Installation kit for fax board
MK-P02 Mount kit	Installation kit for ID card reader
MK-P06 Mount kit	Installation kit for Wireless LAN
NC-P03 Wireless LAN	Wireless LAN to network connector and wireless LAN Access Point Mode
1 GB memory extension	For faster processing and for LK-101v3

PRINTER SPECIFICATIONS

Print resolution	600 x 600 dpi 1,200 x 1,200 dpi (reduced speed)
Page description language	PCL 6 (XL 3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows Vista (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003 (32/64) Windows Server 2003 R2 (32/64) Windows Server 2008 (32/64) Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 R2 Macintosh OS X Ver. 10.2.8 or later Linux Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Print functions	Direct print of TIFF, XPS, PDF and OOXML (DOCX, XLSX, PPTX); secure print; combination; n-up; poster; booklet page order; watermark
Mobile Printing	AirPrint (iOS), Mopria (Android), Google Cloud Print (optional), Konica Minolta Print Service (Android), PageScope Mobile (iOS & Android)

SCANNER SPECIFICATIONS

Scan speed (mono/colour)	Up to 35 opm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-eMail Scan-to-SMB Scan-to-FTP Scan-to-HDD Scan-to-USB Scan-to-WebDAV Network TWAIN scan
File formats	JPEG; TIFF; PDF; PDF/A (1b); Compact PDF; encrypted PDF; XPS
Scan destinations	2,100 (single + group); LDAP support
Scan functions	Up to 400 job programs

¹ If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

² Warm-up time may vary depending on the operating environment and usage

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analogue i-Fax
Fax resolution	Max.: 600 x 600 dpi (ultra-fine)
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)
Fax functions	Time shift; PC-Fax; fax forwarding; up to 400 program dials

SYSTEM FEATURES

Security	ISO 15408/IEEE 2600.1; IP filtering and port blocking; SSL2; SSL3 and TSL1.0 network communication; IPsec support; IEEE 802.1x support; user authentication; secure print; hard disk overwrite (8 standard types); hard disk data encryption, copy protection (print only)
Accounting	Up to 1,000 user accounts; Active Directory support ID card authentication optional
Software	PageScope Net Care Device Manager PageScope Direct Print Print Status Notifier Download Manager Driver Packaging Utility

- All specifications refer to A4-size paper of 80 gsm quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



Visit our product page



CORTADO

