

> PRINT > COPY > SCAN > FAX

ECOSYS M6030cdn ECOSYS M6530cdn

COLOUR MULTIFUNCTIONALS FOR A4 FORMAT





These productive multifunctional devices offer fast print speeds and a short wait for the first copy. Their high input capacity and exceptional scanning performance make large digitisation projects a breeze. And thanks to their minimum downtime – based on the KYOCERA long-life components – plus full duplex support, they are ideal for busy, environmentally aware offices.

- > Up to 30 pages per minute in A4 in colour and b/w
- > Up to 9,600 dpi printing quality with multi-bit technology
 > Double-sided print, copy, scan and fax* functionality as standard
 > 75 sheet reversing document processor with support of A6 scan

- > Advanced scan functionality with compact and encrypted PDF
- > Up to 5 input trays for various media types
- > Mobile printing support including AirPrint, Mopria, KYOCERA Mobile Print
- > Exceptionally low printing costs in its class *Only ECOSYS M6530cdn



Cosys ECOSYS stands for ECOlogy, ECOnomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means the toner is the only consumable for the first 200,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility.

ECOSYS M6030cdn I ECOSYS M6530cdn GENERAL

Technology: KYOCERA ECOSYS, Colour Laser

Control panel display: 5 lines LCD display

Engine speed: Up to 30 pages A4 per minute in colour and b/w

Resolution: 600 x 600 dpi, multibit technology for print quality of up to 9,600 x 600 dpi (print), 600 x 600 dpi, 256 greyscales per colour (scan / copy)

Duty cycle: Max. 100,000 pages per month

Warm-up time: Approx. 26 seconds or less

Time to first print: Approx. 7 / 8.5 seconds or less in b/w /

Time to first copy: Approx. 9.5 / 11.5 seconds or less in

CPU: PowerPC 465S / 1 GHz

Memory: Standard 1,024 MB, max. 2,048 MB Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host (10BaseT/100BaseTX/1000BaseT) Slot for optional inter-nal print server or SSD hard disc Slot for optional SD/

SDHC-Card

Integrated accounting: 100 department codes

Dimensions (W x D x H): Main unit: 475 x 558 x 616 mm

Weight: Main unit: Approx. 34.6 / 34.7 kg Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Copy / Print: 510 W / 502 W Ready mode: 57 W Sleep mode: 2.1 W

Noise (Sound pressure level: ISO 7779 / ISO 9296): ECOSYS M6030cdn ECOSYS M6530cdn

Copy / Print colour: 48.4 dB(A) LpA Quite mode in colour: 46.2 dB(A) LpA Sleep mode: Immeasurably low 48.7 dB(A) LpA 46.6 dB(A) LpA

Safety standards: GS, TÜV, CE This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thick ness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray; 60 – 220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm – / 216 x 356 mm) 250-sheet universal cassette; 60 – 163 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 – 216 x 356 mm). Max. input capacity with options: 1,850 sheets

Duplex functionality as standard: Double-sided printing: 60 - 163 g/m²; A4, A5, B5, Letter, Legal

Reversing document processor: 75-sheet, 50 – 120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 to 216 x 356 mm)

Output capacity: Max. 250 sheets face-down with paper full sensor

PRINT FUNCTIONS

Control language: PRESCRIBE IIc

Emulations: PCL 6 (PCL 5c/PCL-XL), PostScript 3 (KPDL 3), PDF Direct Print 1.7, XPS Direct Print

Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request

Fonts/barcodes: 93 scalable fonts for PCL/PostScript. 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional bar-codes PDF-477 under PRESCRIBE (PCL and other barcodes available as an option)

COPY FUNCTIONS

Max. original size: A4 / Legal

Continuous copying: 1-999

Zoom range: 25-400 % in 1 % steps

Preset magnification ratios: 7 Reductions / 5 Enlarge-

Exposure mode: Auto, manual: 9 steps

Image adjustments: Text + Photo, Photo, Text, Map, Printed document

Features: Auto Colour Mode, Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail (SMTP over SSL), Scan-to-FTP (FTP over SSL), Scan-to-SMB, Scan to USB Host, TWAIN scan (USB, network), WSD (WIA) scan (USB, network)

Scan speed: 40 ipm (300 dpi, A4, b/w), 30 ipm (600 dpi, A4 b/w, 300 dpi, A4, colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscalesper colour)

Max. scan size: A4, Legal

Original recognition: Text + Photo, Photo, Text, Light Text/ Fine Line, Text (for OCR)

File types: TIFF, PDF, PDF/A , high compression PDF, encrypted PDF, JPEG, XPS

Compression method: MMR / JPEG

Features: Integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB / FTP folder, print) at once

FAX FUNCTIONS (ECOSYS M6530cdn only)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps

Transmission speed: Less than 3 seconds

Scanning speed: 2.5 seconds

One-touch dial: 22 numbers

Address book: 200 entries

Scanning density: Normal: 200 x 100 dpi, Fine: 200 x 200 dpi

Superfine: 200 x 400 dpi, Ultrafine: 400 x 400 dpi Halftone: 256 greyscales

Maximum original size: A4, Legal

Compression method: JBIG, MMR, MR, MH

Memory reception: 256 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmis-sion and reception, broadcast

OPTIONS

PF-5100 Paper feeder (max 3 units): Max. 500 sheets; 60–220 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)

MS-5100 Convenient Stapler: 20 sheets, one position semi-automatic stapling, includes 1,500 staples

CB-5100H Cabinet: Wooden desk with storage capacity. Approx. 39 cm x 53 cm x 50 cm (WxDxH)

CB-5100L Cabinet: Wooden desk with storage capacity. Approx. 39 cm x 53 cm x 37 cm (WxDxH)

Memory upgrade: MDDR3-1GB: 1.024 MB

HD-6 SSD: 32 GB for easy document management HD-7 SSD: 128 GB for easy document management

Data security kit (E): in line with security level EAL3

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

UG-33: ThinPrint support

Optional interfaces:

Optional Internaces. IB-50 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45) IB-51 Wireless LAN: 802.11b/g/n

CONSUMABLE

Average continuous toner yield in accordance with ISO/IEC 19798


Toner-Kit TK-5140C, TK-5140M, TK-5140Y: cyan, magenta, yellow toner yield 5,000 pages A4 Starter toner: cyan, magenta, yellow toner yield 2,500 pages A4


Toner-Kit TK-5140K: black toner yield 7,000 pages A4 Starter toner: black toner yield 3,500 pages A4

SH-13 Staple cartridge: 2 x 1,500 staples for MS-5100

WARRANTY

1-year warranty** as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 200,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.





KYOCERA Document Solutions Europe B.V. – Branch Office Germany Otto-Hahn-Straße 12 - 40670 Meerbusch - Germany Tel +49 (0) 2159 928-500 - Fax +49 (0) 2159 918-100 www.kyoceradocumentsolutions.eu - info@deu.kyocera.com

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri

Chuo-Ku – Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. ecifications are subject to change without notice. Information is correct at time of going to press All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country



