





Professional Multifunction you can rely on.

The professional standard functionalities of these compact A4 MFPs will increase the productivity of any office work group: with print and copy speeds of up to 30 pages per minute and a fast time to first print of under 7 seconds. Featuring a large capacity document processor that scans double-sided originals for an enhanced document workflow and a structured five-line LCD display which offers fast and easy access to all the functionality you need.

- ▶ Up to 30 pages per minute in A4
- ► Time to first copy 6.9 seconds
- ▶ 5-line LCD display for clear messages and ease of use
- ► Print, copy, scan and fax* functionality as standard
- Standard Network and USB Connectivity
- ▶ Duplex unit for cost-saving double-sided printing
- ▶ 50-sheet document processor scans double-sided originals
- ► Automatic "Power Off" mode provides lowest power consumption

*Only for FS-1130MFP





With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network

The KYOCERA Net Viewer enables complete monitoring and control of all ECOSYS® printers and digital Kyocera multifunction units from any Windows@ PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

The Status Monitor shows the current printers condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

Ecosys Ecosys stands for Ecology, Economy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly and the drum unit every 100,000 pages. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides longterm cross-network compatibility. Kyocera's long-life components cost you and the environment less.

Technology: Kyocera ECOSYS Mono Laser Control panel display: 5 line LCD display Engine speed: Up to 30 pages A4 per minute

Resolution: 1,200 dpi quality, 600 x 600 dpi, 256 greyscales (scan/copy)

Duty cycle: Max. 20,000 pages per month Warm-up time: Approx. 20 seconds or less Time to first print: Approx. 6 seconds or less Time to first copy: Approx. 6.9 seconds

CPU: PowerPC 440/667 MHz Memory: Standard 256 MB, max. 768 MB

Standard interface: USB 2.0 (Hi-Speed), USB Host, Fast Ethernet 10/100Base-TX, slot for optional CompactFlash® card, slot for optional print server (not in FS -1130MFP)

Integrated accounting: 20 department codes Dimensions (W x D x H): 494 x 430 x 448 mm

Weight: Approx. 18 kg

Power source: AC 220 ~ 240 V, 50 Hz

Power consumption FS -1130MFP. FS -1030MFP Copying/Printing: 482 W 480 W Ready-mode: 83 W 78 W 10.6 W Sleep-mode: 7.8 W Auto-power-off-mode: 0.5 Worless 0.5 Worless

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray, 60-220 q/m², A4, A5, A6, B5, Letter, Legal, Folio, envelopes, Custom (70 x 148 to 216 x 356 mm) 250-sheet universal paper cassette, 60-120 g/m², A4, A5, A6, B5, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm)

Max. input capacity with options: 800 sheets

Duplex unit: Duplex as standard supports 60-105 g/m²

Platen glass: Up to 216 x 356 mm Reversing document processor:

50-sheet, simplex scan 50-120 g/m², duplex scan 50-110 g/m², A4, A5, B5, Letter, Legal, Custom (140 x 210 to 216 x 356 mm)

Output capacity: Max. 150 sheets face-down

Controller language: PRESCRIBE IIe

Emulations: PCL6 (5c/XL), KPDL 3 (PostScript 3-compatible), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF Direct Print, XPS Direct Print (requires memory expansion) Operating systems: All current Windows operating systems, MAC OS X version 10.4 or higher, Unix, Linux as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL 6, HP-compatible) + 8 (Windows Vista), 101 (KPDL3), 1 bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SN MPv3 and Private Print (requires memory expansion)

Max. original size: A4/Legal Continuous copying: 1-999 Zoom range: 25-400% in 1% steps

Preset magnification ratios: 7 Reductions / 5 Enlargements

Exposure mode: Auto, manual: 7 steps Image adjustments: Text + photo, text, photo

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

Functionality: Scan-to-e-mail, Scan-to-FTP (FTP over SSL), Scan-to-SMB, Scan to USB Host, TWAIN (USB), WSD (WIA) scan (USB) Scan speed: 35 ipm (300 dpi, A4, b/w), 14 ipm (300 dpi,

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales) Max. scan size: A4, Legal

Original recognition: Text, photo, text + photo, for OCR

File types: TIFF, PDF, JPEG, XPS Compression method: MMR/JPEG

Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi-send (e-mail, fax, SMB/FTP folder, print) at once

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Less than 3 seconds

Scanning speed: 2.5 seconds One-touch dial: 22 numbers Address book: 100 entries

Scanning density Normal: 8 dot/mm x 3.85 lines/mm Fine: 8 dot/mm x 7.7 lines/mm Superfine: 8 dot/mm x 15.4 lines/mm Ultrafine: 16 dot/mm x 15.4 lines/mm Maximum original size: A4, Legal

Compression method: JBIG, MMR, MR, MH Memory reception: 256 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast, memory reception

Paper handling

PF-120 Paper feeder: Max. 250 sheets, 60–120 g/m², A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 297 mm)

Memory upgrade: DIMM-512P:512MB

CompactFlash® card: Up to 4GB for printing forms, fonts, logos, macro storage

USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available

Average continuous toner yield in accordance with ISO /IE C 19752

TK-1134 Toner-Kit: Microfine toner for 3,000 pages A4

Capacity of starter toner is 1,000 pages A4

Maintenance Kit MK-1134 installed every 100,000 pages

2-year warranty as standard. Kyocera guarantees the drum and developer for 2 years or 100,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.







The images displayed in this brochure are for illustrative purposes only, and may include optional extras-

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA Document Solutions Australia

Ph: 13 KYOCERA (596 2372)

www.KyoceraDocumentSolutions.com.au

KYOCERA Document Solutions New Zealand

Ph: 0508 KYOCERA (596 2372)

www.KyoceraDocumentSolutions.co.nz

KYOCERA Document Solutions Australia Ptv. Ltd ABN 77 003 852 444

