



› PRINT › COPY › SCAN › FAX

TASKalfa 4551ci

COLOR MULTIFUNCTIONAL
SYSTEM






POWERING COLOR PERFORMANCE... COMPANY-WIDE.



- › Vibrant, Color Output Up to 45 Pages per Minute in Color and Black
- › Color Scan Up to 160 ipm
- › Intuitive and Customizable Touch Screen Control Panel
- › Advanced Finishing Options to Power Workflow
- › Robust and Scalable Business Applications
- › Statement - 12" x 18" Printing from the Paper Trays
- › Standard Gigabit Ethernet
- › Tab Printing Available Through Multi Purpose Tray
- › Apple AirPrint™ Enabled for a Mobile Printing Solution

**HARNESS THE POWER OF YOUR TASKalfa MFP
WITH CUSTOMIZED BUSINESS APPLICATIONS**

The speed and robust performance of the TASKalfa 4551ci helps your company easily tackle the most demanding document imaging needs. Vibrant color and exceptional black & white output combines with flexible product configurations and advanced finishing for professional output. Scalable, integrated business applications power document workflow, while KYOCERA's award-winning ultra-reliability and unique long-life technology ensure superior performance and maximum efficiency. For document imaging innovation and quality you can rely on, the TASKalfa 4551ci delivers.

-  **KYOCERA CLOUD CONNECT:** Easily print from and scan directly to the cloud while on the go from your KYOCERA MFPs.
-  **KYOCERA MOBILE PRINT:** Simply and conveniently print files, web pages, and images using your smartphone or tablet.
-  **DMS LINK:** Simplify document workflow through digital imaging, distribution, retrieval and long-time archival.
-  **PINPOINT SCAN:** Scan from your MFP to your PC with added speed, functions and versatility.
-  **SHAREPOINT CONNECTOR:** Enhance collaboration utilizing your KYOCERA MFPs and your existing Microsoft SharePoint Server.

BASIC SPECIFICATIONS

Configuration: Color Multifunctional System – Print/Scan/Copy/Optional Fax

Pages Per Minute:

Color: 3.9 Seconds – Letter: 45 ppm, Legal: 21 ppm, Ledger: 22 ppm, 12" x 18": 22 ppm (print only)

Warm Up Time: 30 Seconds or Less (Power On)

First Page Out:

Copy: 3.9 Seconds or Less Black, 5.1 Seconds or Less Color; Print: 5.4 Seconds or Less Black, 6.6 Seconds or Less Color

Resolution / Bit Depth: 600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth

Memory / Hard Disk Drive: 3.5 GB RAM Standard / 320 GB HDD

Duplex: Standard Stackless Duplex Supports Statement to 12" x 18", 16 lb Bond – 140 lb Index (60 – 256gsm)

Standard Output Tray: Statement – 12" x 18" / 250 sheets; up to 12" x 48" Banner / Single Sheet

Electrical Requirements: 120V, 60Hz, 12.0A; 220-240V, 50Hz, 7.2A

Dimensions / Weight: 25.51" x 30.20" x 29.41" / 251.33 lbs

Maximum Monthly Duty Cycle: 200,000 Pages Per Month

PAPER SUPPLY
Standard Paper Sources:

Dual 500 Sheet Trays, 150 Sheet MPT; Auto Selection/Switching

Optional Paper Sources:

Dual 500 Sheet Trays (**PF-730(B)**), Dual 1,500 Sheet

Trays (**PF-740(B)**); Side LCTs: 500 Sheet Multimedia

Tray (**PF-780(B)**), 3,000 Sheet Large Capacity Tray (**PF-770**)

Paper Capacity:

Standard: 1,150 Sheets;

Maximum: 7,650 Sheets

Paper Size: Trays 1, 2 / 5.5" x 8.5" – 12" x 18", Custom size;

PF-730(B), **PF-780(B)**; 5.5" x 8.5" – 12" x 18"; **PF-740(B)**,

PF-770: 8.5" x 11" **MPT:** 5.5" x 8.5" – 12" x 18" (Multiple Sheets);

Up to 12" x 48" Banner (Single Sheet)

Paper Weight:

Trays: 16 lb Bond – 140 lb index (60 – 256gsm);

MPT: 16 lb Bond – 110 lb Cover (60 – 300gsm)

Input Materials:

Bond Paper, Recycled Paper, Transparencies, Cardstock,

Envelopes, Labels, Tabs, Gloss

SECURITY SPECIFICATIONS

Standard: Local Authentication, Network Authentication (IPsec,

HTTPS, LDAP over SSL, SNMPv3); Secure Print (IPP over SSL);

Scan to e-mail (POP3/SMTP over SSL); Scan to FTP (FTP over SSL);

Scan to SMB/PC/USB; FTP over SSL

Optional: Data Security Kit (E): Network Data Encryption, HDD

Overwrite Mode, HDD Data Encryption

PRINT SPECIFICATIONS

Standard Controller: Freescale QorIQ P1022 (Dual Core) / 1,067MHz

PDLs / Emulations: PRESCRIBE, PCL6 (5e, XL), KPD3 (PS3), XPS;

Optional (**UG-34**): IBM ProPrinter, Line Printer, LQ-850

Fonts: 136 KPD3, 93 PCL6, 8 Windows Vista, 1 Bitmap

Specifications and design are subject to change without notice.

For the latest on connectivity visit

www.kyoceradocumentsolutions.com/us

DMS Link and PinPoint Scan are trademarks of the KYOCERA

Companies.

MAC and AirPrint are trademarks of Apple, Inc.

Java is a trademark of Oracle Corporation.

Fiery is a trademark of Electronics for Imaging, Inc.

Other trademarks are the property of their respective owners.

KYOCERA Document Solutions America, Inc.

Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA

©2015 KYOCERA Document Solutions America, Inc.

Windows® OS Compatibility: Windows XP/2003/Vista/2008/7/8/ Server 2008 R2/Server 2012

Novell OS Compatibility: Novell NetWare 3.x/4.x/5.x/6.x

Mac OS Compatibility: Mac OS 10.x; AirPrint Enabled

UNIX OS Compatibility: Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)

Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0,

4 USB Host Interfaces, 2 Expansion Slots

Optional: 10/100/1000BaseTX (**IB-50** for Dual NIC);

Optional: IEEE 802.11 b/g/n (**IB-51** for Wireless LAN Interface)

Network Print and Supported Protocols:

TCP/IP, NetBEUI, FTP, LPR, IPv6, IPsec, SSL, WSD Print

Drivers: KX Driver, Mini Driver, KX Driver for XPS, XPS Mini Driver,

Network Fax Driver, PPD for MAC

Utilities: KYOCERA Net Admin, KYOCERA Net Viewer, PDF Direct

Print, Command Center RX

SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner

Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi

File Formats: BW: TIFF, XPS, PDF, PDF/A;

Color: TIFF, JPEG, XPS, PDF, PDF/A

PDF Extension: High Compression PDF, Encrypted PDF,

Searchable PDF (OCR) Option

Scan Speeds:

DP-770(B): Simplex: 75 ipm BW/Color (300 dpi);

Duplex: 45 ipm BW/Color (300 dpi)

DP-772: Simplex: 80 ipm BW/Color (300 dpi);

Duplex: 160 ipm BW/Color (300 dpi)

Connectivity / Supported Protocols: 10/100/1000BaseTX, TCP/IP

Scanning Functions: Scan to Folder (SMB), Scan to e-Mail, Scan to

FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan

Original Size: Through DP: Statement to 11" x 17";

Glass: up to 11" x 17"

Driver: TWAIN/WIA Driver

COPY SPECIFICATIONS

Image Mode: Text, Photo, Text/Photo, Auto, Manual, Map

Continuous Copy: 1 – 999 / Auto Reset to 1

Additional Features: Positive/Negative Reverse, Mirror Image,

Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin

Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed

Through, Text Stamp, Bates Stamp, Blank Page Skip

Job Management: 1,000 Department Codes, Job Programs,

Job Build, Shortcut Keys, Repeat Copy

Color Adjustment: One Touch, Hue, Auto Exposure, Sharpness

Magnification / Zoom: Full Size, 4 Reduction, 4 Enlargement

Preset Ratios, 25 – 400% in 1 step increments

Document Box: Custom Box, Job Box, Removable Memory Box,

Fax Box (with optional Fax System)

DOCUMENT PROCESSOR OPTIONAL DP-770(B) OR DP-772

Type / Capacity:

DP-770(B): Reversing Automatic Document Processor / 100 Sheets

DP-772: Dual Scan Document Processor / 175 Sheets



Document Solutions