

**LANIER**

# FAX 1190L



FACSIMILE

*Designed for All-In-One Productivity*

*The right choice for small and mid-size offices that need versatile faxing plus other critical workflow tools.*



**LANIER****FAX 1190L****Designed for All-In-One Productivity**

Every office needs smart multifunctional technology to complete document tasks quickly and keep productivity high. For small- and mid-size offices, the LANIER® FAX 1190L delivers comprehensive faxing plus essential printing and copying features in a reliable, convenient and space-saving design.

**Comprehensive Capabilities**

The FAX 1190L is a cost-effective choice for satellite offices, home offices, independent businesses and executive suites.

- Rely on a single, well-equipped system for faxing, printing and convenience copying.
- Complete two tasks simultaneously — such as sending a fax and making a copy — with dual access.
- Send fax documents with the Super G3 modem and a transmission time of just two seconds-per-page. You can also use the built-in PC-Fax Send feature.
- Forward incoming documents to another fax with remote fax forwarding. It can be accessed remotely, so mobile users always get their documents.

**Simple, Smart Design**

This all-in-one system offers exceptional convenience and accessibility.

- Place this compact device right on the desktop, without taking up valuable space.
- Automatically resize incoming faxes. The system detects the paper size loaded in the tray, then reduces 8.5" x 14" faxes to fit.
- Easily transmit contracts, proposals and other documents (up to 8.5" x 14" in size) with the 20-Sheet Automatic Document Feeder.
- Hold received faxes in memory in case paper runs out while you are out of the office.

**Economical Performance**

Increase your personal productivity while maximizing cost-efficiency.

- Fax directly from your PC, without having to print documents first.
- Maintain separate phone and fax numbers on a single telephone line. Distinctive ringtones make it easy to differentiate phone calls from incoming faxes.\*
- Reduce the risk of missing important faxes. Fax paging calls your cell phone or pager to let you know when a fax arrives.
- Save energy with sleep mode, which shuts the system down when it is not in use. A short warm-up time ensures incoming faxes will be printed quickly.

\* Requires Distinctive Ringing option from your local phone company

**Superior Ease of Use**

- Send faxes to as many as 220 recipients with 20 One-Touch Dials, 200 Speed Dials and 8 Group Dials.
- Check the status of documents held in memory that are waiting to be sent.
- Print from your PC while you wait, or while sending or receiving a fax in memory.

**SPECIFICATIONS**

|                              |   |
|------------------------------|---|
| Type                         | Desktop   |
| Recording Method             | Laser   |
| Modem Speed                  | 33.6 Kbps (with Auto Fallback)  |
| Maximum Transmit Speed       | Approx. 2 sec.* (ITU-T Test Chart #1)   |
| Data Compression             | MH/MR/MMR/JBIG  |
| Dual Access                  | Yes   |
| Standard Document Memory     | 16 MB (up to 500 pages)   |
| Auto Dialer                  | 20 (10 x 2) One-Touch Dials, 200 Speed Dials, 8 Group Dials   |
| Document Memory Backup       | Up to 4 Days (up to 96 hours)   |
| Automatic Document Feeder    | 20 Sheets (20 lb. Bond)   |
| Output Tray Capacity         | 100 Sheets (Face down)  |
| Maximum Width/Scan Width     | 8.5" (216 mm)/8.2" (208 mm)   |
| Document Length              | 14" (356 mm)  |
| Maximum Print Width          | 8.2" (208 mm)   |
| Recording Paper Capacity     | 250-Sheets/1 Cassette Tray, 1-Sheet/Manual Feed Slot  |
| Paper Sizes                  | Paper Cassette: Letter, Legal, Executive/A4, A5, A6, B5, B6<br>Manual Feed Slot: Width: 2.75" - 8.5" (69.9 - 215.9 mm);<br>Length: 4.6" - 16" (116 - 406.4 mm)  |
| Paper Weights                | Paper Cassette: 16 - 28 lb. Bond (60 - 105 g/m <sup>2</sup> )<br>Manual Feed Slot: 16 - 43 lb. Bond/90 lb. Index (60 - 161 g/m <sup>2</sup> )   |
| Paper Types                  | Paper Cassette: Plain Paper, Recycled Paper or Transparencies<br>Manual Feed Slot: Plain Paper, Bond Paper, Recycled Paper, Transparencies, Envelopes or Labels   |
| Fax Scan Resolution          | Standard: 203.2 x 97.8 dpi<br>Fine: 203.2 x 195.6 dpi<br>Super Fine: 203.2 x 391.2 dpi<br>Photo: 203.2 x 195.6 dpi<br>Halftone 64 Levels  |
| Power Consumption            | Power Saver Mode: 10 Watts<br>Stand-by Mode: 80 Watts<br>Operating Mode: 475 Watts  |
| Power Requirements           | 100/120V, 50/60Hz   |
| Environment                  | 68° to 104° C, 10% to 95% RH or less  |
| Dimensions (WxDxH)           | 14.7" x 14.7" x 10.3"<br>(374 mm x 374 mm x 262 mm)   |
| LCD (Liquid Crystal Display) | 16 Characters x 1 Line  |
| Weight                       | 16.21 lbs./7.35 kg (Without Toner Cartridge and Drum Unit)  |
| Transmission Features        | Automatic Redial, Batch Transmission, Broadcasting, Error Correction Mode (ECM), Daylight Savings Time Adjustment, Delayed Fax/Delayed Batch Transmission, Direct Fax Number Entry, Immediate Transmission, Memory Transmission, Polling Transmission, Programmable and Auto Cover Sheet, Remote Fax Retrieve, Sleep Mode, Transmission Result Report |
| Reception Features           | Automatic/Manual Reception, Auto Memory Receive, Auto Reduction, Distinctive Ring, Telephone Answering Device (TAD), Fax Forwarding/Remote Fax Forward, Fax Paging, Memory and Lock User Function, Notification of Reception, Out-of-Paper Reception, Volume Adjustment for Hearing Impaired, Polling Reception                                       |

\*Approximately 2 seconds per page is dependent on optimal line quality.

**LASER PRINTING FEATURES**

|                  |                                   |
|------------------|-----------------------------------|
| PDL              | Windows GDI                       |
| Speed            | 15 ppm (Letter)/600 x 600 dpi     |
| Paper Size       | Up to Legal Size (8.5" x 14")     |
| Resolution       | Up to 1200 x 600 dpi              |
| Interface        | USB 2.0 (Full-speed)              |
| Operating System | Windows 2000/XP/Vista/7           |
| Other Features   | Manual Duplex; Watermark; Scaling |

**COPY FEATURES**

|                         |                           |
|-------------------------|---------------------------|
| Copy Speed              | 15 cpm                    |
| Reduction & Enlargement | 50 - 200% (1% increments) |
| Resolution              | 200 x 300 dpi             |
| Copies                  | Up to 99                  |
| Combine Copy            | 2-in-1/4-in-1             |

**PC FAX**

|                  |   |
|------------------|---|
| Interface        | USB 2.0 (Full-speed)  |
| Operating System | Windows 2000/XP/Vista/7   |
| Features         | PC-Fax Send Only; Cover Page; Address Book; Broadcast; Remote Setup |

**SUPPLIES\***

|                           |                        |
|---------------------------|------------------------|
| Toner Cartridge Type 1190 | Yield 2,500 Pages @ 5% |
| Drum Unit Type 1190       | Yield 12,000 Pages     |

\*Ships with Starter Toner Cartridge (Yield: 2,500 pages @ 5%) and Drum Unit at full yield.

Actual yields may vary based on types of images printed and other factors.

For maximum performance and yield, we recommend using Lanier parts and supplies.

[www.lanier.com](http://www.lanier.com)

Bringing Lanier Value to Your Organization  
Lanier technology offers a diverse portfolio of solutions to help your organization stay competitive and move ahead. Let Lanier show you how to empower your business to improve critical processes, keep information secure, ensure compliance and promote environmental sustainability while reducing the total cost of ownership.

Lanier Five Dedrick Place, West Caldwell, NJ 07006  
©2010 Lanier is a registered trademark of Ricoh Americas Corporation. All rights reserved. All other trademarks are the property of their respective owners. Print speed may be affected by network, application or PC performance. Specifications and external appearances are subject to change without notice.



L3208

