LANIER

SP C261SFNw

Color Laser MFP

- ✓ Printer✓ Copier
- ∠ Facsimile
- Z Scanner





Get versatile capabilities at a low cost

If you run a startup or small workgroup, you need a highguality multifunction printer (MFP) that saves you time and offers low long-term costs. The affordable and compact Lanier SP C261SFNw Color Laser MFP is designed for personal users or workgroups of up to three people. You'll get jobs moving quickly with print and copy speeds of up to 21 pages per minute (ppm) and easy connectivity from your smartphone or tablet. And with a low TEC value of 1.5 kWh, ENERGY STAR[®] certification and an EPEAT[®] Silver rating, you'll enjoy low energy usage.

Deliver high-impact communications fast

At up to 2400 x 600 dpi resolution, you can still print 21 ppm to deliver documents with vivid color and crisp black text guickly. Plus, the single pass document feeder (SPDF) lets you load up to 50 pages for uninterrupted scanning at up to 40 images per minute (ipm).*

Create a user-friendly workstation

Simplify scan, print, copy and fax jobs with the 4.3" color touchscreen—store up to 12 settings for guick access to common tasks. Load up to three different paper sizes and increase paper capacity to 751 sheets with an optional paper tray to increase efficiency. Plus, with the easy-setup installation wizard, you'll hit the ground running in no time.

*Maximum speed for scanning black-and-white documents. The maximum scan speed for color documents is 24 ipm.

Desktop, Color Laser

System Specifications

Engine Specifications

Configuration/Technology Printing Process Scanning Element Toner Type Color/B&W Print Speed (Letter) Max. Monthly Volume/Duty Cycle First Page Out/Warm Up Time Print Resolution

Electro-photographic printing Flatbed Scanner with full color Contact Image Sensor (CIS) Dry mono-component toner developer, AIO Cartridge 21 ppm Up to 1,500 prints/30,000 prints 14 seconds/30 seconds 600 x 600 dpi (Default) (Speed Mode). 1200 x 600 dpi equivalent (Standard Mode), 2400 x 600 dpi equivalent (Fine Mode) 250-sheet tray + 1-sheet Bypass Tray/ 751 sheets 150 sheets Standard Tray/Bypass Tray: 3.54" x 5.83"–8.5" x 14.0" Standard Tray: 16–43 lb Bond/90 lb, Index (60–160 g/m²) Optional Tray: 16–28 lb. Bond (60–105 g/m²) Duplexing: 16-24 lb. Bond (60-90 g/m2)

Supported Paper Types

Standard/Max Paper Capacity

Standard Output Capacity

Supported Paper Weights

Supported Paper Sizes

Bond*, Cardstock*, Color, Label*, Letterhead, Plain, Pre-printed, Pre-punched, Thick, Thin & Recycled papers, Envelopes* (*via Standard Tray and Bypass only)

Duplexing Dimensions (W x D x H) Weight Power Consumption

Typical Electricity Consumption (TEC) 1.5 kWh/week Recovery from Sleep Mode Power Requirements ENERGY STAR Certified EPEAT Silver

Automatic (standard) 16.5" x 19.4" x 18.1" (420 x 493 x 460 mm) 63.9 lbs. (29.0 kg) Operating: B&W: 331.3 W, Color: 404.1 W, Sleep Mode: 1.3 W 29 seconds 120V, 60Hz, 11A

Copy Specifications

Copy Resolution Document Feeder Type Document Feeder Capacity Document Feeder Original Size **Document Feeder Paper Weight** Maximum Original Size

Maximum Copy Quantity Reduction & Enlargement Ratios Zoom Range

Copier Features

Auto Duplex, Combine Copy (2-in-1, 4-in-1), Electronic Sort, ID Card Copy, Image Density, Image Quality Mode (Text, Photo, Mixed), Memory Copy, Auto Tray Switch, Series Copy

25% to 400% in 1% increments

600 x 600 dpi (Platen), 300 x 600 dpi (SPDF)

14-28 lb. Bond (52-105 g/m²) Platen: Up to 8.5" x 11.7"/A4 (210 x 297 mm),

50%, 65%, 78%, 93%, 129%, 155%, 200%, 400%

Color and B&W: up to 600 dpi, TWAIN: up to 1200 dpi

JPEG, Single/Multi Page TIFF, Single/Multi Page PDF

Network: TCP/IP; Email: SMTP; Scan-to-Folder: SMB, FTP

Scan-to-Email; Scan-to-Folder (SMB/FTP); Scan-to-Media (USB):

B&W: up to 40 ipm, Color: up to 24 ipm

Black & White, Grayscale, Color

TWAIN/WIA, ICA, SANE Scanning

SPDF: Up to 8.5" x 14" (216 x 356 mm)

5.5" x 5.5" to 8.5" x 14" (140 x 140 mm to 216 x 356 mm)

Single Pass Document Feeder (SPDF)

50 Sheets

99 copies

400 MHz

Print Specifications

Processor Speed Memory (Standard/Maximum) Printer Languages Connection Type Font Support Network Protocols Supported Operating Systems

Device Management Utilities Mobile Printing

Other Print Features

1–999 Set Quantity, Collate, Dithering, Duplexing, Do Not Print Blank Pages, Front Cover, Layout/N-up Printing, Locked Print, Mirror Image Print, Reduce/Enlarge Print, Rotate Print, User Codes, User ID, Watermarks, Economy Color

Up to 8.5" x 11"/A4 Up to 8.5" x 14"

Scan Specifications

Scanner Resolution Scanning Speed (Letter) Platen Size Maximum Scanning Size Scan Modes File Formats Scan-To Modes

Scan Protocols

Facsimile Specifications

Fax Resolution Fax Scanning Speed Modem Speed Fax Compression Method Fax Memory Transmission Speed

Quick Dials/ Speed Dials

Standard Fax Features

Up to 200 dpi Less than 5 seconds/page (Letter @ 200 dpi) 33.6 kbps with auto fallback MH. MR. MMR. JBIG 100 pages (2.5 MB Flash ROM) Approximately 3 seconds/page *ITU No.1 chart, Compression: MMR, Resolution: Standard speed: 33.6 Kbps 20/200 LAN-Fax (Outbound TX only), Internet Fax (T.37),

Fax Forwarding to E-Mail/Folder, PSTN, PBX

Security Features

Wireless LAN Security-WEP, WPA2, Network Security via TCP/IP Access Control, Encrypted Communication using IPsec, IPP Authentication, Locked Print, User Restrictions

500 sheets

Hardware Options Paper Feed Unit TK1220

Paper Capacity: Supported Paper Sizes: Supported Paper Weight: Dimensions (W x D x H): Weight

Consumables and Yields

Print Cartridge Black SP C250A Print Cartridge Cyan SP C250A Print Cartridge Magenta SP C250A Print Cartridge Yellow SP C250A Waster Toner Bottle SP C220

16-28 lb Bond (60-105 g/m²) 15.7" x 17.7" x 5.0" (400 x 450 x 127 mm) 8.8 lbs. (4 kg)

Fixed for 8.5" x 11" / Letter, A4

2.300 pages* 2,300 pages* 2,300 pages* 2,300 pages* 25,000 pages

*Declared yield values in accordance with ISO/IEC 19752. Actual yields may vary based on images printed and other factors.

Warranty

The Lanier SP C261SFNw is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for period of 90 days from the date of purchase or until depleted, whichever comes first.

Please refer to warranty documents shipped with the product for more details.

www.lanier.com

Ricch USA, Inc., 70 Valley Stream Parkway, Malvern, PA 19355, 1-855-5-LANIER @2017 Ricch USA, Inc. All rights reserved, Lanier² and the Lanier loga are trademarks of Ricch USA, Inc. Ricch[®] and the Ricch Logo are registered trademarks of Ricch Company Ltd. All other trademarks are the property of their respective owners. Lanier products and services are offered by Ricch USA, Inc. Ricch[®] and the Ricch Logo are registered trademarks of Ricch Company Ltd. All other and specifications of Lanier products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricch makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be lable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Lanier products and services are as set forth in the express warranty statements accompanying them.

256MB RAM PCL6/5c, PostScript 3, PictBridge 10Base-T/100Base-TX, USB 2.0 Type B, USB 2.0 Type A, IEEE802.11b/g/n PCL/PS3: 80 fonts TCP/IP, IPP, Bonjour Windows Vista, 7, 8.1, 10, Systems Server 2008/R2, Server 2012/R2, Macintosh: OS X 10.9–10.12, Linux and Unix Filter @Remote, Device Manager NX, Print Driver Packager NX RICOH Smart Device Connector App (for printing only) SP C260 Series Scan App (for scanning only), Apple AirPrint[™], Google Cloud Print[™], Mopria[™]