Lexmark E350d and E352dn



LEXMARK

Lexmark E350d, E352dn

The Lexmark E350d and E352dn are affordable, space-saving, monochrome laser printers with duplex standard. Their 366 MHz processor and 32MB of standard memory provide high-quality printing at up to 35 ppm.

Lexmark E350d, E352dn

In the Box

Lexmark E350d

- Lexmark E350d printer
- 1,500-page Starter Return Program Toner Cartridge¹
- Photoconductor Kit (up to 30,00 pages)
- Dust Cover
- · Automatic two-sided printing
- Power Cord

- Combined Drivers, Utilities and Publications CD
- Setup Sheet, Safety Notices, Supplies Return Program Flyer

Lexmark E352dn

Lexmark E350d printer EXCEPT 3,000-page starter
 Return Program Toner Cartridge¹ PLUS Ethernet



Product Specifications			
Part Number	US/Canada: E350d: 33S0400; E352dn: 33S0500		
Product Class	Desktop laser printer		
Speed	Up to 35 ppm		
Time to First Page	As fast as 6.5 seconds (standby and power saver modes)		
Print Resolution	1200 x 1200 dpi, 2400 image quality printing; 1200 image quality printing; 600 x 600 dpi		
Processor	366 MHz		
Memory (std./max.)	32MB/160MB		
Connectivity* Standard Optional	E350d: Parallel, USB; E352dn: Parallel, USB, Ethernet E350d: Ethernet, Wireless, Gigabit Ethernet; E352dn: Wireless, Gigabit Ethernet		
Printer Languages	PostScript 3, PCL 6 emulations, PPDS Migration Tool		
Fonts*	PCL: 89 scalable, including OCR-A, OCR-B and code 3 of 9 bar codes; 2 bitmapped; PostScript: 89 scalable		
Operating Systems*	Windows, Mac, Novell (E352dn only), UNIX, Linux		
Acoustics	Printing: 52 dBA; Quiet mode: 48 dBA; Idle: inaudible		
Size (WxDxH)	15.6 in. x 14.1 in x 10.2 in. (396 mm x 359 mm x 259.5 mm)		
Weight	25 lb. (11.4 kg)		
Duty Cycle	35,000 pages (Maximum usage per month)		

Media Specifications		
Paper Capacity (sheets) Standard Maximum	Input: 250 + 1; Output: 150 + 1 Input: 801 (250 + 550 + 1); Output: 150 + 1	
Paper Sources Standard Maximum	Input: 2; Output: 1 top, 1 rear Input: 3; Output: 1 top, 1 rear	
Media Information Types Size Weight	Plain paper, card stock, transparencies, paper labels Letter, legal, executive, folio, statement, A4, A5, A6, JIS B5, universal (3 x 5 in. to 8.5 x 14 in.), envelopes (7 ³ / ₄ , 9, 10, DL, C5, B5) Plain paper: 16 to 43 lb. (60 to 163 g/m²); Card stock: up to 90 lb. (199 g/m²)	


Shipping Dimensions

Lexmark E350d, E352dn Size: 18.5 x 16.9 x 14.9

Weight: 29.2 lb.



Part Numbers				
Supplies	3,500-page Return Program Toner Cartridge ¹ 3,500-page Toner Cartridge ¹ 9,000-page High Yield Return Program Toner Cartridge ¹ 9,000-page High Yield Toner Cartridge ¹ 30,000-page Photoconductor Kit ²	E250A11A E250A21A E352H11A E352H21A E250X22G		
Memory Options	32MB SDRAM 64MB SDRAM 128MB SDRAM 32MB Flash Card	1021257 1021258 1021259 1021208		
Warranty*	1-year Advanced Exchange (3-5 business days) Upgrade of Base Warranty to Advanced Exchange next business day 1-year Advanced Exchange next business day extended warranty 2-year Advanced Exchange next business day extended warranty Upgrade of Base Warranty to Onsite Repair 1-year Onsite Repair extended warranty 2-year Onsite Repair extended warranty Upgrade of Base Warranty to Onsite Exchange next business day 1-year Onsite Exchange next business day extended warranty 2-year Onsite Exchange next business day extended warranty	Base 2349195 2349129 2349130 2349137 2349138 2349145 2349147		



¹ Declared standard yield value in accordance with ISO/IEC 19752 ² Yield based on approximately 5% coverage

Additional Part Numbers			
Solutions	Korean Font Card Simplified Chinese Font Card Traditional Chinese Font CArd Japanese Font Card	1021240 1021241 1021242 1021243	
Connectivity	External Print Servers Lexmark MarkNet™ N7000e Fast Ethernet - 1 port¹ Lexmark MarkNet N7020e Gigabit Ethernet - 4 port¹ Lexmark N7002e Fast Ethernet - 1 port² Lexmark N4000e Print Server¹ Wireless Print Adapters 802.11g Print Adapter³ Lexmark N4050e 802.11g Print Server¹	14T0230 14T0220 14T0240 14T0030 1010042 14T0145	
Cables	10-foot Parallel Cable 6-foot USB Cable	1021231 1021294	
Media	Lexmark Laser Transparencies	70X7240	

Terms & Conditions

Lexmark, MarkNet and Lexmark with diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. PCL is a registered trademark of Hewlett Packard Company. The USB logo is a trademark of Universal Serial Bus Implementers Forum, Inc. All other trademarks are the property of their respective owners. © 2006 Lexmark International, Inc. All rights reserved.

Requires USB connection
 Requires Parallel connection
 E352dn only