













Lexmark MC2535adwe

The multifunction Lexmark MC2535adwe builds on output at up to 35 pages per minute* with a 4.3-inch/10.9-cm color touch screen. In addition to reliably handing diverse media types and sizes, it includes built-in Wi-Fi and tools that help you both minimize toner consumption and get the color right.



Ready when you are

- 1.2-GHz quad-core processor and up to 6 GB memory drives printing at up to 35 ppm.*
- Scan at up to 50 pages per minute.
- Steel frame and durable design stands up to heavy use and harsh environments.
- Long-life fuser and imaging components extend uptime.
- Vinison[™] Toner replacement cartridges deliver up to 3500 color and 8000 monochrome pages**.
- ▶ Keep printing in black even when color toner is empty.

Color that keeps saving

- PANTONE® calibration, embedded color sample pages and Lexmark Color Replacement produce accurate, professional color output in-house.
- Save toner with suite of tools that let you choose when and how much color to print.

Input that works

- Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or a convenient single-sheet feeder.
- 251 pages of standard input can grow to 1451.

Interact with ease

- Tiltable 4.3-inch/10.9-cm e-Task touch screen comes with convenience and productivity apps and is customizable to meet your needs.
- Front USB port allows walk-up printing from popular file formats without a computer.
- Compact footprint allows flexible placement in more locations.
- Connect easily via Ethernet, USB, Wi-Fi or simple mobile printing options.

Full-spectrum security

- Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device and over the network.
- Keypoint Intelligence Buyers Lab honored Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- Energy management features reduce power consumption in active use or sleep mode.
- Standard two-sided printing saves paper.
- Recycle cartridges through the award-winning Lexmark Cartridge Collection Program (LCCP).

^{*}Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

**Average continuous black or continuous composite color (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

***Award based on North America and/or Western Europe data



Lexmark MC2535adwe



Multifunction product with 4.3-inch/10.9-cm e-Task color touch screen 18.2 x 17.4 x 23.1 inches 462 x 442 x 588 mm

2 650-sheet duo tray 5.2 x 16.7 x 16.4 inches 133 x 424 x 416 mm

3 550-sheet tray 5.2 x 16.7 x 16.4 inches 133 x 424 x 416 mm Adjustable printer stand (not shown) 20.5 x 25.7 x 24.6 inches 521 x 653 x 625 mm

Swivel cabinet (not shown) 10.4 x 18.7 x 23.6 inches 263 x 476 x 600 mm



Note 1: Supports one optional 650-sheet duo tray; or one optional 650-sheet duo tray and one optional 550-sheet tray with the 650-sheet duo tray on top.

Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. PANTONE® Goe™ and other Pantone, Inc. trademarks are property of Pantone, Inc. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http:// ww.openssl.org/).



| Product specifications | Lexmark MC2535adwe |
|---|--|
| Printing | |
| Display | Lexmark e-Task 4.3-inch (10.9 cm) color touch screen |
| Print Speed: Up to ⁵ | Black: 35 ppm / Color: 35 ppm |
| Time to First Page: As fast as | Black: <8.5 seconds / Color: <8.5 seconds |
| Print Resolution | Black: 1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi) / Color: 1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi) |
| Memory / Processor | Standard: 2048 MB / Maximum: 6144 MB / Quad Core, 1200 w/ GPU MHz |
| Hard Disk | Option available |
| Recommended Monthly Page Volume ¹ | 1500 - 8500 pages |
| Maximum Monthly Duty Cycle: Up to ² | 85000 pages per month |
| Copying | |
| Copy Speed: Up to⁵ | Black: 35 cpm / Color: 35 cpm |
| Time to First Copy: As fast as | Black: 9 seconds / Color: 9.5 seconds |
| Scanning | |
| Scanner Type / ADF Scan | Flatbed scanner with ADF / RADF (Reversing Duplex) |
| A4/Ltr Duplex Scan Speed: Up to | Black: 21 / 23 sides per minute / Color: 13 / 14 sides per minute |
| A4/Ltr Simplex Scan Speed: Up to | Black: 47 / 50 sides per minute / Color: 30 / 32 sides per minute |
| ADF Paper Input Capacity: Up to | 50 pages 20 lb or 75 gsm bond |
| Faxing | |
| Modem Speed | Max is 33,600 bps, V.34 Half-Duplex Kbps |
| Supplies ⁶ | |
| Laser Cartridge Yields (up to) | 1,000-page Black and Color (CMYK) Cartridges, 6,000-page Black Extra High Yield Cartridge, Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798., 2,300-page Colour (CMY) High Yield Cartridges, 3,000-page Black High Yield Cartridge, 3,500-page Colour (CMY) Extra High Yield Cartridges, 8,000-page Black Ultra High Yield Cartridge |
| Photoconductor Estimated Yield: Up to ⁴ | 125000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage |
| Cartridge(s) Shipping with Product | 1,400-page Color (CMY) Starter Return Program Toner Cartridge, 3,000-page Black Starter Return Program Toner Cartridge |
| Paper Handling | |
| Included Paper Handling | 250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed |
| Optional Paper Handling | 550-Sheet Tray, 650-Sheet Duo Tray |
| Paper Input Capacity: Up to | Standard: 250+1 pages 20 lb or 75 gsm bond / Maximum: 1450+1 pages 20 lb or 75 gsm bond |
| Paper Output Capacity: Up to | Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond |
| Media Types Supported | Card Stock, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Card Stock & Label Guide. |
| Media Sizes Supported | 10 Envelope, 7 3/4 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Universal, Oficio, A6 |
| General Information ³ | |
| Standard Ports | USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), 802.11b/g/n Wireless, Front USB 2.0 Specification Hi-Speed Certified port (Type A) |
| Optional Network Ports | Marknet N8372 WiFi Option |
| Noise Level: Operating | Print: 52 dBA / Copy: 56 dBA / Scan: 55 dBA |
| Specified Operating Environment | Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet), Temperature: 10 to 32°C (50 to 90°F) |
| Limited Warranty - See Statement of Limited Warranty | 1-Year Onsite Service, Next Business Day |
| Size (in H x W x D) / Weight (lb.) | 18.2 x 17.4 x 23.1 in. / 60 lb. |

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ²"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ³Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁵Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁴Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

