

## → STITCHFOLD AND OPTIONAL TRIMMER

### WIRE-STITCH BOOKLETMAKER

wire-fed stitching system provides lower operating costs than bookletmakers using pre-formed staples | produces booklets up to 100 pages\* | low maintenance—jogs, stitches, and folds up to 65,000 booklets without replacing wire spools | runs on-line with a variety of collators (interface is included) including the MBM FC 10 | easy to use, push-button controls with 6 digit counter | moveable, magnetic stitching heads | one-step threading for quick and easy set-up | knife fold with dual fold rollers for crisp, consistent folds | powered exit conveyor | transparent safety access covers—machine will not operate with covers in open position | includes back jog, and stand with casters | optional activated clinch, and on-line corner/side stitch gate

Dimensions (D x W x H): 21 x 52 x 24 ½ inches, Shipping weight: 400 lbs.

### OPTIONAL FACE TRIMMER FOR STITCHFOLD BOOKLETMAKER

operates on-line with StitchFold bookletmaker | trims booklets up to 100 pages\* | powered exit conveyor | transparent safety access cover—machine will not operate with cover in open position

Dimensions (D x W x H): 24 ¼ x 48 ½ x 24 inches, Shipping weight: 402 lbs.




### ONE-STEP THREADING



Magnetic stitching heads feature one-step threading for quick and easy set-up.

### POWERED CONVEYOR



The powered exit conveyor on the bookletmaker or trimmer stacks booklets neatly.

### → STITCHFOLD

Speed	2,300 sets/hr*
Sheet capacity	25*
Paper size	4 ¾" x 8 ½" to 12 ¾" x 18 ½"
Power supply	115 V, 60 Hz

### → OPTIONAL TRIMMER

Speed	2,300 sets/hr*
Sheet capacity	25*
Paper size	4 ¾" x 8 ¾" to 12 ¼" x 18 ¼"
Power supply	115 V, 60 Hz

\* may vary due to variations in paper and power supply

Dealer:

**MBM**  
CORPORATION

3134 Industry Drive  
North Charleston, South Carolina 29418  
800-223-2508, fax: 843-552-2974  
[www.mbmcorp.com](http://www.mbmcorp.com)

**IDEAL.MBM**  
CORPORATION

1675 Sismet Road, unit 4  
Mississauga, Ontario L4W 4K8  
800-387-2528, fax: 905-840-1114  
[www.ideal-mbm.com](http://www.ideal-mbm.com)