

→ 4705 MANUAL CUTTER

"SCS" (Safety Cutting System) features: hinged, transparent safety guard on front table (locks automatically while cutting); transparent safety cover on rear table; safety catch (locks blade lever in up position); blade change from front without removing machine covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine; cutting stick can be turned or changed from outside of machine | Solingen steel blade | solid steel blade carrier and adjustable blade guides | extra large cut lever requires minimal effort | spindle clamping system applies even pressure along entire cutting width | spindle-guided back gauge with calibrated crank | precision back gauge measuring scale on front table | all-metal construction | optional stand (shown)

Dimensions (D x W x H): 34 1/2 x 20 inches (50 H with stand), Shipping weight: 297 lbs. (320 with stand).



LOCKING SAFETY GUARD



The hinged front safety guard locks in the lowered position during cutting process.

SPINDLE CLAMP



A solid spindle clamp applies variable, even pressure along the entire cutting width.

EASY CUTTING STICK CHANGE



Cutting sticks can be turned or changed from outside of machine.

→ TRIUMPH 4705

1 7 111101111111111100	
Cutting width	18 ¾"
Cutting height	2 3/4"
Narrow cut	1 3/16"
Cutting length behind blade	18 ¼"
Table length in front of blade	8 1/8"

Dealer:



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com