

#### **CUSTOMER BENEFITS**



Security

Secure network integration, data encryption, hard drive overwrite and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



#### Sustainability

Numerous eco features reduce energy consumption and costs



#### Intuitive operability Operate the MFX-3695i like a

smartphone or tablet with fully customized user interface



# **Application ecosystem** Enhanced efficiency thanks to

Muratec's extensive applications portfolio



#### Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

### **OPTIONS**



PDF enhancements LK-102v3

OCR text recognition LK-105v4

Barcode fonts LK-106

Unicode fonts

OCR A and B fonts LK-108

Document converter pack

ThinPrint® client

Antivirus LK-116

FOIP IP Fax (T.38) LK-117







Document feeder DF-714 (standard)

Working table WT-506

**10-Key pad** KP-102

Replacement SSD EM-908

Keyboard holder KH-102

### 4 MEDIA INPUT

Intelligent media sensor

2 x Universal tray

Large capacity tray

Large capacity tray PC-417

Large Capacity tray LU-302

#### **MEDIA OUTPUT**

Job Separator

Inner Finisher FS-533

Punch kit

Staple finisher FS-539

Staple/booklet finisher FS-539SD

Relay unit RU-513

Punch kit

#### **LEGEND**



This option can only be installed with the respective option above it

### FINISHING FUNCTIONALITIES































stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

Half-fold

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling (offline)

### **DESCRIPTION**

	 Ι Λ	R I	$\sim$	 `	_	۸-	ГΙ		^
ΕN									

LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all
	incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit

#### CONNECTIVITY

EK-608 USB I/F kit	USB keyboard connection
MK-735 Mount kit	Installation kit for ID card reader
ID card reader	Various ID card technologies
AU-102 Biometric authentication	Finger vein scanner
FK-514 Fax board	Super G3 fax, digital fax functionality
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
IIK-221 Wireless I AN	Wireless LAN and wireless LAN Access Point Mode

#### OTHERS

WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard

#### MEDIA INPUT

IM-102 Intelligent media sensor	Auto detects paper weight and type
PC-116 1x Universal tray	500 sheets, 5.5" x 8.5" to 11" x 17", 52-256 gsm
PC-216 2x Universal tray	2x 500 sheets, 5.5" x 8.5" to 11" x 17", 52-256 gsm
PC-416 Large capacity tray	2,500 sheets, 8.5" x 11", 52-256 gsm
PC-417 Large capacity tray	1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m <sup>2</sup>
LU-302 Large capacity tray	3,000 sheets, 8.5" x 11", 52-256 gsm
MK-730 Banner tray	Multipage banner feeding

#### MEDIA OUTPUT

FS-539 Staple finisher	50-sheet stapling; 3,200 sheets max. output		
FS-539SD Booklet finisher	50-sheet stapling; 20 sheets booklet finisher;		
	2,200 sheets max. output		
PK-524 Punch kit for FS-539/SD	2/3-hole punching; auto switching		
RU-513 Relay unit	For FS-539/SD installation		
JS-506 Job separator	Separation of fax output; etc.		
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output		
PK-519 Punch kit for FS-533	2/3-hole punching, auto switching		

## **TECHNICAL SPECIFICATIONS**

### SYSTEM SPECIFICATIONS

System speed 8.5" x 11"	Up to 36 ppm
System speed 11" x 17"	Up to 18 ppm
Autoduplex speed 8.5" x 11"	Up to 36 ppm
1st page out time 8.5" x 11"	4.6 sec.
Warm-up time	Approx. 12 sec. <sup>1</sup>
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S)
Automatic document feeder	Up to 100 originals; A6–A3; 35–163 gsm;
(standard)	Dual scan ADF
ADF double feed detection	Standard (with dual scan ADF)
Printable paper size	A6-SRA3; banner paper max. 1,200 x 297 mm;
	customized paper sizes
Printable paper weight	52-300 g/m <sup>2</sup>
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500 sheets; 3.5" x 8.5" to 11" x 17"; custom sizes; 52–256 gsm
	1x 500 sheets; 5.5" x 8.5" to 12" x 18"; custom sizes; 52–256 gsm
Paper tray input (optional)	2x 500 sheets; 5.5" x 8.5" to 11" x 17"; 52–256 gsm
	1x 2,500 sheets; 8.5" x 11"; custom sizes; 52–256 gsm
Large capacity tray (optional)	1x 3,000 sheets; 8.5" x 11"; custom sizes; 52–256 gsm
Manual bypass	150 sheets; 3.5" x 8.5" to 12" x 18"; Custom sizes; Banner;
	60-300 gsm
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet
Automatic duplexing	5.5" x 8.5" to 12" x 18"; 52–256 gsm

#### SYSTEM SPECIFICATIONS

Up to 250 sheets / up to 3,300 sheets (standard/max)
Max. 50 sheets or 48 sheets + 2 cover sheets (up to $209 \text{ g/m}^2$ )
Max. 100 sets
Max. 3 sheets
Max. 30 sets; unlimited (without tray)
Max. 20 sheets or 19 sheets + 1 cover sheet (up to $209  \text{g/m}^2$ )
Max. 20 booklets; unlimited (without tray)
Rec. 33,000 pages; Max. <sup>2</sup> 175,000 pages
Black up to 25,000 pages
Black up to 245,000/1,000,000 pages (drum/developer)
110–120 V / 50/60 Hz; Less than 1.50 kW
24.2" x 27" x 31" (without options)
Approx. 187 lbs. (without options)

### PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2; Windows Server
	2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS)

#### SCANNER SPECIFICATIONS

Scan speed	Up to 100 ipm in simplex (mono)
	Up to 200 ipm in duplex (mono)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-
	to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact
	XPS; PPTX
	Optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/
	PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

#### **COPIER SPECIFICATIONS**

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. A3
Magnification	25–400% in 0.1% steps; Auto-zooming

#### **FAX SPECIFCIATION**

Fax standard	Super G3 (optional)
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

#### LISER BOX SPECIFICATIONS

USER BOX SPECIFICATIONS	
Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

#### SYSTEM FEATURES

Security	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL3 and TLS1.0/1.1/1.2 network communica-
	tion; IPsec support; IEEE 802.1x support; User authentication;
	Authentication log; Secure print; Kerberos; Hard drive overwrite;
	Hard drive data encryption (AES 256); Confidential fax; Print user
	data encryption
	optional: Antivirus realtime scanning (Bitdefender®); Copy
	protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

<sup>&</sup>lt;sup>1</sup> Warm-up time may vary depending on the operating environment and usage

- All specifications refer to letter-size paper of 80 gsm weight.
   The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
  particular page size (6% coverage of letter).. The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

  - Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Muratec does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

















© 2020 MURATEC AMERICA, INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited.



For complete information on Muratec products and solutions, please contact: 469.429.3300 or visit www.Muratec.com



Muratec America, Inc. 14800 Landmark Blvd., Suite 720, Dallas, TX 75254





 $<sup>^{2}</sup>$  If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed