

## MFX-7595i black & white A3 multifunctional printer


## BRIDGE THE GAP BETWEEN PAPER AND DIGITAL BUSINESS-CLASS DOCUMENT SOLUTIONS

# MFX-iNTELLIGENT Series





### **CUSTOMER BENEFITS**



## **DESCRIPTION**

| ENHANCED FEATURES                |  |
|----------------------------------|--|
| LK-102v3 PDF enhancements        | PDF/A(1b), PDF encryption, digital signature                     |
| LK-105v4 OCR text recognition    | Searchable PDF and PPTX  |
| LK-106 Barcode fonts             | Supports native barcode printing                                 |
| LK-107 Unicode fonts             | Supports native Unicode printing                                 |
| LK-108 OCR A and B fonts         | Supports native OCR A and B font printing                        |
| LK-110v2 Document converter pack | Generates various file formats incl. DOCX, XLSX and PDF/A        |
| LK-111 ThinPrint® client         | Print data compression for reduced network impact                |
| LK-116 Antivirus                 | Bitdefender® antivirus provides real time scanning of all incom- |
|                                  | ing and outgoing data  |
| LK-117 FOIP activation           | Fax over IP networks (T.38), requires fax kit                    |
|                                  |  |

Super G3 fax, digital fax functioality

USB keyboard connection; Bluetooth

USB keyboard connection

Various ID card technologies

Installation kit for ID card reader

Finger vein scanner

Wireless LAN and wireless LAN Access Point Mode

| IM-102 Intelligent Media Sensor    | Detects paper type and weight automatically    |
|------------------------------------|--|
| LU-303 Large capacity tray         | 3,000 sheets, A4, 52-256 g/m <sup>2</sup>      |
| LU-205 Large capacity tray         | 2,500 sheets, A4–SRA3, 52–256 g/m <sup>2</sup> |
| MK-730 Banner tray                 | Multipage banner feeding                       |
| MEDIA OUTPUT                       |  |
| OT-514 Output tray                 | Output tray used instead of finisher           |
| FS-539 Staple finisher             | 50-sheet stapling; 3,200 sheets max. output    |
| FS-539SD Booklet finisher          | 50-sheet stapling; 20-sheet booklet finisher;  |
|                                    | 2,200 sheets max. output                       |
| PK-524 Punch kit for FS-539/SD     | 2/3-hole punching; auto switching              |
| FS-540 Staple finisher             | 100-sheet stapling; 3,200 sheets max. output   |
| FS-540SD Booklet finisher          | 100-sheet stapling; 20-sheet booklet finisher; |
|                                    | 2,700 sheets max. output                       |
| PK-526 Punch kit for FS-540/SD     | 2/3-hole punching; auto switching              |
| RU-519 Relay unit                  | For FS-539/SD or FS-540/SD installation        |
| PI-507 Post inserter for FS-540/SD | Cover insertion; post finishing                |
| PI-507 Post Inserter for FS-540/5D |  |
| JS-602 Job separator for FS-540/SD | Separation of fax output; etc.                 |

To place USB keyboard

Keyboard for alpha numeric data entry

CONNECTIVITY FK-514 Fax board

UK-221 Wireless LAN

EK-608 USB I/F kit

EK-609 USB I/F kit

MK-735 Mount kit

AU-205H ID card reader

AU-102 Biometric authentication

| OTHERS               |  |
|----------------------|--|
| WT-506 Working table | Authentication device placement          |
| WT-519 Working table | Working table for upright panel          |
| KP-102 10-Key pad    | For numeric entry instead of touchscreen |
| SC-509 Security kit  | Copy guard function                      |
| EM-908 1 TB SSD      | 1 TB SSD to increase storage space       |

## **TECHNICAL SPECIFICATIONS**

#### SYSTEM SPECIFICATIONS

| SYSTEM SPECIFICATIONS          |   |
|--------------------------------|---|
| System speed letter            | Up to 75  |
| System speed 11" x 17"         | Up to 37  |
| Auto duplex speed letter       | Up to 75  |
| 1st page out time letter       | 2.8/3.8 sec.  |
| Warm-up time                   | Approx. 17 <sup>1</sup>   |
| Imaging technology             | Laser   |
| Toner technology               | Simitri <sup>®</sup> HD polymerized toner                               |
| Panel size/resolution          | 10.1" / 1024 x 600  |
| System memory                  | 8,192 MB (standard/max)   |
| Solid state drive              | 256 GB SSD (standard) / 1 TB SSD (optional)                             |
| Interface                      | 10/100/1,000-Base-T Ethernet; USB 2.0;                                  |
|                                | Wi-Fi 802.11 b/g/n/ac (optional)  |
| Network protocols              | TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour             |
| Automatic document feeder      | Up to 300 originals; A6–A3; 35–210 g/m <sup>2</sup> ; Dual scan ADF     |
| ADF double feed detection      | Standard  |
| Printable paper size           | 3.5" x 5.5" – 12" x 18"; custom paper sizes,                            |
|                                | banner paper max. 47.2" x 11.7"   |
| Printable paper weight         | 52-300 g/m <sup>2</sup>   |
| Paper input capacity           | 3,650 sheets / 6,650 sheets (standard/max)                              |
| Paper tray input (standard)    | 1x 500; 3.5" x 5.5" - 11" x 17"; custom sizes; 52-256 g/m <sup>2</sup>  |
|                                | 1x 500; 5.5" x 8.5" - 12" x 18"; custom sizes; 52-256 g/m <sup>2</sup>  |
|                                | 1x 1,500; 5.5" x 8.5" – 11" x 17"; 52–256 g/m²                          |
|                                | 1x 1,000; 5.5" x 8.5" – 11" x 17"; 52–256 g/m²                          |
| Large capacity tray (optional) | 1x 3,000;5.5" x 8.5" – 11" x 17"; 52–256 g/m <sup>2</sup>               |
|                                | 1x 2,500; 8.5" x 11" – 12" x 18"; custom sizes; 52–256 g/m <sup>2</sup> |
| Manual bypass                  | 150 sheets; 3.5" x 5.5" - 12" x 18"; custom sizes; banner; 60-300       |
|                                | g/m²  |
| Finishing modes (optional)     | Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;        |
|                                | Tri-fold; Booklet; Post insertion; Z-fold                               |
|                                |   |

| Automatic duplexing          | 3.5" x 5.5" – 12" x 18"; 52–256 g/m <sup>2</sup>                            |
|------------------------------|---|
| Output capacity              | Up to 200 sheets / up to 3,300 sheets (standard/max)                        |
| Stapling                     | Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m <sup>2</sup> ) |
| Stapling output capacity     | Max. 200 sets   |
| Tri-fold                     | Max. 3 sheets   |
| Tri-fold capacity            | Max. 50 sets; unlimited (without tray)                                      |
| Booklet                      | Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m <sup>2</sup> )   |
| Booklet output capacity      | Max. 35 booklets; unlimited (without tray)                                  |
| Duty cycle (monthly)         | Max. <sup>2</sup> 300,000 pages   |
| Toner lifetime               | Black up to 45,000 pages  |
| Imaging unit lifetime        | Black up to 240,000/1,000,000 pages (drum/developer)                        |
| Power consumption            | 110-120V/ 50/60 Hz; Less than 2.10 kW                                       |
| System dimension (W x D x H) | 24.2" x 27.1" x 47.5" (without options)                                     |
| System weight                | Approx. 307 lbs. (without options)  |

#### PRINTER SPECIFICATIONS

OTHERS

KH-102 Keyboard holder

External Keyboard

| Print resolution          | 1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi              |
|---------------------------|--|
| Page description language | PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS       |
| Operating systems         | Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64) |
|                           | Windows Server 2008 (32/64); Windows Server 2008 R2;       |
|                           | Windows Server 2012; Windows Server 2012 R2;               |
|                           | Windows Server 2016; Windows Server 2019; Macintosh OS X   |
|                           | 10.11 or later; Unix; Linux; Citrix                        |
| Printer fonts             | 80 PCL Latin; 137 PostScript 3 Emulation Latin             |
| Mobile printing           | AirPrint (iOS)   |
|                           | Konica Minolta Print Service (Android);                    |
|                           | Konica Minolta Mobile Print (iOS/Android)                  |
|                           |  |

#### MFX-7595i Datasheet

#### SCANNER SPECIFICATIONS

4

| Up to 280/280 ipm in duplex (mono/color) can resolution Up to 600 x 600 dpi Can modes Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV Scan-to-DPWS; Scan-to-URL; TWAIN scan le formats JPEG; TIFF; PDF,Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/PPTX/XLSX                   |                   |   |
|--|-------------------|---|
| Can resolution         Up to 600 x 600 dpi           can modes         Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home<br>Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV<br>Scan-to-DPWS; Scan-to-URL; TWAIN scan           le formats         JPEG; TIFF; PDF,Compact PDF; Encrypted PDF; XPS;<br>Compact XPS; PPTX<br>optional: Searchable PDF; PDF/A 1a and 1b;<br>Searchable DOCX/PPTX/XLSX | Scan speed        | Up to 140/140 ipm in simplex (mono/color)               |
| France         Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home<br>Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV<br>Scan-to-DPWS; Scan-to-URL; TWAIN scan           le formats         JPEG; TIFF; PDF,Compact PDF; Encrypted PDF; XPS;<br>Compact XPS; PPTX<br>optional: Searchable PDF; PDF/A 1a and 1b;<br>Searchable DOCX/PPTX/XLSX   |                   | Up to 280/280 ipm in duplex (mono/color)                |
| Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAU<br>Scan-to-DPWS; Scan-to-URL; TWAIN scan<br>JPEG; TIFF; PDF,Compact PDF; Encrypted PDF; XPS;<br>Compact XPS; PPTX<br>optional: Searchable PDF; PDF/A 1a and 1b;<br>Searchable DOCX/PPTX/XLSX   | Scan resolution   | Up to 600 x 600 dpi                                     |
| Scan-to-DPWS; Scan-to-URL; TWAIN scan           le formats         JPEG; TIFF; PDF,Compact PDF; Encrypted PDF; XPS;<br>Compact XPS; PPTX<br>optional: Searchable PDF; PDF/A 1a and 1b;<br>Searchable DOCX/PPTX/XLSX  | Scan modes        | Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); |
| le formats JPEG; TIFF; PDF,Compact PDF; Encrypted PDF; XPS;<br>Compact XPS; PPTX<br>optional: Searchable PDF; PDF/A 1a and 1b;<br>Searchable DOCX/PPTX/XLSX  |                   | Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;  |
| Compact XPS; PPTX<br>optional: Searchable PDF; PDF/A1a and 1b;<br>Searchable DOCX/PPTX/XLSX  |                   | Scan-to-DPWS; Scan-to-URL; TWAIN scan                   |
| optional: Searchable PDF; PDF/A1a and 1b;<br>Searchable DOCX/PPTX/XLSX   | File formats      | JPEG; TIFF; PDF,Compact PDF; Encrypted PDF; XPS;        |
| Searchable DOCX/PPTX/XLSX  |                   | Compact XPS; PPTX                                       |
|  |                   | optional: Searchable PDF; PDF/A 1a and 1b;              |
| can destinations 2,000 destinations + 100 groups; LDAP support   |                   | Searchable DOCX/PPTX/XLSX                               |
|  | Scan destinations | 2,000 destinations + 100 groups; LDAP support           |

#### COPIER SPECIFICATIONS

| Copy resolution | 600 x 600 dpi                    |
|-----------------|----------------------------------|
| Gradation       | 256 gradations                   |
| Multicopy       | 1-9,999                          |
| Original format | Max. 11" x 17"                   |
| Magnification   | 25-400% in 0.1% steps; Auto-zoom |

#### FAX SPECIFCIATION

| Fax standard     | Super G3 (optional)                |
|------------------|------------------------------------|
| Fax transmission | Analog; i-Fax; Color i-Fax; IP-Fax |
| Fax resolution   | Up to 600 x 600 dpi                |
| Fax compression  | MH; MR; MMR; JBIG                  |
| Fax modem        | Up to 33.6 Kbps                    |
| Fax destinations | 2,000 single + 100 groups          |

| Storable documents | Up to 3,000 documents or 10,000 pages                                |
|--------------------|--|
| User boxes         | Public; Personal (with password or authentication);                  |
|                    | Group (with authentication)  |
| System boxes       | Secure print; Encrypted PDF print; Fax receipt; Fax polling          |
| SYSTEM FEATURES    |  |
| Security           | ISO 15408 HCD-PP Common Criteria (in evalutation);                   |
|                    | IP filtering and port blocking;                                      |
|                    | SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support         |
|                    | IEEE 802.1x support; User authentication; Authentication log;        |
|                    | Secure print; Kerberos;  |
|                    | Data encryption (AES 256); Confidential fax;                         |
|                    | Print user data encryption   |
|                    | Optional: Antivirus realtime scanning (Bitdefender®);                |
|                    | Copy protection (Copy Guard; Password Copy)                          |
| Accounting         | Up to 1,000 user accounts;   |
|                    | Active Directory support (user name + password + e-mail + smb folder |
|                    | User function access definition;                                     |
|                    | Authentication by mobile device (Android)                            |
|                    | optional: Biometric authentication (finger vein scanner);            |
|                    | ID card authentication (ID card reader);                             |
|                    | Authentication by mobile device (iOS)                                |
| Software           | Net Care Device Manager; Data Administrator; Box Operator;           |
|                    | Web Connection; Print Status Notifier; Driver Packaging Utility;     |
|                    | Log Management Utility   |

<sup>1</sup> Warm-up time may vary depending on the operating environment and usage

<sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

All specifications refer to 8.5" x 11"-size paper of 80 g/m<sup>2</sup> quality.

- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
  particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and
  other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient
  temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Muratec does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



For complete information on Muratec products and solutions, please contact: **469.429.3300** or visit **www.Muratec.com** 

© 2020 MURATEC AMERICA, INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. MURATEC and the MURATEC logo are registered trademarks or trademarks of MURATEC AMERICA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



Muratec America, Inc. 14800 Landmark Blvd., Suite 720, Dallas, TX 75254

www.muratec.com

