Ricoh Aficio SP 5200S/SP 5210SF/ SP 5210SR

RICOH

Digital Imaging System Versatile, powerful performance



produce



deliver



Discover the value of convenience and productivity. Turn new challenges and everyday demands into cost-saving opportunities—with the flexible RICOH® Aficio® SP 5200S/SP 5210SF/SP 5210SR Digital Imaging System. The powerful system is specifically designed to simplify everyday general office tasks for midsize workgroups. Users can quickly access exceptional multifunction performance—including monochrome copy, color scan, print and fax capabilities—to complete a wide range of projects faster with incredibly low cost-per-page. Ideal for busier workloads, it offers incredible speed, quality, finishing and intuitive controls to streamline workflow so you can manage your documents more efficiently. Its compact design is packed with versatility for optimal production and value. Plus, it's ideal for organizations deploying a print management solution with Ricoh's Managed Document Services (MDS).



The Ricoh Aficio SP 5200S/SP 5210 SP 5210SR combines multifunction performance with user-friendly convenience to streamline workflow for mid-size workgroups in a wide range of environments.

ProductiveFlexibleSecureVersatile

Deliver More Efficiently

The Ricoh Aficio SP 5200S/SP 5210SF/SP 5210SR offers a wide range of innovative features to improve productivity.

- Boost throughput with exceptional print speeds. The SP 5200S generates up to 47 pages-per-minute. The SP 5210SF and SP 5210SR print up to 52 pages-per-minute.
- Produce crisp, sharp text at up to 1200 x 600 dpi resolution for high-quality, compelling results.
- Take advantage of easy-to-use scanning capabilities to simplify workflow with cost-effective electronic document storage and distribution.
- Work quickly with near-instant system readiness. Warm-up time is less than 20 seconds and first print/copy times are less than 8 seconds.
- Reduce paper, mailing costs and filing space with standard automatic duplexing at nearly 90% percent of rated simplex speeds.
- Maximize convenience with paperless faxing. Super G3 faxing, Internet Fax, IP Fax, and LAN Fax support come standard on the SP 5210SF and are optional on the SP 5200S and SP 5210SR.

Manage More Conveniently

The Ricoh Aficio SP 5200S/SP 5210SF/SP 5210SR includes user-friendly controls for convenient, intuitive operation.

- Maximize uptime, streamline maintenance and reduce cost-per-page output with a high-yield, 25,000-page AIO print cartridge. When depleted, users can quickly replace the cartridge without technical assistance and recycle the spent cartridge with a provided return label.
- Gain clear, unobstructed access to critical device information from virtually any angle with an innovative 8.5" full-color tilting LCD panel.*
- Perform all of your general office tasks from a single machine without compromising floor space or your budget. The compact footprint offers users more options for placement in more office environments.
- Access most functions, including all paper sources and the print cartridge, in even the tightest spaces via the forward-facing design.
- Set dozens of system parameters such as paper supplies and user authentication from the desktop with Web Image Monitor.
- Monitor device usage in real time with the Ricoh @Remote[™] Intelligent Management System and receive service notifications quickly to minimize downtime.

Protect Document Integrity

Ensure the right information gets in the right hands with advanced security features that can protect sensitive information from a multitude of threats.

- Restrict access to system functions with user authentication. Up to 500 user codes can be registered and assigned for optimal efficiency in larger workgroups.
- Ensure optimal data protection with the Data OverwriteSecuritySystem (DOSS). When enabled, it destroys latent images and data from the internal hard drive to prevent document reconstruction.
- Stifle attempts by hackers to steal print job data and passwords transmitted over the LAN with SSL Data Encryption or Wi-Fi Protect Access Support.
- Choose the optional Enhanced Locked Print-NX to store print jobs with encrypted data at the MFP until the user swipes an ID card or enters ID information at the control panel to release the job.



The adjustable full-color touch screen control panel on the SP 5210SF and SP 5210SR can be tilted to give users greater visibility and to provide easy access to the 1-bin and finisher trays. It even offers animated guidance screens for easy step-by-step instructions.



A USB Type A port is conveniently located in the control panel for quick and easy printing from/scanning to removable media.



The all-in-one (AIO) print cartridge is ideal for users without technical training. Easily accessible within seconds simply by opening the front cover, this convenient feature restores output to "like-new" image quality.

Share Information Cost-Effectively

The Ricoh Aficio SP 5200S/SP 5210SF/SP 5210SR offers a host of scanning capabilities to make electronic document capture and distribution quick, easy and free.

- Speed scanning tasks with the 50-sheet Automatic Reversing Document Feeder (ARDF). It accepts originals up to 8.5" x 14" (up to 49" long in custom mode for banner scanning) for incredible flexibility and productivity.
- Convert hardcopy documents to electronic files and incorporate them into new documents using TWAIN scanning capabilities.
- Send scanned documents to hundreds of recipients cost-free over the network in one operation with Scan-to-Email/Folder/URL with LDAP support.
- Quickly transfer documents and images to portable media with Scan-to-Media (USB/SD Card) to streamline distribution in any environment.
- Reduce file sizes for scanned color documents without compromising image quality with high compression PDF for faster transmission and printing.

Connect Your User Network

The Ricoh Aficio SP 5200S/SP 5210SF/SP 5210SR includes flexible networking support that enables workgroups to produce a wide range of jobs efficiently.

- Use the robust Controller to support advanced networking features, device monitoring utilities and data protection functions, including innovative device customization and host print capabilities.
- Complete multiple projects with ease. Powerful performance from the 533 MHz processor provides the bandwidth to prepare data streams and expedite project queues to meet the needs of corporate workgroups with 8.5" x 11"/ A4 monochrome workflows.
- Enjoy full compatibility throughout the office with standard USB 2.0 Hi Speed Interface and Ethernet connectivity, including support for PCL and genuine Adobe PostScript3[®] in Windows and Macintosh network environments.
- Store up to 3,000 documents (up to 9,000 pages) on the powerful 128 GB Hard Disk Drive for easy, secure document management.

Handle Every Task

Engineered to help users complete everyday office tasks with ease, the Ricoh Aficio SP 5200S/SP 5210SF/ SP 5210SR offers flexible media handling and finishing to expedite workflow.

- Support up to 8.5" x 14" paper sizes with front-loading, user-adjustable paper sources.
- Increase paper supply without compromising floor space. Up to three additional paper trays can be added for a maximum paper capacity of 2,300 sheets.
- Finish sets up to 50 pages automatically, and offset stack up to 250 sheets, with the internal finisher that comes standard on the SP 5210SR.
- Accommodate stocks up to 59 lb. Bond/120 lb. Index (220 g/m²) from any paper source to ensure print jobs are executed on time and deadlines are met.
- Enhance envelope output productivity with universal feeding.
- Extend acceptable paper sizes up to 35" long in the bypass tray to accommodate banner printing and keep more projects in-house.



Accommodate thicker paper stock—up to 120 lb. Index—from every paper tray to ensure more projects can be completed to specifications in-house.



These flexible systems can be configured for desk or floor placement. Stack up to 3 optional Paper Feed Units to boost input capacity to 2,300 sheets.* The Paper Feed Unit TK1100 with casters is designed specifically for floor placement.

*Requires the assistance of a service technician.

The Total Green Office Solution



Ricoh continues its longstanding commitment to developing office solutions with environmentally friendly and superior energy- and supply-saving features, without compromising productivity.

CompactEffectiveClearEngaged

User-friendly design improves office productivity.

User-Adjusted LCD Control Panel* See the easy-to-read, tilted control panel comfortably from virtually anywhere.

Super G3 Faxing

Perform a variety of fax functions with preprogrammed speed, quick and group dial shortcuts on the SP 5210SF. A 1-Bin Tray is included to collect inbound faxes.

100-Sheet Bypass Tray Extend paper sizes up to 35" long for banner production.

Standard 550-Sheet Paper Tray

Front-facing, user-adjustable paper trays accommodate envelopes and paper sizes up to 8.5" x 14" and stock weights up to 80 lb. Bond/120 lb. Index.

3 x 550-Sheet Paper Trays Add up to three additional paper trays to expand paper capacity to 2,300 sheets.

*SP 5210SF and SP 5210SR only.

Pre-configured to meet your needs.







Model	SP 5200S	SP 5210SF	SP 5210SR		
Standard Functions	Copy / Print / Scan	Copy / Print / Scan / Fax	Copy / Print / Scan / Finishing		
Print Speed	47 cpm/ppm	52 cpm/ppm			
Super G3 Faxing	Optional	Standard	Optional		
Color Touch Panel	Fixed Placement	Adjustable			
Internal Staple Finisher	N/A	N/A	Standard		
Inner 1-Bin Tray	N/A	Standard	N/A		
Output Capacity	500 sheets	600 sheets	250 sheets		

50-Sheet Automatic Reversing Document Feeder (ARDF) Process originals efficiently—up to 8.5" x 14" and custom banner scanning up to 49" long—to speed the scanning process.

Internal Finisher

Staple up to 50 pages and stack up to 250 sheets with the space-saving internal finisher on the SP 5210SR.

Duplex Unit

Copy and print on both sides of each sheet of paper, reducing paper usage by half.

Easy-Grip Paper Tray Handles Open and close doors with only one hand, sitting or standing.

Ricoh Aficio SP 5200S/SP 5210SF/SP 5210SR

Aficio

System Specifications

Main Unit				Commission Commission		· 100 -1-1
Afinia CD 52000	Deet # 400001	Supported Environments	Windows XP, Vista, 7, Server 2003/2003R2, Server 2008/2008R2, Mac OS X v.10.2+, Novell	Scanning Speed Original Capacity/Size	Up to 40-ppm (B&W, LTR @ 200 See Scanner & Document Feedin	
Aficio SP 5200S Aficio SP 5200SG*	Part # 406851 Part # 407570		NetWare v 6.5+, Citrix Presentation Server,	Auto Dialing	Up to 2,000 Quick Dial numbers	
Aficio SP 5210SF	Part # 406852	Network Protocols	UNIX/Linux TCP/IP (IPv4, IPv6), IPX/SPX, Bonjour	5	100 Group Dial numbers (500 loca	tions per Group
Aficio SP 5210SFG*	Part # 407571	Software Utilities	Bundled Utilities: Web Image Monitor,	Page Memory Capacity	Standard: 4 MB RAM (approx. 32	
Aficio SP 5210SR Aficio SP 5210SRG*	Part # 406853 Part # 407572		Font Manager 2000. Optional Utilities:	Momony Packup	Maximum: 28 MB RAM (approx.	2,240 pages)
*Trade Agreement Acts (TAA) Con			SmartDeviceMonitor for Admin Acounting Package, SmartDeviceMonitor for Client	Memory Backup Additional Fax Modes	1 hour LAN Fax, Internet Fax (T.37), IP Fa	ax (T 38)
Configuration	Desktop		DeskTopBinder Lite, @Remote Communication	LAN Fax	Standard on SP 5210SF, requires	
Printing Technology	Laser beam scanning & electrophotographic		Gate S Pro		Type 5200 for SP 5200S and SP	5210SR;
	printing; Monocomponent toner development; All-In-One Print Cartridge Technology	Standard Security Features	Administrator Authentication (5 levels), User Authentication (5 types), HDD Overwrite (DOSS)		Connection; 10/100Base-TX Ethe	
Scanning Technology	Full-Color Flatbed Scanning w/CCD Image Sensor		& Data Encryption, Secure Print, Encrypted Secure		802.11 a/g Wireless, or Gigabit E interface; Protocol: G3; Max. Ad	
Scan Type	Sheet, book, three-dimensional objects		Print, Encrypted PDF Mode, Scan-to-Web Mail (SMTP over SSL), IP Address Filtering, Transport		500; Operating Systems: Window	
Print Speed (LTR)	SP 5200S: 47-ppm, SP 5210SF: 52-ppm, SP 5210SR: 52-ppm		Layer Security (TLS), SSL Communication, IPv6,		2003, Vista, 7, Server 2008/R2; I	
First Print Speed	7.5 seconds or less		IP Sec, SNMPv3, Quota Setting		Letter, Legal, A4, A5	
Warm-up Time Grayscale	20 seconds or less 256 levels	Controller Options	IEEE802.11 a/g Interface Unit Type J (Part #414008); Gigabit Ethernet Board Type C	Internet Fax	Standard on SP 5210SF, requires F 5200 for SP 5200S and SP 5210	
Copy Resolution	600 x 600 dpi via Platen Glass, 600 x 300 dpi		(Part #406914); Bluetooth Interface Unit Type D		10/100Base-TX Ethernet, IEEE 802	
Delet Developing	via ARDF		(Part #415818); IPDS Unit Type 5210 (Part #406816); Data Overwrite Security Unit Type I*		or Gigabit Ethernet interface; Pro	
Print Resolution Fax Resolution	1200 x 600 dpi, 600 x 600 dpi, 300 x 300 dpi 200 x 200 dpi, 200 x 100 dpi standard; 200 x		(Part #413955); Remote Communication Gate		Mode; Max. Addresses Per TX: 50	
	400 dpi, 400 x 400 dpi with optional memory		A (Part #415135); Fax Option Type SP5200		Function: Conversion of files to T E-mail TX to a PC; Original Size:	
Document Feeding	Automatic Reversing Document Feeder (Standard); Original Capacity: 50 sheets		(Part #406594); Fax Memory Unit Type B 32MB (Part #001342MIU); Telephone Handset Type	IP Fax	Standard on SP 5210SF, requires	
Oric x 13	Original Size: 5.5" x 8.5" – 8.5" x 14" (128 mm		1018 (Part #410781); HotSpot MFP Option		5200 for SP 5200S and SP 5210	
	x 139.7 mm – 216 mm x 355.6 mm); Custom:		Type E (Part #415621); Browser Unit Type E		10/100Base-TX Ethernet, IEEE 80	
Max. Imageable Area	Up to 49.6" (1260 mm) (Simplex only) Platen: 8.5" x 11.69" (216 x 297 mm)		(Part #414715); File Format Converter Type E (Part #414007); CAC/PIV v3 support**		Wireless, or Gigabit Ethernet inte	
-	ARDF: 8.5" x 49.6" (216 x 1260 mm)	*For Common Criteria Certification			T.38, TCP, UDP/IP communication; To/from IP Fax compatible maching	
Multiple Copies	Up to 999 Platen: 25% – 400% in 1% increments	**For TAA Compliant models only	Option requires installation by a Ricoh Authorized		To/from G3 Fax machines via Vol	
Zoom	ARDF: 25% – 200% in 1% increments	Technician.			Original Size: Letter, A4 (216 mm	
Preset Reduction	93%, 78%, 65%	Scanner			Custom: Up to 8.5" x 47" (216 n	nm x 1200 mn
Preset Enlargement Standard Paper Supply	155%, 129% 550-sheet Tray + 100-sheet Bypass = 650 sheets	Scanner Type	Full Color CCD	Hardware Accesso	ries	
Optional Paper Supply	550-sheet Paper Feed Unit (Up to 3 may be installed)	Scanning Resolutions	Scan-To Modes: 100/200/300/400/600 dpi (Black &			
Max. Paper Capacity	2,300 sheets		White, ARDF & Platen); 100/200/300 dpi (Full Color, ARDF); 100/200/300/400/600 dpi (Full Color, Platen).	Optional Paper Feed Unit (Capacity	550 sheets, 1 or 2 units may be	installed
Automatic Duplexing	Standard, up to 8.5" x 14" (Approx. 90% productivity)		TWAIN/WSD/WIA: 100 – 600 dpi in 1% increments	Paper Size Range	3.86" x 6.3" - 8.5" x 14.01" (98	
Output Capacity	SP 5200S: 500 sheets face down; SP 5210SF:		(Black & White, ARDF); 100 – 1200 dpi in 1% increments (Black & White, Platen); 100 – 600 dpi in		– 216 mm x 356 mm)	
	600 sheets face down (w/1Bin Tray); SP 5210SR: 250 sheets face down (w/Finisher)		1% increments (Full Color, ARDF & Platen)	Paper Weight	14 lb. Bond – 80 lb. Cover/120 ll	b. Index
Paper Sizes	Standard Tray, Standard Sizes: Letter, Legal,	Default Resolution	200 dpi	Dimensions (WxDxH)	(52 – 220 g/m ²) 17.8" x 20.3" x 5.9" (450 mm x 51)	5 mm v 150 mr
	Executive, Half Letter, A4, A5, A6, B5, B6, F/GL,	Scanning Speed Max. Original Size	Over So-Ipin (bawin c, En & 200 dpi)		5 1111 × 150 1111	
	Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" – 8.5"	-	ARDF: Up to 8.5" x 49.6" (216mm x 1260 mm)	Optional Paper Feed Unit with Casters (TK1100) – Part # 406600		
	(98 mm – 216 mm), Length: 5.52" – 14.01"	Protocols	Network: TCP/IP; Scan-to-Email: POP, SMTP; Scan-to-Folder: SMB, FTP, NCP	Capacity	550 sheets, 1 unit may be installed	
	(140 mm – 356 mm). Bypass Tray, Standard Sizes: Letter, Legal, Executive, Half Letter, A4,	Scan Modes	B&W Text, B&W Text/Line Art, B&W Text/Photo,	Paper Size Range	3.86" x 6.3" - 8.5" x 14.01" (98	mm x 160 mr
	A5, A6, B5, B6, F/GL, Foolscap, Folio; Envelopes:		B&W Photo, Grayscale, Full-Color Text/Photo,	Paper Weight	- 216 mm x 356 mm)	- testas
	Com10, Monarch, C6, C5, DL. Custom Sizes:		Full-Color Glossy Photo, Auto Color Select (ACS)		14 lb. Bond – 80 lb. Cover/120 ll	o. Index
		Image Density	Auto + 7-sten Manual scale	ruper meight		
	Width: 2.52" - 8.5" (64 mm - 216 mm),	Image Density Image Rotation	Auto + 7-step Manual scale Supported	Dimensions (WxDxH)	(52 – 220 g/m²) 24.7" x 25.0" x 8.7" (627 mm x	635 mm x
	Width: 2.52" – 8.5" (64 mm – 216 mm), Length: 5.52" – 35.43" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal,	Image Rotation SADF/Batch Mode	Supported Supported	Dimensions (WxDxH)	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters)	635 mm x
	Width: 2.52" – 8.5" (64 mm – 216 mm), Length: 5.52" – 35.43" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL,	Image Rotation	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/		(52 – 220 g/m²) 24.7" x 25.0" x 8.7" (627 mm x	635 mm x
	Width: 2.52" – 8.5" (64 mm – 216 mm), Length: 5.52" – 35.43" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch,	Image Rotation SADF/Batch Mode	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Enail, Scan-to-Folder (SMB/FTP/NCP);	Dimensions (WxDxH) Weight Internal Finisher (Standard	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only)	635 mm x
	Width: 2:52" - 8.5" (64 mm - 216 mm), Length: 5:52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 6.3" - 14.01"	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card)	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets	635 mm x
Paper Weights	Width: 2.52" - 8.5" (64 mm - 216 mm), Length: 5.52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, 85, 86, F/GL, Foolscap, Folics; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm)	Imäge Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Enail, Scan-to-Folder (SMB/FTP/NCP);	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 52105R only) 250 sheets Shift Sort, Stack, Staple	
Paper Weights	Width: 2.52" - 8.5" (64 mm - 216 mm), Length: 5.52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folics; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm) Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²)	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-JRL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication SOD; Attention: To, Cc, bcc	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5	
Paper Weights	Width: 2.52" - 8.5" (64 mm - 216 mm), Length: 5.52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folics; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm) Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²) Bypass Tray: 14 - 59 lb. Bond/120 lb. Index	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Emal, Scan-to-Folder (SMB/FTPN/CP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 52105R only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, F.	52 – 220 g/m²
Paper Weights		Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Okedia (SMB/FTPNCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartbeviceMonitor for Admin	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, F- 50 sheets/set (Letter)	52 – 220 g/m²
	$ \begin{array}{l} \mbox{Width: $2.52" - 8.5" (64 mm - 216 mm), \\ \mbox{Length: $5.52" - 35.43" (140 mm - 900 mm), \\ \mbox{Optional FFU(s), Standard Sizes: Letter, Legal, \\ \mbox{Executive, Half Letter, A4, A5, B5, B6, F/GL, \\ \mbox{Follscap, Folio; Envelopes: Com10, Monarch, \\ \mbox{C6, C5, DL. Custom Sizes: Width: $3.86" - 8.5" \\ \mbox{(98 mm - 216 mm), Legnth: $6.3" - 14.01" \\ \mbox{(160 mm - 356 mm) } \\ \mbox{Standard & Optional Tray(s): $14 - 59 lb. \\ \mbox{Bond/120 lb. index (52 - 220 g/m3) } \\ \mbox{Bypass Tray: $14 - 59 lb. Bond/120 lb. Index \\ \mbox{(52 - 220 g/m3) } When Duplexing: $16 - 44 lb. \\ \mbox{Bond/90 lb. index (60 - 163 g/m3) } \\ \mbox{Pain Paper, Recycled Paper, Middle Thick } \\ \end{array} $	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-OHedia (SMB/FTPNCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²)	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, Fi 50 sheets/set (Letter) 30 sheets/set (Letgal)	52 – 220 g/m² oolscap, Folio,
		Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication SOD; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 52105R only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, Fi 50 sheets/set (Letter) 30 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets;	52 – 220 g/m² oolscap, Folio,
Paper Types (all sources)	$ \begin{array}{l} \mbox{Width: $2.52" - 8.5" (64 mm - 216 mm), \\ \mbox{Length: $5.2" - 35.43" (140 mm - 900 mm), \\ \mbox{Optional PFU(s), Standard Sizes: Letter, Legal, \\ \mbox{Executive, Half Letter, A4, A5, B5, B6, F/GL, \\ \mbox{Follscap, Folio; Envelopes: Com10, Monarch, \\ \mbox{C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), \\ \mbox{Ug8 mm - 216 mm), } \\ \mbox{Standard & Optional Tray(s): 14 - 59 lb. \\ \mbox{Bond/120 lb. index (52 - 220 g/m)} \\ \mbox{Bypass Tray: 14 - 59 lb. \\ \mbox{Bond/120 lb. index (52 - 220 g/m)} \\ \mbox{Bypass Tray: 14 - 59 lb. \\ \mbox{Bond/120 lb. index (60 - 163 g/m^2) \\ \mbox{Plain Paper, Recycled Paper, Middle Thick \\ \mbox{Paper, Thick Paper, Thin Paper, Transparency, \\ \mbox{Letterhead, Label, Color, Preprinted, Envelopes} \end{array} $	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 8128 characters Up to 8128 characters + 5 pre-registered messages	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²)	(52 - 220 g/m ²) 24.7* x 25.0* x 8.7* (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, F- 50 sheets/set (Letter) 30 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²)	52 – 220 g/m² oolscap, Folio,
Paper Types (all sources)	$ \begin{array}{l} \mbox{Width:} 2.52" - 8.5" (64 mm - 216 mm), \\ \mbox{Length:} 5.52" - 35.43" (140 mm - 900 mm). \\ \mbox{Optional PFU(s), Standard Sizes: Letter, Legal, \\ \mbox{Executive, Half Letter, A4, A5, B5, B6, F/GL, \\ \mbox{Foolscap, Folio: Fnvelopes: Com10, Monarch, \\ \mbox{C6}, C5, DL. Custom Sizes: Width: 3.86" - 8.5" \\ \mbox{(98 mm - 216 mm), Length: 6.3" - 14.01" \\ \mbox{(160 mm - 356 mm)} \\ \mbox{Standard & Optional Tray(s): 14 - 59 lb. \\ \mbox{Bond/120 lb. Index (52 - 220 g/m3)} \\ Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (50 - 163 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (50 - 163 g/m3) \\ \mbox{Pairs, 14 - 50 lb. Bond/120 lb. Index (50 - 163 g/m3) \\ \mbox{Pairs, 14 - 50 lb. Bond/120 lb. Index (60 - 163 g/m3) \\ \mbox{Pairs, 18 lb. 200's, 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 52 lost 10 los$	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMITP authentication, POP before SMITP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight	(52 - 220 g/m ²) 24.7* x 25.0* x 8.7* (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 staples	52 – 220 g/m ² oolscap, Folio,
Paper Types (all sources)	$ \begin{array}{l} \mbox{Width: $2.52" - 8.5" (64 mm - 216 mm), \\ \mbox{Length: $5.2" - 35.43" (140 mm - 900 mm), \\ \mbox{Optional PFU(s), Standard Sizes: Letter, Legal, \\ \mbox{Executive, Half Letter, A4, A5, B5, B6, F/GL, \\ \mbox{Follscap, Folio; Envelopes: Com10, Monarch, \\ \mbox{C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" \\ \mbox{(98 mm - 216 mm), Length: 6.3" - 14.01" \\ \mbox{(160 mm - 356 mm)} \\ \mbox{Standard & Optional Tray(s): 14 - 59 lb. \\ \mbox{Bond/120 lb. Index (52 - 220 g/m²)} \\ \mbox{By as Tray: 14 - 59 lb. Bond/120 lb. Index \\ \mbox{(52 - 220 g/m²)} \\ Pain Paper, Point Paper, Middle Thick \\ \mbox{Paper, Thick Paper, Thin Paper, Transparency, \\ \mbox{Letterhead, Label, Color, Preprinted, Envelopes \\ \mbox{Ps 5200S: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52100S: 18.1" x 20" x 27" (460 mm x 518 mm) \\ \mbox{Based Standard Stan$	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Subject Input Subject Naintain Address	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 8128 characters Up to 8128 characters + 5 pre-registered messages	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 52105R only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, Fi 50 sheets/set (Letter) 30 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 staples 52105F only) 100 sheets	52 – 220 g/m² oolscap, Folio, 50 sheets: 4 se
Paper Types (all sources) Dimensions (WxDxH)	$ \begin{array}{l} \mbox{Width:} 2.52" - 8.5" (64 mm - 216 mm), \\ \mbox{Length:} 5.52" - 35.43" (140 mm - 900 mm). \\ \mbox{Optional PFU(s), Standard Sizes: Letter, Legal, \\ \mbox{Executive, Half Letter, A4, A5, B5, B6, F/GL, \\ \mbox{Foolscap, Folio: Fnvelopes: Com10, Monarch, \\ \mbox{C6}, C5, DL. Custom Sizes: Width: 3.86" - 8.5" \\ \mbox{(98 mm - 216 mm), Length: 6.3" - 14.01" \\ \mbox{(160 mm - 356 mm)} \\ \mbox{Standard & Optional Tray(s): 14 - 59 lb. \\ \mbox{Bond/120 lb. Index (52 - 220 g/m3)} \\ Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (50 - 163 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m3) \\ \mbox{Pairs, 14 - 59 lb. Bond/120 lb. Index (50 - 163 g/m3) \\ \mbox{Pairs, 14 - 50 lb. Bond/120 lb. Index (50 - 163 g/m3) \\ \mbox{Pairs, 14 - 50 lb. Bond/120 lb. Index (60 - 163 g/m3) \\ \mbox{Pairs, 18 lb. 200's, 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 55 2105: 18 l^* x 20' x x 27' (460 mm x 510 mm x s68 mm); 52 lost 10 los$	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMITP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmarDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 180 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmarDeviceMonitor for Admin 100	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplie Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, Fi 50 sheets/set (Letter) 30 sheets/set (Letgal) 2 sheets/set (Letgal) 2 sheets/set (Letgal) 2 sheets/set (Letgal) 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 staples 52105F only) 100 sheets 14 lb. Bond - 80 lb. Cover/120 ll	52 – 220 g/m² oolscap, Folio, 50 sheets: 4 se
Paper Types (all sources) Dimensions (WxDxH) Weight		Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Subject Input Subject Naintain Address	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication SOO; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 52105R only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, Fi 50 sheets/set (Letter) 30 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 staples 52105F only) 100 sheets	52 – 220 g/m² oolscap, Folio, 50 sheets: 4 se
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements	$ \begin{array}{l} \mbox{Width: $2.52" - 8.5" (64 mm - 216 mm), \\ \mbox{Length: $5.2" - 35.43" (140 mm - 900 mm), \\ \mbox{Optional FFU(s), Standard Sizes: Letter, Legal, \\ \mbox{Executive, Half Letter, A4, A5, B5, B6, F/GL, \\ \mbox{Follscap, Folio; Envelopes: Com10, Monarch, \\ \mbox{C6}, C5, DL. Custom Sizes: Width: 3.86" - 8.5" \\ \mbox{(98 mm - 216 mm), Legnth: 6.3" - 14.01" \\ \mbox{(160 mm - 356 mm)} \\ \mbox{Standard & Optional Tray(s): 14 - 59 lb. \\ \mbox{Bond/120 lb. Index (52 - 220 g/m?)} \\ \mbox{Bypass Tray: 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m?) \\ \mbox{Plain Paper, Recycled Paper, Middle Thick \\ \mbox{Paper, Thick Paper, Thin Paper, Transparency, \\ \mbox{Letterhead, Label, Color, Preprinted, Envelopes \\ \mbox{S46 mm}; SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 21" x 27" (460 mm x 686 mm); SP 52105F: 103.6 lb. \\ \mbox{(47 kg); SP 52105F: 116.8 lb. (53 kg) \\ \mbox{120 - 127V, 60Hz \\ \end{tabular}} \end{array}$	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication SOD; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position, Top parallel Letter, Legal, Executive, A4, B5, Fr 50 sheets/set (Letter) 30 sheets/set (Letgal) 2 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 staples 52105F only) 100 sheets 14 lb. Bond - 80 lb. Cover/120 ll (52 - 220 g/m ²)	52 – 220 g/m² oolscap, Folio, 50 sheets: 4 se
Paper Weights Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption	Width: 2.52" – 8.5" (64 mm – 216 mm), Length: 5.52" – 35.4" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folics; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" – 8.5" (98 mm – 216 mm), Length: 6.3" – 14.01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ²) Bypass Tray: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ²). When Duplexing: 16 – 44 lb. Bond/90 lb. Index (60 – 163 g/m ²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 – 127V, 60Hz Operating: SP 52005: 863 W, SP 52105F: 892 W, SP 52105F: 888 W	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Okedia (SMB/ETPNCP); Scan-to-URL, Scan-to-Media (USBS/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters Up to 80 characters Up to 80 characters Up to 80 characters Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 Up to 2000 MB Yes Standard – All models + Web Services (WSD)	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Const	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, Fr 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 5,000 staples *5210SF only) 100 sheets 14 lb. Bond - 80 lb. Cover/120 ll (52 - 220 g/m ²) umables	52 – 220 g/m² oolscap, Folio, 50 sheets: 4 se b. Index
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption	$ \begin{array}{l} \mbox{Width: $2.52" - 8.5" (64 mm - 216 mm), \\ \mbox{Length: $5.2" - 85.4" (140 mm - 900 mm), \\ \mbox{Optional PFU(s), Standard Sizes: Letter, Legal, \\ \mbox{Executive, Half Letter, A4, A5, B5, B6, F/GL, \\ \mbox{Follscap, Folio; Envelopes: Com10, Monarch, \\ \mbox{C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), \\ \mbox{Equations of the mm), } Executive, Half Letter, A4, A5, H1, B1, B1, B2, B1, B1, B1, B1, B2, B1, B1, B1, B1, B1, B1, B1, B1, B1, B1$	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Otedie (SMB/FTPNCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication S00; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2003R42, Scan	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplie Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 sheets 2510SF only) 100 sheets 14 lb. Bond - 80 lb. Cover/120 ll (52 - 220 g/m ²) umables Yield	52 – 220 g/m² oolscap, Folio, 50 sheets: 4 se
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI	Width: 2:52" = 55" (64 mm – 216 mm), Length: 5:52" = 55.4" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" – 8:5" (98 mm – 216 mm), Legnth: 6:3" – 14:01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ²) Bypass Tray: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ²). When Duplexing: 16 – 44 lb. Bond/90 lb. Index (60 – 163 g/m ²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105R: 18.1" x 24.2" x 27" (460 mm x 510 mm x 686 mm); SP 52105R: 103.6 lb. (47 kg); SP 52105R: 116.8 lb. (53 kg) 120 – 127V, 60Hz Operating: SP 52005: 83 W, SP 52105F: 892 W, SP 52015R: 85W Lefory Saver: 8 W or less UL60950-1, CAN/CSA C22.2 No.60950-1 (c-UL)	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMITP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplie Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Const Item Black AIO Print Cartridge SP 5200HA	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (f 14 position; Top parallel Letter, Legal, Executive, A4, B5, Fi 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 staples 52105F only) 100 sheets 14 lb. Bond - 80 lb. Cover/120 ll (52 - 220 g/m ²) umables Yield 25,000 pages*	52 – 220 g/m²) oolscap, Folio, 50 sheets: 4 se b. Index Part # 406683
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI Environmental Standard	Width: 2.52" – 8.5" (64 mm – 216 mm), Length: 5.52" – 35.4" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folics; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" – 8.5" (98 mm – 216 mm), Length: 6.3" – 14.01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ³) Bypass Tray: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ³) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 516 mm x 616 mm); SP 521051: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 521051: 18.1" x 20" x 27" (460 mm x 510 mm x 615 mm x 686 mm) SP 52005: 19.2 lb. (45 kg); SP 521051: 10.3 c lb. (47 kg); SP 521058: 63 W, SP 521051: 10.3 c lb. (147 kg); SP 521058: 63 W, SP 521051: 10.3 c lb. (147 kg); SP 521058: 63 W, SP 521051: 822 W, SP 521051: 858 W Energy Saver: 8 W or less UL60950-1, CAN/CSA C22.2 No.60950-1 (c-UL) FCC Part 15 Subpart B, IC ES-003	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication S00; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing; image Adjustmert: Brightness, Contrast, Threshold,	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplie Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Consul Item Black AIO Print Cartridge Staple Type T	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 14 - 59 lb. Bond/120 lb. Index (5 14 position; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 sheets 14 lb. Bond - 80 lb. Cover/120 ll (52 - 220 g/m ²) umables Yield 25,000 pages* 5,000/carton	52 – 220 g/m ² oolscap, Folio, 50 sheets: 4 se b. Index Part # 406683 415009
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume	Width: 2:52" - 85" (64 mm - 216 mm), Length: 5:52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm) Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m) Bypass Tray: 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²). When Duplexing: 16 - 44 lb. Bond/90 lb. Index (60 - 163 g/m ²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 - 127V, GOHz Operating: SP 52005: 863 W, SP 52105F: 892 W, SP 52005: 97 S005: 863 W, SP 52105F: 892 W, SP 52105F: 888 W Energy Saver: 8 W or less UL60950-1, CAWCSA C22.2 No.60950-1 (c-UL) FCC Part 15 Subpart B, IC ES-003 ENERGY STAR Tier 2, ECP	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMITP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Capartidge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Constitute Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 52105R only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 10 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 staples 52105F only) 100 sheets 14 lb. Bond - 80 lb. Cover/120 ll (52 - 220 g/m ²) umables Yield 25,000 pages* 5,000/carton 10,000/carton	52 – 220 g/m ² oolscap, Folio, 50 sheets: 4 se b. Index Part # 406683 415009 415010
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle	Width: 2.52" – 8.5" (64 mm – 216 mm), Length: 5.52" – 35.4" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folics; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" – 8.5" (98 mm – 216 mm), Length: 6.3" – 14.01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ³) Bypass Tray: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ³) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 516 mm x 616 mm); SP 521051: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 521051: 18.1" x 20" x 27" (460 mm x 510 mm x 615 mm x 686 mm) SP 52005: 19.2 lb. (45 kg); SP 521051: 10.3 c lb. (47 kg); SP 521058: 63 W, SP 521051: 10.3 c lb. (147 kg); SP 521058: 63 W, SP 521051: 10.3 c lb. (147 kg); SP 521058: 63 W, SP 521051: 822 W, SP 521051: 858 W Energy Saver: 8 W or less UL60950-1, CAN/CSA C22.2 No.60950-1 (c-UL) FCC Part 15 Subpart B, IC ES-003	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page TDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing, Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halflotne Pattern	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplic Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Const Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T Maintenance Kit SP 5200	(52 - 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 52105R only) 250 sheets Shift Sort, Stack, Staple 14 - 59 lb, Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, Fi 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Legal) 2 sheets: 33 sets; 30 sheets: 7 sets; 14 - 24 lb. Bond (52 - 90 g/m ²) 5,000 staples 52105F only) 100 sheets 14 lb. Bond - 80 lb. Cover/120 ll (52 - 220 g/m ²) Unables Yield 25,000 pages* 5,000/carton 10,000/carton 120,000 pages	52 – 220 g/m², 50 sheets: 4 se b. Index Part # 406683 415009 415009
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller	Width: 2:52" = 8.5" (64 mm – 216 mm), Length: 5:52" = 8.5" (64 mm – 216 mm), Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" – 8.5" (98 mm – 216 mm), Length: 6.3" – 14.01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m) Bypass Tay: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ²). When Duplexing: 16 – 44 lb. Bond/90 lb. Index (60 – 163 g/m ²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm) SP 52005: 9.21b. (15 kg); SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 – 127V, 60Hz Operating: SP 52105F: 18.5" x 20" SP 52005: 858 W Energy Saver: 8 W or less UL60950-1, CAN/CSA C22.2 No.60950-1 (c-UL) FCC Part 15 Subpart 8, LIC E5-003 ENERGY STAR Tier 2, ECP	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTPNCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMITP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filmg; Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplic Spacity (21 lb. Bond, 80g/m ²) Stack Capacity (21 lb. Bond, 80g/m ²) Staple Capacity (21 lb. Bond, 80g/m ²) Staple Capacity (21 lb. Bond, 80g/m ²) Staple Capacity Staple Capacity Capacity Paper Weight Supplies and Const Item Black AIO Print Cartridge SP 5200HA Staple Type T Maintenance Kit SP 5200 Includes 1 Fusing Unit, 1 Transfer	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 52105R only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb, Bond/120 lb, Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 30 sheets/set (Letter) 50 sheets/s	52 – 220 g/m², 50 sheets: 4 se b. Index Part # 406683 415009 415009
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU	Width: 2:52" - 85" (64 mm - 216 mm), Length: 5:52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm) Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m) Bypass Tray: 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²). When Duplexing: 16 - 44 lb. Bond/90 lb. Index (60 - 163 g/m ²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 - 127V, GOHz Operating: SP 52005: 863 W, SP 52105F: 892 W, SP 52005: 97 S005: 863 W, SP 52105F: 892 W, SP 52105F: 888 W Energy Saver: 8 W or less UL60950-1, CAWCSA C22.2 No.60950-1 (c-UL) FCC Part 15 Subpart B, IC ES-003 ENERGY STAR Tier 2, ECP	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Store Documents	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page TDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMITP authentication, POP before SMITP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing, Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplie Spacet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Consu- Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T Maintenance Kit SP 5200 Indudes 1 Fusing Unit, 1 Transfer *Declared yield values based on IS	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (E 14 – 59 lb. Bond/120 lb. Index (E 14 – 59 lb. Bond/120 lb. Index (E 14 – 29 lb. Bond (120 lb. Index (E 14 – 24 lb. Bond (52 – 90 g/m ²) 5,000 sheets 2510SF only) 100 sheets 2510SF only 100 sheets 2510SF only 100 sheets 10	52 – 220 g/m², 50 sheets: 4 se b. Index Part # 406683 415009 415009
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU Memory Hard Disk Drive*	Width: 2:52" - 85" (64 mm - 216 mm), Length: 5:52" - 35.43" (140 mm - 900 mm). Optional PFU(s). Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folios; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" - 8:5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm) Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²) Plain Paper, Pecyled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52005: 18.1" color, Preprinted, Envelopes SP 52005: 18.1" color, SP 52105F: 18.1" x 20" x 27" (460 mm x 615 mm x 686 mm); SP 52005: 18.1" color, SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 - 127V, 60Hz Operating: SP 52005: 863 W, SP 52105F: 1036 lb. (47 kg); SP 52105F: 654 W, SP 52105F: 858 W Energy Saver: 8 W or less UL60950-1, CAN/CSA C22.2 No.60950-1 (c-UL) FCC Part 15: Subpart 8, IC E5-003 ENERGY STAR Tier 2, ECP 5,500 - 15,000 total impressions/month Up to 200,000 total impressions/month S33 MHz 1 GB RAM standard/maximum 128 GB (standard)	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Spage per Documents Max. Pages per Document	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page TDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMITP authentication, POP before SMITP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Purtocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing, Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80gm?) Stack Capacity fer Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Consol Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T Maintenance Kit SP 5200 Includes 1 Fusing Unit, 1 Transfer "Declared yield values based on 15 images printed and other factors.	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (5 14 – 59 lb. Bond/120 lb. Index (5 14 j position; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 100 sheets 14 lb. Bond (52 – 90 g/m ²) 5,000 staples 2510SF only) 100 sheets 14 lb. Bond - 80 lb. Cover/120 ll (52 – 220 g/m ²) UITABLES Yield 25,000/carton 120,000 pages* 5,000/carton 120,000 pages Roller, 5 Feed Rollers and 5 Friction Pad: SC/IEC 19752. Actual yields may vary ba	52 – 220 g/m ² oolscap, Folio, 50 sheets: 4 se b. Index 406683 415009 415010 406686 5
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU Memory Hard Disk Drive*	Width: 2:52" - 85" (64 mm - 216 mm), Length: 5:52" - 35.43" (140 mm - 900 mm). Optional PFU(s). Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folios; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" - 8:5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm) Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²) Plain Paper, Pecyled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52005: 18.1" color, Preprinted, Envelopes SP 52005: 18.1" color, SP 52105F: 18.1" x 20" x 27" (460 mm x 615 mm x 686 mm); SP 52005: 18.1" color, SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 - 127V, 60Hz Operating: SP 52005: 863 W, SP 52105F: 1036 lb. (47 kg); SP 52105F: 654 W, SP 52105F: 858 W Energy Saver: 8 W or less UL60950-1, CAN/CSA C22.2 No.60950-1 (c-UL) FCC Part 15: Subpart 8, IC E5-003 ENERGY STAR Tier 2, ECP 5,500 - 15,000 total impressions/month Up to 200,000 total impressions/month S33 MHz 1 GB RAM standard/maximum 128 GB (standard)	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input Bubject Input Boby Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Stored Documents Max. Parket Server Total HDD Capacity Max. Stored Documents Max. Parket Server Fax Option Type SF	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication Stol; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista; 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing; Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text 128 GB (Shared with other functions) 3,000 documents 2,000 page	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80gm?) Stack Capacity fer Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Consol Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T Maintenance Kit SP 5200 Includes 1 Fusing Unit, 1 Transfer "Declared yield values based on 15 images printed and other factors.	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (5 1 position; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 100 sheets 5210SF only) 100 sheets 5210SF only) 100 sheets 5210SF only) 100 sheets 5210SF only) 100 sheets 14 lb. Bond – 80 lb. Cover/120 ll (52 – 220 g/m ²) Umables Yield 25,000 pages* 5,000/carton 10,000/carton 120,000 pages Roller, 5 Feed Rollers and 5 Friction Pads S0/IEC 19752. Actual yields may vary ba	52 – 220 g/m ² oolscap, Folio, 50 sheets: 4 se b. Index 406683 415009 415010 406686 5
Paper Types (all sources) Dimensions (WxDxH) Weight Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU Memory Hard Disk Drive*	Width: 2:52" = 55" (64 mm – 216 mm), Length: 5:52" = 35.43" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" – 8.5" (98 mm – 216 mm), Legnth: 6.3" – 14.01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m) Bypass Tray: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ²). When Duplexing: 16 – 44 lb. Bond/120 lb. Index (60 – 163 g/m ³) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 – 127V, GOHz Operating: SP 52005: 863 W, SP 52105F: 832 W, SP 52005: 99.2 b, (45 kg); SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 – 127V, GOHz Operating: SP 52005: 863 W, SP 52105F: 892 W, SP 52005: 91.500 total impressions/month UP to 200,000 total impressions/month UP to 200,000 total impressions/month 128 GB (standard) Overwrite (D0SS)	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Subject Input Subject Naintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Stored Documents Max. Addres per Document Fax Option Type SF (Standard for SP 52105F, O	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page TDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTPNCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, PCP before SMTP authentication Sol; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2, Scan Modes: Standard, Photo, OCR, Filing; Image Adjustmert: Enghtness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text 128 GB (Shared with other functions) 3,000 documents 2,000 pages 25200 – Part # 406594 ptional for SP 52005/ 5210SP)	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplie Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Consti Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T Maintenance Kit SP 5200 Includes 1 Fusing Unit, 1 Transfer *Declared yield values based on IS images printed and other factors.	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (9 14 – 59 lb. Bond/120 lb. Index (9 14 – 24 lb. Bond (52 – 90 g/m ²) 30 sheets/set (Letter) 30 sheets/set (Letter) 10 obsheets 14 – 24 lb. Bond (52 – 90 g/m ²) 5,000 staples 14 – 18 Bond – 80 lb. Cover/120 ll (52 – 220 g/m ²) umables Yield 25,000 pages* 5,000/carton 10,000/carton 120,000 pages Roller, 5 Feed Rollers and 5 Friction Pad: SO/FSP 5210SR ships with one starter All unsumables ship at full yield.	52 – 220 g/m ² oolscap, Folio, 50 sheets: 4 se b. Index Part # 406683 415009 415010 406686 5 sed on types of 0 cartridge
Paper Types (all sources) Dimensions (WxDxH) Weight Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU Memory Hard Disk Drive*	 Width: 2:52" - 85" (64 mm - 216 mm), Length: 5:52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio: Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" - 8:5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm) Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m²) Bypass Tray: 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Staff and Staf	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Boly Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Stored Documents Max. Pages per Document Max. Address SI Scantary Max. Stored Documents Max. Pages per Documents Max. Pages per Documents Max. Pages per SI Scantary Stores SI Scant	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USBX5D Card) Standard; Authorization: SMITP authentication, POP before SMITP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Autocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing; Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text 128 GB (Shared with other functions) 3,000 documents 2,000 pages 25200 – Part # 406594 ptional for SP 52005/ 52105R) Super G3 Transceiver	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Capacity (21 lb. Bond, 80g/m²) Stack Capacity after Stapling Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Staple Cartridge Sp Staple Staple Type T Maintenance Kit SP 5200 Indudes 1 Fusing Unit, 1 Transfer * Declared yield values based on IS images printed and other factors. The Ricch Africio SP 5200/SP 5211 then Construction SP 5200 Staple Sp 200/SP 5211 Staple Sp 200 Sp 201 Sp 200 Indudes 1 Fusing Unit, 1 Transfer	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (6 14 – 59 lb. Bond/120 lb. Index (7 10 osition; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 10 osheets 7510SF only) 100 sheets 7510SF only 100 optics 7510SF only 100 optics 7510SF only 101 Sheets 7510SF only 100 optics 7510SF only 102 Sheets 7510SF only 103 Sheets 7510SF only 104 Sheets 7510SF only 105 Sheets 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF	52 – 220 g/m ² oolscap, Folio, 50 sheets: 4 se b. Index Part # 406683 415009 415010 406686 5 sed on types of 0 cartridge
Paper Types (all sources) Dimensions (WxDxH) Weight Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU Memory Hard Disk Drive*	Width: 2:52" – 35' (64 mm – 216 mm), Length: 5:52" – 35.43" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" – 8.5" (98 mm – 216 mm), Length: 6.3" – 14.01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m) Bypass Tay: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m ²). When Duplexing: 16 – 44 lb. Bond/90 lb. Index (60 – 163 g/m ²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 508 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm) SP 52005: 9.2 lb. (45 kg); SP 52105F: 103.6 lb. (47 kg); SP 52105F: 116.8 lb. (53 kg) 120 – 127V, G0Hz Operating: SP 52105F: 162-603 ENERGY STAR Tier 2, ECP 5,500 – 15,000 total impressions/month Up to 200,000 total impressions/month S13 MHz 1 GB RAM standard/maximum 128 GB (standard) 3 overvite (DOSS) Standard: 10/1008ase-TX Ethernet, USB 2.0 Hi Speed Type B (for direct computer connection), Dual USB 2.0. Hots (Jb. 182 AU).	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Stored Documents Max. Pages per Document Fax Option Type SI (Standard for SP 5210SF, O Type Circuit Number of Lines	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page TDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTPNCP); Scan-to-URL, Scan-to-Media (USBS/D Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7; Server 2003/RY2, Scan Modes: Standard, Photo, OCR, Filing; Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halflotne Pattern Date, Page Number, Text 128 GB (Shared with other functions) 3,000 documents 2,000 pages P5200 – Part # 406594 ptional for SP 52005/ 52105R) Super G3 Transceiver PSTN, PRX	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplie Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Consti Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T Maintenance Kit SP 5200 Includes 1 Fusing Unit, 1 Transfer *Declared yield values based on IS images printed and other factors.	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (6 14 – 59 lb. Bond/120 lb. Index (7 10 osition; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 10 osheets 7510SF only) 100 sheets 7510SF only 100 optics 7510SF only 100 optics 7510SF only 101 Sheets 7510SF only 100 optics 7510SF only 102 Sheets 7510SF only 103 Sheets 7510SF only 104 Sheets 7510SF only 105 Sheets 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF 7510SF	52 – 220 g/m², 50 sheets: 4 se 50 sheets: 4 se b. Index Part # 406683 415010 406686 5 seed on types of 0 cartridge
Paper Types (all sources) Dimensions (WxDxH) Weight Power Requirements Power Consumption Safety Regulations EMI	 Width: 2.52" – 8.5" (64 mm – 216 mm), Length: 5.52" – 8.5.4" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folics; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" – 8.5" (98 mm – 216 mm), Length: 6.3" – 14.01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m³) Bypass Tray: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m³) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 510 mm x 516 mm); SP 521051: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 521051: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 521051: 10.3 (b. (47 kg); SP 521058: 63 W, SP 521051: 10.3 (b. (47 kg); SP 521058: 63 W, SP 521051: 10.3 (b. (47 kg); SP 521058: 63 W, SP 521051: 10.3 (b. (53 KMHz 1 GB RAM standard/maximum 128 GB (standard) Soverwrite (DOS) Standard: 10/100Base-TX Ethernet, USB 2.0 Hi Speed Type B (for direct computer connection), Dual USB 2.0 Host Interfaces Type A (for external device connection), Front USB 2.0 (Stal) 	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Stored Documents Max. Pages per Document Fax Option Type SI (Standard for SP 5210SF, O Type Circuit Number of Lines Compatibility	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication Stol; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 to 2 000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing; Image Adjustmert: Brightnes, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text 128 GB (Shared with other functions) 3,000 documents 2,000 pages P5200 – Part # 406594 ptional for SP 52005/ 5210SR) Super G3 Transceiver PSTN, PEX.	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Capacity (21 lb. Bond, 80g/m²) Stack Capacity after Stapling Staple Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Staple Cartridge Sp Staple Cartridge Sp Staple Staple Type T Refill Staple Type T Maintenance Kit SP 5200 Indudes 1 Fusing Unit, 1 Transfer *Declared yield values based on IS images printed and other factors. The Ricch Africis SP 5200/SP 5211 other con For maximum performance and yie	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (6 14 – 59 lb. Bond/120 lb. Index (7 10 osition; Top parallel Letter, Legal, Executive, A4, B5, F 50 sheets/set (Letter) 10 sheets/set (Letter)	52 – 220 g/m²) oolscap, Folio, 50 sheets: 4 se b. Index Part # 406683 415009 415010 406686 5 sed on types of 0 cartridge
Paper Types (all sources) Dimensions (WxDxH) Weight Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU Memory Hard Disk Drive*	 Width: 2:52" - 8:5" (64 mm - 216 mm), Length: 5:52" - 8:5.4" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" - 8:5" (98 mm - 216 mm), Legnth: 6:3" - 14:01" (160 mm - 356 mm) Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m²) Bypass Tray: 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m²). When Duplexing: 16 - 44 lb. Bond/90 lb. Index (60 - 163 g/m²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105R: 103.6 lb. (47 kg); SP 52105R: 116.8 lb. (53 kg) 120 - 127V, 60Hz Operating: SP 52005: 863 W, SP 52105F: 892 W, SP 52005: 99.2 lb. (45 kg); SP 52105F: 103.6 lb. (47 kg); SP 52105R: 116.8 lb. (53 kg) 120 - 127V, 60Hz Operating: SP 52005: 18.1" x 20" x 27", 1460 Styber 15 Subpart 8, IC ES-003 ENERGY STAR Tier 2, ECP Stodo total impressions/month Up to 200,000 total impressions/month Up to 200,000 total impressions/month 128 GB (standard) Otwerkit (D053); Standard: 10/1008ase-TX Ethernet, USB 2.0 Hi Spaed Type B (for direct computer connection), Dual USB 2.0 Host Interfaces Type A (for external device connection), Front USB 2.0 SD Card Slot Interface (for Scan T0Print From portable media). Optional: Gigabit Ethernet (10008ase-TX Ethernet (10008ase-TX Ethernet), SD Card Slot 	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Stored Documents Max. Pages per Document Fax Option Type SI (Standard for SP 5210SF, O Type Circuit Number of Lines	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page TDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTPNCP); Scan-to-URL, Scan-to-Media (USBS/D Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; AutoreviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003/Vista, 7: Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing; Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text 128 GB (Shared with other functions) 3,000 documents 2,000 pages PS200 – Part # 406594 Pitoinal for SP 52005/ S2105R) Super G3 Transceiver PSTN, PBX 1 TU-T, Group 3 200 x 100, 200 x 200, 200 x 400, 400 x 400 (for	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80gm?) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Supplies and Consul Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T Maintenance Kit SP 5200 Includes 1 Fusing Unit, 1 Transfer * Declared yield values based on IS images printed and other factors. The Ricoh Africio SP 52005/SP 521 yielding 6,000 pages. All other con for maximum performance and yie Specifications subject to change w Warranty The Ricoh Africio SP 52005/SP	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (5 14 – 59 lb. Bond/120 lb. Index (5 14 – 59 lb. Bond/120 lb. Index (5 10 sosteets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 100 sheets 14 lb. Bond (52 – 90 g/m ²) 5,000 staples 2510SF only) 100 sheets 14 lb. Bond (52 – 90 g/m ²) 210SF only) 100 sheets 14 lb. Bond – 80 lb. Cover/120 ll (52 – 220 g/m ²) UITABLES Yield 25,000 pages* 5,000/carton 120,000 pages Roller, 5 Feed Rollers and 5 Friction Pad: SO/ICC 19752. Actual yields may vary ba 105/SP 5210SR ships with one starter AI misumables ship at full yield. eld, we recommend using genuine Ricoh without notice.	52 – 220 g/m²) oolscap, Folio, 50 sheets: 4 se b. Index 406683 415009 415010 406686 5 sed on types of 0 cartridge parts and supplie
Paper Types (all sources) Dimensions (WxDxH) Weight Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU Memory Hard Disk Drive* *Includes HDD Encryption Unit and Interfaces	 Width: 2:52" – 8:5" (64 mm – 216 mm), Length: 5:52" – 35:43" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" – 8:5" (98 mm – 216 mm), Legnth: 6:3" – 14:01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m²) Bypass Tray: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m²). When Duplexing: 16 – 44 lb. Bond/20 lb. Index (60 – 163 g/m³) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes Sp 2005: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 52105F: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 5210SR: 18.1" x 24.2" x 27" (460 mm x 615 mm x 686 mm) SP 52005: 99.2 lb. (45 ks); SP 52105F: 103.6 lb. (47 kg); SP 52105R: 116.8 lb. (53 kg) 120 – 127V, 60Hz Operating: SP 52005: 863 W, SP 5210SF: 822 W, SP 5200; SP 5000; SD 5; 18.1" k Sp 52105F: 18.1" k Sp 52105F: 18.1" k Sp 52105F: 18.1" S2 Sp 52105F: 18.1" S2 Sp 52105F: 18.1" S2 Sp 52105F: 15.3 lb. 16.4 Kg); SP 52105F: 88 W Energy Saver: 8 W or less UL60950-1; CANUCSA C22.2 No.60950-1 (c-UL) FCC Part 15 Subpart B, IC ES-003 ENRERGY STAR Tier 2, ECP Sp 500 - 15,00 total impressions/month Up to 200,000 total impressions/month 126 B (standard) Overwrite (D0SS) Standard: 10/100Base-TX Ethernet, USB 2.0 Hi Speed Type B (for direct computer connection), Dual USB 2.0 Host Interfaces Type A (for external device connection), Front USB 2.0/SD Card Slot Interface (for Scan T0P/int From portable media). Optional: Gigabit Ethernet (1000Base-7D, IEEE 802.114a/ Wireless, Bluetooth PCT L5 e, PCL 6, KPS, Adobe PostSCript3[®], PD	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Maintain Address Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Stored Documents Max. Pages per Document Fax Option Type SI (Standard for SP 5210SF, Of Type Circuit Number of Lines Compatibility Resolution (dpi) Modem Speed	Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page TDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTPNCP); Scan-to-URL, Scan-to-Media (USBS/D Card) Standard; Authorization: SMTP authentication, PCP before SMTP authentication Sol; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 128 characters Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 500 Up to 2000 MB Yes Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2003/R2, Scan Modes: Standard, Photo, OCR, Filing; Image Adjustmert: Enghtness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text 128 GB (Shared with other functions) 3,000 documents 2,000 pages 25200 – Part # 406594 Prional for SP 52005/ 5210SPI Super G3 Transceiver PSTN, PBX 1 TU-T, Group 3 200 x 100, 200 x 200, 200 x 400, 400 x 400 (for Internet & IP Fax, requires optional SAF memory) 33,600 bpc - 2,400 bps Wixdu Fallback	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Staplie Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m ²) Stack Capacity after Stapling Staple Paper Weight Staple Capacity after Stapling Staple Paper Weight Staple Capacity Paper Weight Supplies and Const Item Black AIO Print Cartridge SP 5200HA Staple Type T Refill Staple Type T Maintenance Kit SP 5200 Includes 1 Fusing Unit, 1 Transfer "Declared yield values based on IS images printed and other factors. The Ricoh Africio SP 52005/SP 521 yielding 6,000 pages. All other co For maximum performance and yie Specifications subject to change w Warranty The Ricoh Africio SP 52005/SP 52005/SP	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (6 14 – 59 lb. Bond/120 lb. Index (7 50 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 10 sheets 14 – 24 lb. Bond (52 – 90 g/m ²) 5,000 staples *22105F only) 100 sheets 14 lb. Bond – 80 lb. Cover/120 ll (52 – 220 g/m ²) umables Yield 25,000/carton 10,000/carton 10,000/carton 10,000/carton 120,000 pages Roller, 5 Feed Rollers and 5 Friction Pade SO/EC 19752. Actual yields may vary ba 05F/SP 5210SR ships with one starter AI nsumables ship at full yield. eld, we recommend using genuine Ricoh without notice.	52 – 220 g/m²) oolscap, Folio, 50 sheets: 4 se b. Index Part # 406683 415010 415010 406686 5 sed on types of 0 cartridge parts and supplie anty against nsumables are
Paper Types (all sources) Dimensions (WxDxH) Weight Power Consumption Safety Regulations EMI Environmental Standard Average Monthly Volume Maximum Duty Cycle Print Controller CPU Memory Hard Disk Drive* *Includes HDD Encryption Unit and Interfaces	 Width: 2:52" – 8:5" (64 mm – 216 mm), Length: 5:52" – 35:43" (140 mm – 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B5, F/GL, Foolscap, Folio: Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3:86" – 8:5" (98 mm – 216 mm), Length: 6.3" – 14:01" (160 mm – 356 mm) Standard & Optional Tray(s): 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m²) Bypass Tray: 14 – 59 lb. Bond/120 lb. Index (52 – 220 g/m²) Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes SP 52005: 18.1" x 20" x 27" (460 mm × 510 mm x 686 mm); SP 52105: 18.1" x 20" x 27" (460 mm × 510 mm x 686 mm); SP 52005: 18.1" x 20" s 27" (460 mm x 510 mm x 686 mm); SP 52005: 18.1" x 20" s 27" (460 mm x 510 mm x 686 mm); SP 52005: 863 W, SP 52105F: 18.1" x 24.2" x 27" (460 mm x 615 mm x 686 mm); SP 52005: 863 W, SP 52105F: 18.1" x 24.2" x 27" (460 mm x 615 mm); SP 52005: 863 W, SP 52105F: 18.1" x 24.2" x 27" (460 mm x 615 mm); SP 52005: 863 W, SP 52105F: 892 W, SP 52005: 863 W, SP 52105F: 892 W, SP 52005: 992 Lb. (45 kg); SP 52105F: 892 W, SP 52005: 992 Lb. (45 kg); SP 52105F: 892 W, SP 52005: 863 W, SP 52105F: 103.6 lb. (47 kg); SP 52105; 863 W, SP 52105F: 892 W, SP 52005: 878 W Energy Saver: 8 W or less UL60950-1, CAN/CSA C22.2 No 60950-1 (c-UL) FCC Part 15 Subpart B, IC ES-003 ENREGY STAR Tier 2, ECP 5,500 – 15,000 total impressions/month Up to 200,000 total impressions/month 	Image Rotation SADF/Batch Mode Supported File Formats Scan-To Modes Scan-to-Email Max. Addresses/Send LDAP Search Maintain E-mail Address E-mail Attachments Input File Name Input Subject Input Body Message Scan-to-Folder Max. Addresses/Send Max. Folders/Send Max. Folders/Send Max. Addresses/Send File Attachment Size Input File Name Network TWAIN Scanning Endorse Document Server Total HDD Capacity Max. Stored Documents Max. Page per Document Max. Page per Document Fax Option Type SF (Standard for SP 5210SF, O Type Circuit Number of Lines Compatibility Resolution (dpi)	Supported Supported Single/Multi Page TIFF, Single Page JPEG, Single/ Multi Page PDF, High Compression PDF Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication Sol; Attention: To, cc, bcc Supported Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction Yes Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 80 characters + 5 pre-registered messages Standard; Protocol Support: SMB, FTP, NCP Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100 Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard – All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Halftone Pattern Date, Page Number, Text 128 GB (Shared with other functions) 3,000 documents 2,000 page SP200 – Part # 406594 ptional for SP 52005 (S210SR) Super G3 Transceiver PSTN, PBX 1 (TU-T, Group 3 200 x 100, 200 x 200, 200 x 400, 400 x 400 (for Internet & IP Fax, requires optional SAF memory)	Dimensions (WxDxH) Weight Internal Finisher (Standard Tray Capacity Modes Paper Weight Stapling Staple Capacity (21 lb. Bond, 80g/m²) Stack Capacity after Stapling Staple Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP Tray Capacity Paper Weight Staple Cartridge SP S200HA Staple Type T Refill Staple Type T Maintenance Kit SP S200 Indudes 1 Fusing Unit, 1 Transfer * Declared yield values based on IS images printed and other factors. The Ricch Aficio SP S200/SP S21 yielding 6,000 pages. All other co For maximum performance and yie Specifications subject to change w Warranty The Ricch Aficio SP S200S/SP S21 Under Sp S200S/SP S21 Specifications subject to change w	(52 – 220 g/m ²) 24.7" x 25.0" x 8.7" (627 mm x 220 mm) (including casters) 26.5 lb (12.0 kg) for SP 5210SR only) 250 sheets Shift Sort, Stack, Staple 14 – 59 lb. Bond/120 lb. Index (5 14 – 59 lb. Bond/120 lb. Index (5 14 – 59 lb. Bond/120 lb. Index (5 10 sosteets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 30 sheets/set (Letter) 100 sheets 14 lb. Bond (52 – 90 g/m ²) 5,000 staples 2510SF only) 100 sheets 14 lb. Bond (52 – 90 g/m ²) 210SF only) 100 sheets 14 lb. Bond – 80 lb. Cover/120 ll (52 – 220 g/m ²) UITABLES Yield 25,000 pages* 5,000/carton 120,000 pages Roller, 5 Feed Rollers and 5 Friction Pad: SO/ICC 19752. Actual yields may vary ba 105/SP 5210SR ships with one starter AI misumables ship at full yield. eld, we recommend using genuine Ricoh without notice.	52 – 220 g/m ²) oolscap, Folio, 50 sheets: 4 se b. Index Part # 406683 415009 415010 406686 seed on types of O cartridge parts and supplie anty against nsumables are ase or until

RICOH www.ricoh-usa.com

Ricoh Americas Corporation, Five Dedrick Place, West Caldwell, NJ 07006 Ricoh[®] and the Ricoh Logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and flactors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them. Descent and the second services are as effecting performed to the service services are as effecting performance.

Adobe:PDF Adobe: PostScrip

Java Wi Ei