# SCX-3405W Multi-Function Printer

# There's still room in your shopping cart for a professional image.



## Our Most Compact and Efficient Multi-Function Printer

It's our smallest, most compact MFP. And it'll provide you with nothing short of a big, professional image. With a footprint of just 15.3" W x 10.8" D x 9.8" H, the Samsung SCX-3405W print/copy/scan MFP prints up to 10,000 sharp, professional pages a month. It's wireless, so you can set it up virtually anywhere in your home or small office. Smart features like one-touch wireless setup save you time, while an ECO button prints two-sided copies more efficiently, to save you paper and toner. And of course, the SCX-3405W comes standard with the exceptional durability and reliability that Samsung is known for. The Samsung SCX-3405W. **Business. Innovated**.



#### Quick 21 ppm Print Speeds

Print speeds of up to 21 ppm and first print out time of as fast as 8.5 seconds means you'll spend more time printing and less time waiting.

#### Compact and Quiet

The SCX-3405W is our most compact MFP yet. With a footprint of just 15.3" W x 10.8" D x 9.8" H, it'll fit comfortably on a desk or bookshelf. And at sound levels of less than S0dBA, you won't notice it's there until you need it.



## Wireless Printing

Wireless printing means you can place the compact SCX-3405W anywhere in your office. It also makes sharing the MFP with multiple computers simple.



#### **One-Touch Wireless Setup**

The SCX-3405W's One-Touch WPS button (Wi-Fi Protected Setup) lets you connect quickly and easily. Press the WPS button on your router and the WPS button on your SCX-3405W, and your MFP automatically configures and connects to your wireless network.



With a monthly duty cycle of 10,000 pages, you can count on your Samsung printer to be there for you when you need it.



#### ECO Button

The one-touch ECO button allows you to customize your output to save toner and paper.



# SCX-3405W Multi-Function Printer



## KEY SPECIFICATIONS For complete product specifications, visit samsung.com/printer

Indum         Indum <thindum<tr>         Indum         Indum         <thi< th=""><th>Product</th><th colspan="2">Model Number</th><th>SCX-3405W</th></thi<></thindum<tr>	Product	Model Number		SCX-3405W
Pred         Special Mamij Lugaganji           Braduki         Up to 21 poni iu Lellar           Braduki         SPL Genunga Pintri Lugaganji           Braduki         Up to 120 x 1200 dellave outga           First Page Dui Time         Less Tura SSe sec fram Rendy           Degre Pintri         Less Tura SSe sec fram Rendy           Degre Pintri         Katada ta si associa           Pred Cogy Dui Time         Katada ta 14 associa           Zoon Fasty         Katada ta 14 associa           Zoon Fasty         D Date Cogy           Madi Cogy         Ta 99           Cogy Fasty         D Date Cogy           Residue         D Date Cogy           Enacad         400 x 400 dpl           Mada Vagit         100 dects           Variation Same         Y X = - S Y X		Function		3-in-1 Printer
Image:		Value Added Features		WPS (Wireless Protected Setup), EC0 button, Easy Printer Manager
Readiant         log 120 Control deficiency of the Control of the Control of C	Print Speed (Mono)			Up to 21 ppm in Letter
Part Rep U T Image         Less tan Base from Ready           Japine Pierry         Kask and Supdamo           Optige Support         Kask and Support           A base and Support         Sale Support           A base and Support         D Sup Colory           A base and Support         D Support           A base and Support         Support           A base france Asset         Support           A bas		Emulation		SPL (Samsung Printer Language)
Idada         Idada         Idada           Grop Size         Kask and vacuum         Kask and vacuum           Fire Copy IIII         Kask and vacuum         Kask and vacuum           Inter Copy IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII		Resolution		Up to 1200 x 1200 dpi effective output
Cory         Cory Seed         Us b 21 prin in Letter           Fits Cory: 0T:::::::::::::::::::::::::::::::::		First Page Out Time		Less than 8.5 sec from Ready
First Gay     Inst Gay     A fasta at 4 seconds       Zom Ray:     2% to 40%       Zom Ray:     199       Add Gay:     10 Gad       Result:     0 God Gay       Result:     0 God Gay       Result:     0 God Gay       Result:     10 Go		Duplex Print		Manual with guidance
kor	Сору	py Copy Speed		Up to 21 ppm in Letter
Multi Qay         Ise9           Cory Features         1-94           Cory Features         0 Cory Cory           Resoluti O         Qory Features           Resoluti O         Qory Features           Resoluti O         Qory Features           Resoluti O         Qory Cory           Note Cory         Single Cory           Not		First Copy Out Time		As fast as 14 seconds
Image: Part of the second se		Zoom Range		25% to 400%
Sem         Sem Method         Color OS           Peolution         Optical         600 x 600 dpi           Enhanced         4800 x 600 dpi           Network Sam         4800 x 600 dpi           Vertion Capacity         Yes           Output Capacity         Yes           Output Capacity         100 sheets face down           Output Capacity         100 sheets face down           Media Nage         3" x 5" = 8.5" x 14"           Media Nage         3" x 5" = 8.5" x 14"           Media Nage         16-4 3 bps           Media Nage         16-4 4 Bbg		Multi Copy		1-99
Pediation         Pediation         Pediation         Pediation         Pediation           Networks         Vectors         Vectors         Vectors           Performance         Pediation         Vectors         Vectors           Performance         Pediation         Vectors         Vectors           Performance         Pediation         Vectors         Vectors           Performance         Pediation         Vectors         Vectors           Pediation         Vectors		Copy Features		ID Card Copy
Interface         4800 x4800 dpi           Network Scar         Ves           Output Capacity         150 sheets           Output Capacity         100 sheets face down           Media Size         3" x 5" - 8.5" x 14"           Media Size         3" x 5" - 8.5" x 14"           Media Size         53" x 5" - 8.5" x 14"           Media Size         16 - 4.3 lbs.           Add Rightspre         Fearboard           Media Veight         16 - 4.3 lbs.           ADF Capacity         NA Plathed only           Memory         435 Miz           Memory         64 M8           OsconsatUli         Her Size Advance (State (State Advance (State	Scan	Scan Method		Color CIS
Netwirk Sam         Yes           Paper Handmin         Fund Capacity         150 sheets           Output Capacity         100 sheets face down           Media Size         00 sheets face down           Media Size         37 x5 = 8.5 x 14*           Media Weigre         9 in Envelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Yeigre         9 in Envelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Yeigre         9 in Envelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Yeigre         9 in Envelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Yeigre         9 in Envelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Yeigre         9 in Envelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Yeigre         4 in A Flatae onlow           Internace         4 Sign Merity           Noneson         V Envelope, Marce Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Methy         Internace         1 internace           Noneson         V Envelope, Marce Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Marce Stock, Thick, Thin, Sonetand Tope, Stock, Thick, Thin, Cotton, Color, Prepr		Resolution	Optical	600 x 600 dpi
Paper Handling         Input Capaci/ Output Capaci/ Media Star         150 sheets face down           Media Star         01 sheets face down           Media Star         3" x 5" – 8.5" x 14"           Media Star         9 a'r, 5" – 8.5" x 14"           Media Varper         Pain, Erwelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Varper         Pain, Erwelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Varper         16 - 43 lbs.           ADF Capaci/ Media Varper         16 - 43 lbs.           Noncossor         64 MB           Noncossor         64 MB           Os Compatibility         Hi-Speed USB 2.0, Wrietes 802.11 br/gh, Wi-Fi Direct           Interface         Hi-Speed USB 2.0, Wrietes 802.11 br/gh, Wi-Fi Direct           Nonthin J Curret         10.000 pages           Other Varper         10.000 pages           Interface         15.3" x 10.8" x 9.8"           Vendar         14.7 Ibs.           Stander Toer:         16 x 2 Line LCD (w/o backlight)           Stander J Ower         Less than 310W           Stander J Ower         Less than 310W           Stander J Ower, Average Cartridge Yield 1.500 standard pages (MLT-D101S)           Stander J Ower, Average Cartridge Yield 10.500 stan			Enhanced	4800 x 4800 dpi
Output Capacity     100 sheets face down       Media Size:     3" x 5" - 8.5" x 14"       Media Type:     Pian, Envelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive       Media Weight:     16 - 43 lbs.       ADF Capacity:     NA F Rathed only       Kennerol     Processor:       Memory:     433 MHz       Consume     Generol       Memory:     433 MHz       Consume     Generol       Memory:     433 MHz       Memory:     433 MHz       Memory:     433 MHz       Consume     Generol       Memory:     433 MHz       Memory:     433 MHz       Memory:     44 MB       Discipacity:     Windby Consume Consume       Memory:     Windby Consume Consume       Memory:     Windby Consume       Memory:     Windby Consume       Monthy Duty:     In 0.000 pages       Dimensions:     V > x H       10:2 No Lei LeCD (w/o backlight)       Less than 30 GM       Less than 310W       Consume     Less than 310W       Sendord Consume     Less than 310W <tr< th=""><th></th><th colspan="2">Network Scan</th><th>Yes</th></tr<>		Network Scan		Yes
Media Size5° x 5° + 8.5° x 14°Media Type:Pain, Envelope, Labels, Carl Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, ArchiveMedia Weight:16 + 43 lbs.ADF Capacity:NA Flatbed only)ProcessorProcessor433 MHzMemory:64 MBOS Compatibility:Nindows 7/Msta/P/2008/2002/2000, Various Linux, Unix, Mac 10.4 and upNoise Level:Hi-Speed USB 2.0, Wireless 802.11 br/g/n, Wi-Fi DirectNoise Level:Hi-Speed USB 2.0, Wireless 802.11 br/g/n, Wi-Fi DirectNoise Level:Less than 50 dBA (Printing and Copying), Less than 26 dBA StandbyMonthly Duty:I. 0.000 pagesDimensions:1. 0.30° agesDimensions:1. 0.30° agesDimensions:I. 6x 2 Line LCD (w/o backlight)Prover Consumble:Average OperationStandby Toom:Standby 1. 0.6%Standby Toom:Standby 1. 0.6%Less than 310WConsumble:Standby 1. 0.6%Standby Toom:Standby 1. 0.6%	Paper Handling Input Capa			150 sheets
Media Type         Piakin Envelope, Labels, Card Stock, Thick, Thin, Cotton, Color, Preprinted, Recycled, Bond, Archive           Media Weijk         16 - 43 lbs.           ADF Capacity         NA (Flatted only)           ADF Capacity         VI (Flatted only)           Memory         433 MHz           Constant         64 GM           OS Compatibility         64 MB           Noise Levity         Hi-Speed USB 2:0, Wireless 802:11 big/n, Wi-Fi Direct           Noise Levity         Hi-Speed USB 2:0, Wireless 802:11 big/n, Wi-Fi Direct           Noise Levity         10:00 pages           Noith Work         15.3" x 10.8" x 9.8"           Noise Levity         15.3" x 10.8" x 9.8"           Noise Levity         16.3 Lane LCD (wire backlight)           Levity         16.3 Lane LCD (wire backlight)           Levity         16.3 Lane LCD (wire backlight)           Levity         16.3 Lane LCD (wire back		Output Capacity		100 sheets face down
Media Weight:       16 - 43 lbs.         APE Capacity:       VA (Fatbed only)         General       Processr       433 MFz         Memory:       64 MB         O Compatibility:       64 MB         Interface:       Vindows 7/Vista/XP/2008/2002/2000, Various Linux, Unix, Mac 10.4 and up         Interface:       Hi-Speed USB 2.0, Wireless 802.11 b/gh, Wi-Fi Direct         Noise Leve!       Less than 50 dBA (Printing and Copying), Less than 26 dBA Standby         Monthy:       15.3'x 10.8'x 9.8''         Interface:       16.5'x 10.8'x 9.8''         Veight:       16.3'x 10.8'x 9.8''         Neage Operation       16 x 2 Line LCD (w/o backlight)         Power       Alerage Operation         Power       Alerage Operation         Standby Mode       Less than 300W         Consumable       Tome::		Media Size		3" x 5" - 8.5" x 14"
ADF Capacity         N/A (Flatbed only)           Focessor         433 MHz           Memory         64 MB           OS Compatibility         64 MB           Interface         Hi-Speed USB 2.0, Wireless 802.11 b/g/n, Wi-Fl Direct           Noise Level         Less than 50 dBA (Printing and Copying), Less than 26 dBA Standby           Monthy Duty - V         10,000 pages           Dimensions // W and y a V A B // N La X + S AB           Verigity         15.3" x 10.8" x 9.8"           Verigity         16.5 2 Line LCD (w/o backlight)           Power         Seen Mode           Verigity         Less than 310W           Seen Mode         Less than 310W           Seen Mode         Less than 310W           Seandor More // Nervage Cartridge Yield 1,500 standard pages (MLT-D101S)           Standard Toner: Average Cartridge Yield 1,500 standard pages (MLT-D101S)		Media Type		Plain, Envelope, Labels, Card Stock, Thick, Thin, Colton, Color, Preprinted, Recycled, Bond, Archive
General         Processor         433 MHz           Memory         64 MB           OS Compatibility         Windows 7/Vista/XP/2008/2003/2000, Various Linux, Unix, Mac 10.4 and up           Interface         Windows 7/Vista/XP/2008/2003/2000, Various Linux, Unix, Mac 10.4 and up           Interface         Hi-Speed USB 2.0, Wireless 802.11 b/g/n, Wi-Fi Direct           Noise Level         Less than 50 dBA (Printing and Copying), Less than 26 dBA Standby           Monthy Duty Cycle         10.000 pages           Dimensions (W × D × H)         15.3" x 10.8" x 9.8"           Weight         14.7 lbs.           User Interface         16 x 2 Line LCD (w/o backlight)           Power         Average Operation           Consumption         Seep Mode           Less than 30W         Less than 30W           Consumables         Toner		Media Weight		16 - 43 lbs.
Note         Memory         64 MB           OS Compatibility         Windows 7/Vista/XP/2008/2003/2000, Various Linux, Unix, Mac 10.4 and up           Interface         Hi-Speed USB 2.0, Wireless 802.11 b/g/n, Wi-Fi Direct           Noise Level         Less than 50 dBA (Printing and Copying), Less than 26 dBA Standby           Monthly Dut/ V:         10.000 pages           Dimensions (W × D x H)         15.3° x 10.8″ x 9.8″           Veight         14.7 lbs.           User Interface         16 x 2 Line LCD (w/o backlight)           Veight         16 x 2 Line LCD (w/o backlight)           Seep Mode         Less than 30W           Consumble         Seep Mode           Standard Tomer. Average Cartridge Yield 1,500 standard pages (MLT-D101S) Initial Tomer. Average Cartridge Yield 700 standard pages (MLT-D101S)		ADF Capacity		N/A (Flatbed only)
OS Compatibility       Windows 7/Vista/XP/2008/2003/2000, Various Linux, Unix, Mac 10.4 and up         Interface       Hi-Speed USB 2.0, Wireless 802.11 b/g/n, Wi-Fi Direct         Noise Level       Less than 50 dBA (Printing and Copying), Less than 26 dBA Standby         Monthly Duty ∪cle       10.000 pages         Dimensions (W ∪ D x H)       15.3" x 10.8" x 9.8"         Vieight       14.7 lbs.         User Interface       16 x 2 Line LCD (w/o backlight)         Vieight       Less than 310W         Consumption       Less than 30W         Consumption       Less than 30W         Consumption       Standby Mode         Standard Tomer. Average Cartridge Yield 1,500 standard pages (MLT-D101S)         Intel Tomer. Average Cartridge Yield 700 standard pages	General	Processor		433 MHz
Interface       Hi-Speed USB 2.0, Wireless 802.11 b/g/n, Wi-Fi Direct         Noise Level       Less than 50 dBA (Printing and Copying), Less than 26 dBA Standby         Monthly Duty $\bigtriangledown$ 10,000 pages         Dimension(K $\lor$ D x H)       5.3" x 10.8" x 9.8"         Veight       15.3" x 10.8" x 9.8"         User Interface       16 x 2 Line LCD (w/o backlight)         User Interface       16 x 2 Line LCD (w/o backlight)         Orsumable       Less than 30W         Consumables       Less than 30W         Consumables       Less than 30W		Memory		64 MB
Noise Level     Less than 50 dBA (Printing and Copying), Less than 26 dBA Standby       Monthly Duty ∪yel     10,000 pages       Dimensions (W x D x H)     15.3" x 10.8" x 9.8"       Weight     14.7 lbs.       User Interface     16 x 2 Line LCD (w/o backlight)       Power     Average Operation       Consumables     Less than 30W       Consumables     Less than 30W		OS Compatibility		Windows 7/Vista/XP/2008/2003/2000, Various Linux, Unix, Mac 10.4 and up
Monthly Duty Cycle     10,000 pages       Dimensions (W x D x H)     15.3" x 10.8" x 9.8"       Weight     14.7 lbs.       User Interface     16 x 2 Line LCD (w/o backlight)       Power     Average Operation       Consumables     Standby Mode       Less than 30W       Consumables     Standby Mode		Interface		Hi-Speed USB 2.0, Wireless 802.11 b/g/n, Wi-Fi Direct
Dimensions (W × D × H)       15.3" x 10.8" x 9.8"         Weight       14.7 lbs.         User Interface       16 x 2 Line LCD (w/o backlight)         Power       Average Operation         Consumption       Less than 310W         Standby Mode       Less than 30W         Standby Mode       Less than 30W         Consumables       Toner    Standard Toner: Average Cartridge Yield 1,500 standard pages (MLT-D101S)		Noise Level		Less than 50 dBA (Printing and Copying), Less than 26 dBA Standby
Weight         14.7 lbs.           User Interface         16 x 2 Line LCD (w/o backlight)           Power         Average Operation           Consumption         Less than 310W           Steep Mode         Less than 1.6W           Standby Mode         Less than 30W           Consumption         Toner           Verage Cartridge Yield 1,500 standard pages (MLT-D101S)           Initial Toner: Average Cartridge Yield 700 standard pages		Monthly Duty Cycle		10,000 pages
User Interface         16 x 2 Line LCD (w/o backlight)           Power         Average Operation         Less than 310W           Seep Mode         Less than 1.6W           Standby Mode         Less than 30W           Consumables         Toner           Verage Cartridge Yield 1,500 standard pages (MLT-D101S) Initial Toner: Average Cartridge Yield 700 standard pages		Dimensions (W x D x H)		15.3" x 10.8" x 9.8"
Power Consumption     Average Operation     Less than 310W       Sleep Mode     Less than 1.6W       Standby Mode     Less than 30W       Consumables     Toner       Verage Cartridge Yield 1,500 standard pages (MLT-D101S) Initial Toner: Average Cartridge Yield 700 standard pages		Weight		14.7 lbs.
Consumption         Sleep Mode         Less than 1.6W           Standby Mode         Less than 30W           Consumables         Toner         Standard Toner: Average Cartridge Yield 1,500 standard pages (MLT-D101S) Initial Toner: Average Cartridge Yield 700 standard pages		User Interface		16 x 2 Line LCD (w/o backlight)
Steep Mode     Less than 1.6W       Standby Mode     Less than 30W       Consumables     Toner       Verage Cartridge Yield 1,500 standard pages (MLT-D101S) Initial Toner: Average Cartridge Yield 700 standard pages			Average Operation	Less than 310W
Consumables Toner Standard Toner: Average Cartridge Yield 1,500 standard pages (MLT-D101S) Initial Toner: Average Cartridge Yield 700 standard pages			Sleep Mode	Less than1.6W
Initial Toner: Average Cartridge Vield 700 standard pages			Standby Mode	Less than 30W
Declared cartridge yield in accordance with ISO/IEC 19752	Consumables	Toner		

## CONSUMABLES For a complete list of accessories, visit samsung.com/printer

MLT-D101S

Black Standard Toner Cartridge, 1,500-page yield



starprogram SAMSUNG Toner Recycling Program samsung.com/starus

# For complete product information and accessories, visit samsung.com/printer or samsung.com/business



©2012 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and or registered trademarks of their respective manufacturers and companies. See samsung.com for detailed information. Printed in USA. PNT-SCX3405WWALMARTDSHT-APR12T