

SP 311SFNw

B&W Multifunction Laser Printer

- Z Copier
- Z Printer
- Z Facsimile
- Z Scanner





The versatility of multifunctionality with the convenience of wireless

Managing communications in your office just got easier. The SAVIN[®] SP 311SFNw lets you place high quality black-and-white laser printing, copying, and faxing plus full-color scanning wherever you need it. Simple to use and easy to maintain, this 30-page-per-minute multifunction system offers a robust feature set including standard duplex printing and wireless networking to handle all of your everyday business tasks.

Multifunctionality where you want it

Put the compact Savin SP 311SFNw to work right next to you to keep 30-ppm laser printing/copying/scanning/faxing power within easy reach. Or place this versatile office tool wherever it is most convenient for everyone in the office to share. It's your choice. In addition to hardwired USB 2.0 and Ethernet network interfaces, the SP 311SFNw offers built-in IEEE 802.11 b/g/n Wireless LAN connectivity with authentication and encryption. There are no cables, no complex setup procedures, no physical limitations on where to install trouble-free, secure WiFi-enabled laser printing, scanning, and PC faxing* (and walk-up copying/scanning/faxing too).

*Super G3 Faxing requires a hardwired telephone connection.

Business-class performance

The SP 311SFNw is a true business solution ready to tackle real challenges and able to process multiple jobs simultaneously. Copy while faxing, print while scanning, fax while copying, and scan while printing. Now everyone in the office can keep pace with business. The 35-Sheet Automatic Document Feeder quickly processes multi-page originals up to 8.5" x 14" for scanning, copying, and faxing. The versatile 250-Sheet Front-Loading Paper Tray and 50-Sheet Bypass both accept media from postcard to legal size and up to 90 lb. Index in weight. The 50-Sheet Exit Tray collates sets without occupying more space. The control panel has a 4-line LCD screen with corresponding hard keys plus 8 Quick Dials for fast and easy job programming. The Savin SP 311SFNw has it all, and it's all standard.

Easy to maintain and affordable to own

The cost-cutting SP 311SFNw uses Savin's proven All-In-One print cartridge technology for simplified maintenance and reduced per-page costs. Reliable and durable, the AIO cartridge is the only supply you'll ever need – it contains everything that can run out – and can be changed by anyone in seconds. Stretch supplies and lower page costs even further with Toner Save mode. Take advantage of full-color Scan-to-Email/Folder for cost-free information distribution and bring business communication expenses to an all-time low.











Well-rounded multifunctionality

Print like a pro

The Savin SP 311SFNw includes 80 resident font packages for fast, creative printing in any style. Its powerful controller quickly processes files at up to 1200 x 600 dpi resolution for sharp text and graphics on every page at speeds up to 30-ppm. The intuitive PCL 6 printer driver makes it easy to program advanced features such as duplex printing, combining multiple pages onto a single sheet, adding watermarks to pages and adding front covers to sets.

| | ument Size: | | Brint On |
|----------|-----------------------------|-------|------------------------------------|
| Letter | (8.5" × 11") | • | Letter (8.5" x 11") |
| T Zoo | m % | 100 🛫 | 🐼 🖾 Fit to Print Size |
| | Paper Selection: | | Covers/Pages Selection: |
| ~ | Same Paper for All Pages | | Al Pages |
| | | | |
| | | | |
| | | | |
| 🖊 Output | Tray. | | Input Tray: |
| Standard | Tray | - | Auto Tray Select |
| | | | Paper Type: |
| | | | Plain & Recycled |
| | A DESCRIPTION OF THE OWNER. | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | Custom Paper Size Restore Defaults |

Consistent copying

The 35-sheet ADF quickly feeds multi-page documents up to 8.5" x 14". Use the letter-size platen glass to copy single page or wallet size originals. Either way, the Savin SP 311SFNw uses Scan Once/Print Many technology to reproduce up to 99 sets from the initial scan for consistent image quality from first page to last. ID Card Copy expedites the copying of two-sided checks, driver licenses, and insurance cards in a single operation. Easy access to image type and zoom modes gives users total control over document quality.



High resolution scanning, sending and faxing

Bring a wide range of image capture and distribution capabilities to your office. Support for full-color and grayscale scanning allows for easy TWAIN and WIA image capture. Save files in TIFF, PDF, or JPEG format for further editing or to share files with network destinations through Scan-to-Email and Scan-to-Folder. Standard Super G3 Faxing makes it easy to send documents to people who may not be accessible via e-mail. Professional fax capabilities include a 200-entry Address Book, auto redialing, and PC faxing. Not in the office? One hundred pages of built-in fax memory and a telephone answering machine interface mean you'll never miss another fax or voice call.



Savin SP 311SFNw

SYSTEM SPECIFICATIONS

General Specifications Co

| General Specificat | lions | | |
|-----------------------------------|--|--|--|
| Configuration | Desktop Monochrome Multifunction | | |
| | Printer with AIO Cartridge technology | | |
| Reading Element | Flatbed scanner with full-color CCD | | |
| | Contact Image Sensor (CIS) | | |
| Imaging Technology | Laser beam scanning with | | |
| | electrophotographic printing | | |
| Warm-Up Time | 30 seconds or less | | |
| First Print Speed | 8 seconds or less | | |
| Continuous Print Speed | | | |
| Operation Panel | 4-line LCD + alphanumeric keypad | | |
| Platen Scanning | Supported, up to 8.5" x 11.7" | | |
| | (216 x 297 mm) | | |
| Document Feeding | Automatic Document Feeder (Standard) | | |
| Original Capacity | 35 sheets | | |
| Original Size | 5.5" x 5.5" to 8.5" x 14" | | |
| | (140 x 140 mm to 216 x 356 mm) | | |
| Original Weight | 14 – 28 lb. Bond (52 – 105 g/m ²) | | |
| Paper Capacity | 250-Sheet Tray x 1 + 50-Sheet Bypass = | | |
| | 300 sheets | | |
| Auto Duplexing | Standard duplex printing (@ 50% | | |
| | productivity) | | |
| Output Capacity | 50 sheets (face down) | | |
| Paper Sizes | Standard Tray: 5.5" x 8.5" to 8.5" x 14", | | |
| | A6 – B5 Custom Sizes: 3.94" x 5.82" to 8.5" x 14" | | |
| | (100 x 148 mm to 216 x 356 mm) | | |
| | Bypass Tray: 5.5" x 8.5" to 8.5" x 14", | | |
| | A6 – B5 | | |
| | Custom Sizes: 3.5" x 5.5" to 8.5" x 14" | | |
| | (90 x 140 mm to 216 x 356 mm) | | |
| | Duplexing: 8.5" x 11", 8.5" x 14", A4 | | |
| Paper Weights | Standard Tray: 14 – 43 lb. Bond/ | | |
| Taper Weights | 90 lb. Index (52 – 162 g/m ²) | | |
| | Bypass Tray: 14 – 43 lb. Bond/90 lb. Index | | |
| | $(52 - 162 \text{ g/m}^2)$ | | |
| | Duplexing: 16 – 28 lb. Bond (60 – 105 g/m ²) | | |
| Paper Types | Standard Tray: Thin, Thick, Plain, & | | |
| 31.00 | Recycled papers | | |
| | Bypass: Thin, Thick, Plain, & Recycled | | |
| | papers, Labels, Envelopes | | |
| System Dimensions | 15.9" x 15.5" x 15.3" | | |
| (WxDxH) | (405 x 392 x 390 mm) | | |
| Weight | 38.6 lb. (17.5 kg) (including Starter AIO) | | |
| Power Requirements | 120V, 60Hz | | |
| Power Consumption | Maximum: 800 W, Energy Saver: 4.7 W | | |
| | | | |
| Printer/Controller Specifications | | | |

Printer/Controller Specifications

| CPU Memory Printer Languages/ | 360 MHz 128 MB RAM standard/maximum PCL 6 PCL 5e' 80 PCL fonts 1200 x 600 dpi 600 x 600 dpi IEEE 802.11 b/g/n Wireless LAN (Ad Hoc & Infrastructure modes) 10/100Base-TX Ethernet USB 2.0 Hi Speed Type B TCP/IP (IPV4, IPv6), IPP Windows XP, Vista, 7, 8, Server 2003/R2, Server 2008/R2, Server 2012 Citrix Presentation Server 4.0, 4.5, Citrix XenApp 5.0, 6.0 | Optical Resolution TWAIN/WIA Scan Resolution | 1200 x 1200 dpi Platen: 75/100/150/200/300/4 1200/2400/4800/9600/19200 ADF: 75/100/150/200/300/400/ |
|---------------------------------------|--|---|--|
| Drivers Fonts Print Resolutions | | Scan-to Resolutions Grayscale Scan Modes/Speeds | 100/150/200/300/400/600 dp 256 levels Black & White (1 bit): 5 secon |
| Interfaces Network Protocols | | Scanner Interface | (LTR @ 300 dpi via USB 2.0) Grayscale (8 bit): 5 seconds/page Color (8 bit): 10 seconds/page USB 2.0 10/100Base-TX IEEE 802.11 b/g/n Wireless LA Up to 100 Scan destinations in 8 Quick Dial entries TIFF, JPEG, PDF TWAIN Scanner Driver WIA Scanner Driver |
| Network/OS Support | | Address Book Capacity Supported File Formats Software Utilities | |

Utilities

Advanced Printer

Features

Web Image Monitor Smart Organizing Monitor @Remote² (limited support, requires optional @Remote Office Appliance) Collate, Dithering, Duplex, Do Not Print Blank Pages, Front Cover, Layout/N-up, Reduce/Enlarge, Rotate Print, Toner Saving, Watermarks

¹PCL 5e does not ship with the product, but the controller can receive PCL 5e data from the host PC ²Counter information only

Copier Specifications

| copier specification | 5115 | | | | |
|--|--|--|--|--|--|
| Multi-Copy Speed | Single-page document via ADF or platen: | | | | |
| | 30 copies-per-minute | | | | |
| | Multi-page document via ADF: 13 copies- per-minute | | | | |
| First Copy Speed | 13 seconds or less | | | | |
| Maximum Original Size | Platen: Up to 8.5" x 11.7"/A4 | | | | |
| indutination original bize | (210 x 297 mm) | | | | |
| | ADF: Up to 8.5" x 14" (216 x 356 mm) | | | | |
| Original Type | Platen: Sheets/Books/3D objects/Wallet-size | | | | |
| | ID Cards | | | | |
| | ADF: Sheets | | | | |
| Copy Resolution | Scanning: 600 x 600 dpi via Platen | | | | |
| | 600 x 300 dpi via ADF Printing: 600 x 600 dpi | | | | |
| Grayscale | 256 levels | | | | |
| Quantity Indicator | 1 – 99 | | | | |
| Zoom Range | 25 - 400% in 1% increments via ADF | | | | |
| g_ | or platen | | | | |
| Preset Reduction Ratios | 50%, 65%, 78%, 93% | | | | |
| Preset Enlargement | 129%, 155%, 200%, 400% | | | | |
| Ratios | | | | | |
| Copier Features | Combine Copy (2 in 1, 4 in 1), Electronic | | | | |
| | Sort, ID Card Copy, Image Density | | | | |
| | (5 levels), Image Quality Mode (Text/Photo/Mixed), Manual Duplex, | | | | |
| | Photo Mode | | | | |
| | Thoto Mode | | | | |
| Scanner Specifications | | | | | |
| Scanning Device | Full-color CCD array Contact Image | | | | |
| J | Sensor (CIS) | | | | |
| Scanning Capabilities | TWAIN/WIA Scanning | | | | |
| | Scan-to-Email (1 recipient per TX) | | | | |
| | Scan-to-Folder (1 destination per TX) | | | | |
| | Scan-to-FTP (1 destination per TX) | | | | |
| Optical Resolution TWAIN/WIA Scan | 1200 x 1200 dpi | | | | |
| Resolution | Platen: 75/100/150/200/300/400/500/600/ 1200/2400/4800/9600/19200 dpi | | | | |
| Resolution | ADF: 75/100/150/200/300/400/500/600 dpi | | | | |
| Scan-to Resolutions | 100/150/200/300/400/600 dpi | | | | |
| Grayscale | 256 levels | | | | |
| Scan Modes/Speeds | Black & White (1 bit): 5 seconds/page | | | | |
| | (LTR @ 300 dpi via USB 2.0) | | | | |
| | Grayscale (8 bit): 5 seconds/page | | | | |
| | Color (8 bit): 10 seconds/page | | | | |
| | | | | | |
| Scanner Interface | USB 2.0 | | | | |
| Scanner Interface | USB 2.0 10/100Base-TX | | | | |
| Scanner Interface Address Book Capacity | USB 2.0 | | | | |
| | Color (8 bit): 10 seconds/page | | | | |

Facsimile Specifications Circuit

| Circuit | PSTN/PBX |
|-----------------------------|--|
| Compatibility | ITU-T G3, Super G3 Transceiver |
| Maximum Number of Lines | 1 |
| Modem Speed | 33.6 Kbps with Auto Fallback to 2,400 bps |
| Transmission Speed | Approx. 3 seconds/page* |
| Resolution | Standard: 200 x 100 dpi (8 x 3.85 lines/mm) |
| | Detail: 200 x 200 dpi (8 x 7.7 lines/mm) |
| Maximum Scan Width | 8.5" |
| Maximum Scan Length | Platen: 11.7" (297 mm) |
| | ADF: 14" (356 mm) |
| Compression | MH, MR, MMR |
| Scanning Speed | Less than 5 seconds/page (@ 200 dpi) |
| Dialing Modes | Direct Fax Number Entry |
| | 8 Quick Dials |
| CAE Manager | 200 Speed Dials |
| SAF Memory | 100 pages |
| Address Book Capacity | Up to 200 Fax destinations |
| | Outbound TX only |
| Software Utilities | LAN Fax Driver with 1,000-entry LAN Fax |
| F F | Address Book |
| Fax Features | Auto Answer, Auto Redial, Auto/ |
| | Manual/Substitute Reception, Book Fax, |
| | Broadcasting (100 stations), Contrast Control, Error Correction Mode, |
| | Image Reduction, Immediate/Memory |
| | Transmission, Monitor Speaker, On |
| | Hook Dial, Page Retransmission, Pulse/ |
| | Tone Selection, Smoothing, Telephone |
| | Answering Machine Interface, Time |
| | Indicator |
| TILL No. 1 short Companying | MMAR Description: Standard mand: 22.6 Khos |

*ITU No.1 chart. Compression: MMR. Resolution: Standard speed: 33.6 Kbps.

Consumables & Yields

All-In-One Print 3,500 pages Part #: 407245 Cartridge SP 311HS

* Declared yield values based on ISO/IEC 19752. Actual yields may vary based on types of images printed and other factors.

The Savin SP 311SFNw ships with a starter All-In-One print cartridge yielding approximately 1,000 pages. All other consumables ship at full vield.

Specifications subject to change without notice.

Warranty

The Savin SP 311SFNw B&W Multifunction Laser Printer, when delivered in new condition in the original packaging, is entitled to one year free technical telephone support and is warranted against defects in materials and workmanship for a period of ONE (1) YEAR from the date of original purchase. The All-In-One (AIO) Toner Cartridge that is sold with the printer is also warranted with Advance Exchange Warranty Service, for a period of 90 DAYS from the date of original purchase or until depletion of the toner, whichever comes first.

www.savin.com

Savin, 70 Valley Stream Parkway, Malvern, PA 19355, 1-877-472-8460 Savin^{*} and the Savin Logo are registered trademarks of Ricoh Americas Corporation. All other trademarks are the property of their respective owners. © 2013 Ricoh Americas Corporation. All rights reserved. The content of this document, and the appearance, features and specifications of Savin products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Savin makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services and the conditions and factors affecting performance. The only warranties for Savin products and services are as set forth in the express warranty statements accompanying them. \$3457

