

SP 5200S/SP 5210SF/ SP 5210SR

Digital Imaging System

Savin®

COPY >

PRINT >

SCAN >

FAX >

WORKFLOW >



**All you need in an
all-in-one design.**

Discover the value of convenience and productivity.

Turn new challenges and everyday demands into cost-saving opportunities—with the flexible SAVIN® SP 5200S/SP 5210SF/SP 5210SR Digital Imaging System. The powerful system is specifically designed to simplify everyday general office tasks for midsize workgroups. Users can quickly access exceptional multifunction performance—including monochrome copy, color scan, print and fax capabilities—to complete a wide range of projects faster with incredibly low cost-per-page. Ideal for busier workloads, it offers incredible speed, quality, finishing and intuitive controls to streamline workflow so you can manage your documents more efficiently. Its compact design is packed with versatility for optimal production and value. Plus, it's ideal for organizations deploying a print management solution with Savin's Managed Document Services (MDS).



The adjustable full-color touch screen control panel on the SP 5210SF and SP 5210SR can be tilted to give users greater visibility and easy access to the 1-bin and finisher trays. It even offers animated guidance screens for step-by-step instructions.

Deliver More Efficiently

The Savin SP 5200S/SP 5210SF/SP 5210SR offers a wide range of innovative features to improve productivity.

- Boost throughput with exceptional print speeds. The SP 5200S generates up to 47 pages-per-minute. The SP 5210SF and SP 5210SR print up to 52 pages-per-minute.
- Produce crisp, sharp text at up to 1200 x 600 dpi resolution for high-quality, compelling results.
- Take advantage of easy-to-use scanning capabilities to simplify workflow with cost-effective electronic document storage and distribution.
- Work quickly with near-instant system readiness. Warm-up time is less than 20 seconds and first print/copy times are less than 8 seconds.
- Reduce paper, mailing costs and filing space with standard automatic duplexing at nearly 90% of rated simplex speeds.
- Maximize convenience with paperless faxing. Super G3 faxing, Internet Fax, IP Fax, and LAN Fax support come standard on the SP 5210SF and are optional on the SP 5200S and SP 5210SR.

Manage More Conveniently

The Savin SP 5200S/SP 5210SF/SP 5210SR includes user-friendly controls for convenient, intuitive operation.

- Maximize uptime, streamline maintenance and reduce cost-per-page output with a high-yield, 25,000-page AIO print cartridge. When depleted, users can quickly replace the cartridge without technical assistance and recycle the spent cartridge with a provided return label.
- Gain clear, unobstructed access to critical device information from virtually any angle with an innovative 8.5" full-color tilting LCD panel.*
- Perform all of your general office tasks from a single machine without compromising floor space or your budget. The compact footprint offers users more options for placement in more office environments.
- Access most functions, including all paper sources and the print cartridge, in even the tightest spaces via the forward-facing design.

*SP 5210SF and SP 5210SR only.

- Set dozens of system parameters such as paper supplies and user authentication from the desktop with Web Image Monitor.
- Monitor device usage in real time with the Savin @Remote™ Intelligent Management System and receive service notifications quickly to minimize downtime.

Protect Document Integrity

Ensure the right information gets in the right hands with advanced security features that can protect sensitive information from a multitude of threats.

- Restrict access to system functions with user authentication. Up to 500 user codes can be registered and assigned for optimal efficiency in larger workgroups.
- Ensure optimal data protection with the Data OverwriteSecuritySystem (DOSS). When enabled, it destroys latent images and data from the internal hard drive to prevent document reconstruction.

- Stifle attempts by hackers to steal print job data and passwords transmitted over the LAN with SSL Data Encryption or Wi-Fi Protect Access Support.
- Choose the optional Enhanced Locked Print-NX to store print jobs with encrypted data at the MFP until the user swipes an ID card or enters ID information at the control panel to release the job.

Share Information Cost-Effectively

The Savin SP 5200S/SP 5210SF/SP 5210SR offers a host of scanning capabilities to make electronic document capture and distribution quick, easy and free.

- Speed scanning tasks with the 50-sheet Automatic Reversing Document Feeder (ARDF). It accepts originals up to 8.5" x 14" (up to 49" long in custom mode for banner scanning) for incredible flexibility and productivity.
- Convert hardcopy documents to electronic files and incorporate them into new documents using TWAIN scanning capabilities.

USB Type A Port

A USB Type A port is conveniently located in the control panel for quick and easy printing from/scanning to removable media.



Flexibility for Desk or Floor

Stack up to 3 optional Paper Feed Units to boost input capacity to 2,300 sheets.* The Paper Feed Unit TK1100 with casters is designed specifically for floor placement.

*Requires the assistance of a service technician.



SP 5200S/SP 5210SF/SP 5210SR Digital Imaging System

COPY >

PRINT >

SCAN >

FAX >

WORKFLOW >

- Send scanned documents to hundreds of recipients cost-free over the network in one operation with Scan-to-Email/Folder/URL with LDAP support.
- Quickly transfer documents and images to portable media with Scan-to-Media (USB/SD Card) to streamline distribution in any environment.
- Reduce file sizes for scanned color documents without compromising image quality with high compression PDF for faster transmission and printing.

Connect Your User Network

The Savin SP 5200S/SP 5210SF/SP 5210SR includes flexible networking support that enables workgroups to produce a wide range of jobs efficiently.

- Use the robust Controller to support advanced networking features, device monitoring utilities and data protection functions, including innovative device customization and host print capabilities.
- Complete multiple projects with ease. Powerful performance from the 533 MHz processor provides the bandwidth to prepare data streams and expedite project queues to meet the needs of corporate workgroups with 8.5" x 11"/A4 monochrome workflows.
- Enjoy full compatibility throughout the office with standard USB 2.0 Hi Speed Interface and Ethernet connectivity, including support for PCL and genuine Adobe PostScript³® in Windows and Macintosh network environments.
- Store up to 3,000 documents (up to 9,000 pages) on the powerful 128 GB Hard Disk Drive for easy, secure document management.

Handle Every Task

Engineered to help users complete everyday office tasks with ease, the Savin SP 5200S/SP 5210SF/SP 5210SR offers flexible media handling and finishing to expedite workflow.

- Support up to 8.5" x 14" paper sizes with front-loading, user-adjustable paper sources.
- Increase paper supply without compromising floor space. Up to three additional paper trays can be added for a maximum paper capacity of 2,300 sheets.
- Finish sets up to 50 pages automatically, and offset stack up to 250 sheets, with the internal finisher that comes standard on the SP 5210SR.
- Accommodate stocks up to 59 lb. Bond/120 lb. Index (220 g/m²) from any paper source to ensure print jobs are executed on time and deadlines are met.
- Enhance envelope output productivity with universal feeding.
- Extend acceptable paper sizes up to 35" long in the bypass tray to accommodate banner printing and keep more projects in house.

All-In-One Print Cartridge

The all-in-one (AIO) print cartridge is ideal for users without technical training. Easily accessible within seconds simply by opening the front cover, this convenient feature restores output to "like-new" image quality.



Thick Stock Capability

Accommodate thicker paper stock—up to 120 lb. Index—from every paper tray to ensure more projects can be completed to specifications in-house.



The Total Green Office Solution

Savin continues its long-standing commitment to developing office solutions with environmentally friendly and superior energy- and supply-saving features, without compromising productivity.



User-friendly design improves office productivity.

User-Adjusted LCD Control Panel*

See the easy-to-read, tilted control panel comfortably from virtually anywhere.

Super G3 Faxing

Perform a variety of fax functions with pre-programmed speed, quick and group dial shortcuts on the SP 5210SF. A 1-Bin Tray is included to collect inbound faxes.

100-Sheet Bypass Tray

Extend paper sizes up to 35" long for banner production.

Standard 550-Sheet Paper Tray

Front-facing, user-adjustable paper trays accommodate envelopes and paper sizes up to 8.5" x 14" and stock weights up to 80 lb. Bond/120 lb. Index.

3 x 550-Sheet Paper Trays

Add up to three additional paper trays to expand paper capacity to 2,300 sheets.

50-Sheet Automatic Reversing Document Feeder (ARDF)

Process originals efficiently—up to 8.5" x 14" and custom banner scanning up to 49" long—to speed the scanning process.

Internal Finisher

Staple up to 50 pages and stack up to 250 sheets with the space-saving internal finisher on the SP 5210SR.

Duplex Unit

Copy and print on both sides of each sheet of paper, reducing paper usage by half.

Easy-Grip Paper Tray Handles

Open and close doors with only one hand, sitting or standing.



*SP 5210SF and SP 5210SR only.

Pre-configured to meet your needs.



Model	SP 5200S	SP 5210SF	SP 5210SR
Standard Functions	Copy / Print / Scan	Copy / Print / Scan / Fax	Copy / Print / Scan / Finishing
Print Speed	47 cpm/ppm	52 cpm/ppm	
Super G3 Faxing	Optional	Standard	Optional
Color Touch Panel	Fixed Placement	Adjustable	
Internal Staple Finisher	N/A	N/A	Standard
Inner 1-Bin Tray	N/A	Standard	N/A
Output Capacity	500 sheets	600 sheets	250 sheets

MAIN UNIT

Configuration	Desktop
Printing Technology	Laser beam scanning & electrophotographic printing; Monocomponent toner development; All-In-One Print Cartridge Technology
Scanning Technology	Full-Color Flatbed Scanning w/CCD Image Sensor
Scan Type	Sheet, book, three-dimensional objects
Print Speed (LTR)	SP 5200S: 47-ppm, SP 5210SF: 52-ppm, SP 5210SR: 52-ppm
First Print Speed	7.5 seconds or less
Warm-up Time	20 seconds or less
Grayscale	256 levels
Copy Resolution	600 x 600 dpi via Platen Glass, 600 x 300 dpi via ARDF
Print Resolution	1200 x 600 dpi, 600 x 600 dpi, 300 x 300 dpi
Fax Resolution	200 x 200 dpi, 200 x 100 dpi standard; 200 x 400 dpi, 400 x 400 dpi with optional memory
Document Feeding	Automatic Reversing Document Feeder (Standard); Original Capacity: 50 sheets Original Size: 5.5" x 8.5" - 8.5" x 14" (128 mm x 139.7 mm - 216 mm x 355.6 mm); Custom: Up to 49.6" (1260 mm) (Simplex only) Platen: 8.5" x 11.69" (216 x 297 mm) ARDF: 8.5" x 49.6" (216 x 1260 mm) Up to 999 Platen: 25% - 400% in 1% increments ARDF: 25% - 200% in 1% increments 93%, 78%, 65% 155%, 129%
Max. Imageable Area	Standard, up to 8.5" x 14" (Approx. 90% productivity) SP 5200S: 500 sheets face down; SP 5210SF: 600 sheets face down (w/Bin Tray); SP 5210SR: 250 sheets face down (w/Finisher)
Multiple Copies	Standard Tray, Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, A6, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 5.52" - 14.01" (140 mm - 356 mm). Bypass Tray, Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, A6, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 5.52" - 14.01" (160 mm - 356 mm)
Zoom	Standard Tray, Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, A6, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL. Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 5.52" - 14.01" (160 mm - 356 mm)
Preset Reduction	Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²)
Preset Enlargement	Bypass Tray: 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²). When Duplexing: 16 - 44 lb. Bond/90 lb. Index (60 - 163 g/m ²)
Standard Paper Supply	Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes
Optional Paper Supply	SP 5200S: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 5210SF: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 5210SR: 18.1" x 24.2" x 27" (460 mm x 615 mm x 686 mm)
Max. Paper Capacity	SP 5200S: 99.2 lb. (45 kg); SP 5210SF: 103.6 lb. (47 kg); SP 5210SR: 116.8 lb. (53 kg)
Automatic Duplexing	120 - 127V, 60Hz
Output Capacity	Operating: SP 5200S: 863 W, SP 5210SF: 892 W, SP 5210SR: 858 W Energy Saver: 8 W or less
Paper Sizes	UL60950-1, CAN/CSA C22.2 No.60950-1 (c-UL) FCC Part 15 Subpart B, IC ES-003 ENERGY STAR Tier 2, ECP
Paper Weights	5,500 - 15,000 total impressions/month Up to 200,000 total impressions/month
Paper Types (all sources)	
Dimensions (WxDxH)	
Weight	
Power Requirements	
Power Consumption	
Safety Regulations	
EMI	
Environmental Standard	
Average Monthly Volume	
Maximum Duty Cycle	

PRINT CONTROLLER

CPU	533 MHz
Memory	1 GB RAM standard/maximum
Hard Disk Drive*	128 GB (standard)
*Includes HDD Encryption Unit and Overwrite (DOSS)	
Interfaces	Standard: 10/100Base-TX Ethernet, USB 2.0 Hi Speed Type B (for direct computer connection), Dual USB 2.0 Host Interfaces Type A (for external device connection), Front USB 2.0/SD Card Slot Interface (for Scan To/Print from portable media). Optional: Gigabit Ethernet (1000Base-T), IEEE 802.11a/g Wireless, Bluetooth PCL 5e, PCL 6, XPS, Adobe PostScript ³ , PDF Direct Print, Genuine iPDFS (optional)
Printer Languages/Drivers	
FonTS	PCL: 45 fonts + 13 International fonts; Post-Script 3: 136 fonts; iPDFS: 108 fonts (optional)

Supported Environments	Windows XP, Vista, 7, Server 2003/2003R2, Server 2008/2008R2, Mac OS X v.10.2+, Novell NetWare v 6.5+, Citrix Presentation Server, UNIX/Linux TCP/IP (IPv4, IPv6), IPX/SPX, Bonjour
Network Protocols	Bundled Utilities: Web Image Monitor, Font Manager 2000. Optional Utilities: SmartDeviceMonitor for Admin Accounting Package, SmartDeviceMonitor for Client, DeskTopBinder Lite, @Remote Communication Gate S Pro
Software Utilities	Administrator Authentication (5 levels), User Authentication (5 types), HDD Overwrite (DOSS) & Data Encryption, Secure Print, Encrypted Secure Print, Encrypted PDF Mode, Scan-to-Web Mail (SMTP over SSL), IP Address Filtering, Transport Layer Security (TLS), SSI Communication, IPv6, IP Sec, SNMPv3, Quota Setting
Standard Security Features	IEEE802.11 a/g Interface Unit Type J; Gigabit Ethernet Board Type C; Bluetooth Interface Unit Type D; iPDFS Unit Type 5210, Data Overwrite Security Unit Type I; Remote Communication Gate A; Fax Option Type SP5200; Fax Memory Unit Type B 32MB; Telephone Handset Type 1018; HotSpot MFP Option Type E; Browser Unit Type E; File Format Converter Type E
Controller Options	

*For Common Criteria Certification (CC) use. Certification pending.

SCANNER

Scanner Type	Full Color CCD
Scanning Resolutions	Scan-To Modes: 100/200/300/400/600 dpi (Black & White, ARDF & Platen); 100/200/300 dpi (Full Color, ARDF); 100/200/300/400/600 dpi (Full Color, Platen). TWAIN/WSD/WIA: 100 - 600 dpi in 1% increments (Black & White, ARDF); 100 - 1200 dpi in 1% increments (Black & White, Platen); 100 - 600 dpi in 1% increments (Full Color, ARDF & Platen)
Default Resolution	200 dpi
Scanning Speed	Over 30-ippm (B&W/FC, LTR @ 200 dpi)
Max. Original Size	Platen: Up to 8.5" x 11.7" (216 mm x 297 mm); ARDF: Up to 8.5" x 49.6" (216 mm x 1260 mm)
Protocols	Network: TCP/IP; Scan-to-Email: POP, SMTP; Scan-to-Folder: SMB, FTP, NCP
Scan Modes	B&W Text, B&W Text/Line Art, B&W Text/Photo, B&W Photo, Grayscale, Full-Color Text/Photo, Full-Color Glossy Photo, Auto & User Manual Select (ACS)
Image Density	Auto + 7-step Manual Select
Image Rotation	Supported
SADF/Batch Mode	Supported
Supported File Formats	Single/Multi Page TIFF, Single Page JPEG, Single/Multi Page PDF, High Compression PDF
Scan-To Modes	Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card)
Scan-to-Email	Standard; Authorization: SMTP authentication, POP before SMTP authentication
Max. Addresses/Send	500; Attention: To, cc, bcc
LDAP Search	Supported
Maintain E-mail Address	Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin
E-mail Attachments	Up to 2 GB without restriction
Input File Name	Yes
Input Subject	Up to 128 characters
Input Body Message	Up to 80 characters + 5 pre-registered messages
Scan-to-Folder	Standard; Protocol Support: SMB, FTP, NCP
Maintain Address	Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin
Max. Folders/Send	100
Max. Addresses/Send	500
File Attachment Size	Up to 2000 MB
Input File Name	Yes
Network TWAIN Scanning	Standard - All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing; Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern
Endorse	Date, Page Number, Text

DOCUMENT SERVER

Total HDD Capacity	128 GB (Shared with other functions)
Max. Stored Documents	3,000 documents
Max. Pages per Document	2,000 pages
FAX OPTION TYPE SP5200	
(Standard for SP 5210SF, Optional for SP 5200S/ 5210SR)	
Type	Super G3 Transceiver
Circuit	PSTN, PBX
Number of Lines	1
Compatibility	ITU-T, Group 3
Resolution (dpi)	200 x 100, 200 x 200, 200 x 400, 400 x 400 (for Internet & IP Fax, requires optional SAF memory)
Modem Speed	33,600 bps - 2,400 bps w/Auto Fallback

Compression Method	MH, MR, MMR, JBIG
Transmission Speed	G3: Approximately 2 seconds/page (w/JBIG) G3: Approximately 3 seconds/page (w/MMR) Up to 40-ppm (B&W, LTR @ 200 x 100 dpi)
Scanning Speed	See Scanner & Document Feeding Specifications
Original Capacity/Size	Up to 2,000 Quick Dial numbers in Address Book
Auto Dialing	100 Group Dial numbers (500 locations per Group) Standard: 4 MB RAM (approx. 320 pages) Maximum: 28 MB RAM (approx. 2,240 pages)
Page Memory Capacity	1 hour
Memory Backup	LAN Fax, Internet Fax (T.37), IP Fax (T.38)
Additional Fax Modes	Standard on SP 5210SF, requires Fax Option Type 5200 for SP 5200S and SP 5210SR; Connection: 10/100Base-TX Ethernet, IEEE 802.11 a/g Wireless, or Gigabit Ethernet interface; Protocol: G3; Max. Addresses Per TX: 500; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Document Size: Letter, Legal, A4, A5
LAN Fax	Standard on SP 5210SF, requires Fax Option Type 5200 for SP 5200S and SP 5210SR; Connection: 10/100Base-TX Ethernet, IEEE 802.11 a/g Wireless, or Gigabit Ethernet interface; Protocol: G3; Max. Addresses Per TX: 500; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Document Size: Letter, Legal, A4, A5
Internet Fax	Standard on SP 5210SF, requires Fax Option Type 5200 for SP 5200S and SP 5210SR; Connection: 10/100Base-TX Ethernet, IEEE 802.11 a/g Wireless, or Gigabit Ethernet interface; Protocol: G3; Max. Addresses Per TX: 500; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Document Size: Letter, Legal, A4, A5
IP Fax	Standard on SP 5210SF, requires Fax Option Type 5200 for SP 5200S and SP 5210SR; Connection: 10/100Base-TX Ethernet, IEEE 802.11 a/g Wireless, or Gigabit Ethernet interface; Protocol: T.38, TCP, UDP/IP communication; TX/RX Function: To/from IP Fax compatible machines via network; To/from G3 Fax machines via VoIP gateway; Original Size: Letter, A4 (216 mm x 356 mm); Custom: Up to 8.5" x 47" (216 mm x 1200 mm)

HARDWARE ACCESSORIES

Optional Paper Feed Unit (TK1090)	
Capacity	550 sheets, 1 or 2 units may be installed
Paper Size Range	3.86" x 6.3" - 8.5" x 14.01" (98 mm x 160 mm - 216 mm x 356 mm)
Paper Weight	14 lb. Bond - 80 lb. Cover/120 lb. Index (52 - 220 g/m ²)
Dimensions (WxDxH)	17.8" x 20.3" x 5.9" (450 mm x 516 mm x 150 mm)
Weight	19.9 lb. (9.0 kg)
Optional Paper Feed Unit with Casters (TK1100)	
Capacity	550 sheets, 1 unit may be installed as bottom PFU
Paper Size Range	3.86" x 6.3" - 8.5" x 14.01" (98 mm x 160 mm - 216 mm x 356 mm)
Paper Weight	14 lb. Bond - 80 lb. Cover/120 lb. Index (52 - 220 g/m ²)
Dimensions (WxDxH)	24.7" x 25.0" x 8.7" (627 mm x 635 mm x 220 mm) (including casters)
Weight	26.5 lb. (12.0 kg)
Internal Finisher (Standard for SP 5210SR only)	
Tray Capacity	250 sheets
Modes	Shift Sort, Stack, Staple
Paper Weight	14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m ²)
Stapling	1 position; Top parallel
Staple Sheet Sizes	Letter, Legal, Executive, A4, B5, Foolscap, Folio, F
Staple Capacity	50 sheets/set (Letter)
(21 lb. Bond, 80g/m ²)	30 sheets/set (Legal)
Stack Capacity after Stapling	2 sheets: 33 sets; 30 sheets: 7 sets; 50 sheets: 4 sets
Staple Paper Weight	14 - 24 lb. Bond (52 - 90 g/m ²)
Staple Cartridge Capacity	5,000 staples
1-Bin Tray (Standard for SP 5210SF only)	
Tray Capacity	100 sheets
Paper Weight	14 lb. Bond - 80 lb. Cover/120 lb. Index (52 - 220 g/m ²)

SUPPLIES AND CONSUMABLES

Item	Yield
Black AIO Print Cartridge	25,000 pages*
SP 5200HA	
Staple Type T	5,000/carton
Refill Staple Type T	10,000/carton
Maintenance Kit SP 5200	120,000 pages
Includes 1 Fusing Unit, 1 Transfer Roller, 5 Feed Rollers and 5 Friction Pads	

*Declared yield values based on ISO/IEC 19752. Actual yields may vary based on types of images printed and other factors.

The Savin SP 5200S/SP 5210SF/SP 5210SR ships with one starter AIO cartridge yielding 6,000 pages. All other consumables ship at full yield.

For maximum performance and yield, we recommend using genuine Savin parts and supplies.

Specifications subject to change without notice.

WARRANTY

The Savin SP 5200S/SP 5210SF/SP 5210SR is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for a period of 90 days from the date of purchase or until depleted, whichever comes first. Please refer to warranty documents shipped with the product for more details.

