

### SP C242SF Desktop Color Laser MFP



# All-in-one color and performance designed for every office.

### savin



### Manage more jobs more efficiently.

In today's fast-paced office environments, success hinges on doing more with less. The new SAVIN® SP C242SF Desktop Color Laser MFP offers impressive copy/print/scan/fax performance in a small footprint with a price point to match. Meet everyday workflow demands with a host of productivity-enhancing features and produce documents in vibrant color for lasting impact. Designed with user-friendly controls to simplify administrative tasks in any environment, this multifunction system offers all-in-one performance to complete more jobs in less time. Whether the SP C242SF is used as a stand-alone, primary MFP or as an integrated component in a Savin Managed Document Services (MDS) strategy, you'll realize the true value of versatility and convenience.



A large, user-friendly control panel simplifies job set-up, monitoring and maintenance tasks to improve efficiency.

### Multitask and Streamline Workflow

Manage more jobs efficiently with powerful performance from a single all-in-one system.

- The SP C242SF produces copies and prints up to 21 pages-per-minute for both full-color and black-and-white documents.
- Expedite printing and manage multiple jobs easily with a powerful 400 MHz controller and 256MB RAM.
- Offer convenient access for shared use in growing offices with standard networking including IPv6 support—and an optional external wireless Ethernet adapter.
- A full suite of Scan-To document distribution capabilities leverages existing infrastructure to improve document-related processes.

### www.savin.com

- Send faxes anywhere at the fastest available speeds with a 33.6 Kbps Super G3 Modem, built-in desktop PC faxing, Internet fax, 200 speed dials, authorized and paperless fax reception and more.
- Share information easily with a strategically placed USB port located on the front of the system. This gives users advanced Scan-to-USB functionality and convenient access for printing images from a digital camera using PictBridge<sup>™</sup> software.
- Enjoy near-instant readiness with first print speeds of less than 14 seconds and a warm-up time of less than 30 seconds.
- Replace the standard or high-yield All-In-One print cartridges in seconds with a convenient top-loading design.

## SP C242SF Desktop Color Laser MFP

### FLEXIBLE >

### CONVENIENT >

ROBUST >

### PRODUCTIVE > VALUE >

**35-sheet Automatic Document Feeder** 

**Conveniently Located USB Port** 

Large, User-Friendly Control Panel

**All-In-One Print Cartridges for Easy Replacement** 

Standard USB 2.0 and 10/100 Base-TX Ethernet with IPv6 Support plus Optional External Wireless

Standard 250-sheet Paper Tray + 1-sheet Bypass Tray

Optional 500-sheet Paper Feed Unit

### Add Color and Energize Documents

Enhance communications with sharp text and vibrant color delivered cost-effectively on a wide range of media for maximum impact.

- Create high-quality color documents. True 600 x 600 dpi and interpolated resolutions up to 2,400 x 600 dpi meet even the highest image quality demands.
- Optimize toner usage with Economy Color Mode, limiting the amount of toner used on images and graphics to reduce color output costs.
- Capture true quality with full-color and monochrome TWAIN/WIA scanning at up to 1,200 x 1,200 dpi optical resolution and 19,200 x 19,200 dpi driver resolution.
- Accommodate more media with thick paper support up to 42 lb. Bond/83 lb. Index for sizes up to 8.5" x 14"—from both the Standard and Bypass Trays.

### Simplify and Improve Functionality

Designed to reduce total cost of ownership, the Savin SP C242SF packs an impressive collection of cost-efficient features into a compact desktop design.

- Preserve space with a footprint of less than 20 inches for incredible functionality while using minimal desk or counter space.
- Add paper without increasing the footprint. An optional 500-sheet Paper Feed Unit can be installed beneath the MFP to bring system capacity to 751 sheets and offer instant access to letter- and legal-size sheets.
- Enhance workflow with the standard 35-sheet Automatic Document Feeder. Users can scan originals as large as 8.5" x 14" without using the platen glass to expedite multi-page copying, scanning and faxing.
- Minimize filing space and postage costs with standard automatic duplex printing.
- Protect information—and your budget.
  Access to system functions and page volume limits can be set with User
   Restriction controls. Using Locked Print can help secure confidential information.
- Monitor the system in real-time, remotely. Web Image Monitor offers immediate access to supply status and print network settings.



Convenient placement of a USB port on the front of the device allows users to leverage the PictBridge interface and access the Scan-to-USB feature without a PC.



All-In-One print cartridges offer easy replacement and long-lasting results to streamline supply purchasing and minimize inventory costs.

### The Total Green Office Solution

Savin continues its long-standing commitment to developing office solutions with environmentally friendly and superior energy- and supply-saving features, without compromising productivity.





### SP C242SF SPECIFICATIONS

#### ROBUST > **PRODUCTIVE >** CONVENIENT > FLEXIBLE > VALUE >

### ENGINE ODEOLEICATIONS

ENGINE SPECIFICATIONS				
Configuration	Desktop			
Imaging Process	Laser beam scanning & electrophotographic printing with			
	monocomponent toner development			
Reading Element	4-drum tandem method Flatbed with CCD array image sensor			
Print Resolution	600 x 600 dpi (Speed Mode)			
	1200 x 600 dpi equiv. (Standard Mode) 2400 x 600 dpi equiv. (Fine Mode)			
Print/Copy Speed	21 ppm/cpm B&W and Full-Color			
(Letter)	14 accordo or loco			
First Print Speed Warm-Up Time	14 seconds or less 30 seconds or less			
Operating Systems	Windows XP/Vista/7/Server 2003/Server			
	2003R2/Server 2008 (32 bit/64 bit)/ Server 2008R2 (64 bit);Mac OS X 10.3			
	- 10.6; Citrix MetaFrame, UNIX (using			
Software Utilities	Savin UNIX filter) Web Image Monitor, Presto! PageManager			
	250-sheet Paper Tray + 1-sheet Bypass			
Ontional Paper Canacity	Tray 500-sheet Paper Feed Unit			
Maximum Input	751 sheets			
Paper Capacity	150 abaata (faaa dayun)			
Output Capacity Automatic Duplex	150 sheets (face down) Standard			
Paper Sizes	Standard & Bypass Tray: Letter			
	(8.5" x 11"), Legal (8.5" x 14"), EXEC (10.5" x 7.25"), Half Letter (5.5" x 8.5"), A4 (8.3" x 11.7"), A5 (5.8" x 8.3"),			
	À4 (8.3" x 11.7"), A5 (5.8" x 8.3"),			
	A6 (4.1" x 5.8"), B5 JIS (7.2" x 10.1"), B6 JIS (5.0" x 7.2"), F (8" x 13"), Foolscap (8.5" x 13"), Folio (8.25" x 13"),			
	Foolscap (8.5" x 13"), Folio (8.25" x 13"),			
	16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL			
	Custom size: Min. 90 mm x 148 mm			
	(3.6" x 5.92"), Max. 216 mm x 356 mm (8.64" x 14.24")			
	Opt. Paper Feed Unit: Letter (8.5" x 11").			
Paper Weight	A4 (8.3" x 11.7") Standard and Bypass Tray: 16 – 42 lb.			
i apoi woigin	Bond/83 lb. Index (60 – 160 g/m <sup>2</sup> )			
	Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m <sup>2</sup> )			
Media Type	Std. and Bypass Tray: Plain Paper,			
	Middle Thick, Recycled Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color			
	Paper, Prepunched Paper, Letterhead,			
	Bond Paper, Card Stock, and Preprinted			
	Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick,			
	Recycled Paper, Thick Paper, Thin			
	Paper, Color Paper, Preprinted Paper, Prepunched Paper, and Letterhead			
Dimensions (WxDxH)	Prepunched Paper, and Letterhead 16.5" x 19.4" x 18.7" (420 x 493 x 476 mm)			
Weight	66.2 lb. (30 kg or less) (including consumables)			
Power Requirements	120V, 60Hz			
Max. Power Consumption	1300W or less			
Energy Saver Mode	10W or less			
Safety Regulations	UL60950-1 2nd Edition, CAN/CSA C22.2 No. 60950-1 (c-UL), Energy Star 1.2			

#### **PRINT SPECIFICATIONS**

	UNIT OF THE OF T	
CPU	400MHz	
Printer Languages	PCL 5c, PCL 6, PostScript 3 emulation	
Fonts	80 fonts	
RAM Memory	256 MB RAM standard/maximum	
Interfaces	USB 2.0, 10/100Base-TX Ethernet,	
	USB Host Interface for PictBridge™	
Optional Interfaces	IEEE 802.11b/g Wireless	
Network Protocols	TCP/IP (IPv4, IPv6), IPP, Bonjour	
Note: Wireless Option and 1	0/100Base-TX cannot operate simultaneously.	
CONTROLLER OPTIONS		

Wireless Adaptor SX-2500CG

#### **COPIER SPECIFICATIONS**

First Copy Speed	30 seconds for both B&W and Full-Color	
Multi-Copy Speed	20 cpm B&W/10 cpm Full-Color	
Copy Resolution	600 x 600 dpi (Platen)	
19	600 x 300 dpi (ADF)	
Quantity Indicator	1 – 99	
Original Type	Sheet/Book/3D Objects	
Original Size	Up to 8.5" x 11.7" (Platen);	
-	Up to 8.5" x 14" (ADF)	
Zoom	25% – 400% in 1% increments	
	Reduction Ratios: 50%, 65%, 78%, 93%	
	Enlargement Ratios: 129%, 155%,	
	200%, 400%	
Copier Features	Image Density Adjustment (manual only:	
	5 levels); Copy Mode (Text/Photo/	
	Mixed); Color Balance Adjustment;	
	Combine Copy (2-in-1, 4-in-1 via ADF	
	only); Duplex Copy; ID Card Copy;	
	Memory Copy; Electronic Sorting	
	(collation, ADF only)	
SCANNER SPECIFICATIONS		
Scan Modes	Full-Color, Black and White, Grayscale	

### S

Scan Modes	Full-Color, Black and White, Grayscale
Compression	Black and White: MH/MR/MMR
	Color/Grayscale: JPEG
Scan Resolution	Up to 1200 x 1200 dpi (optical)
	Up to 19200 x 19200 dpi (interpolated)
Scan Speed	Black and White: Less than 5 seconds
	-per-page
	Grayscale: Less than 5 seconds-
	per-page
	Full-Color: Less than 10 seconds-
	per page
Scan Interface	USB 2.0, 10/100Base-TX Ethernet
Utilities & Drivers	TWAIN Driver, Presto! PageManager
Scanning Features	TWAIN/WIA, Scan-to-Email/Folder/
	FTP/USB

#### **FACSIMILE SPECIFICATIONS**

Circuit	PSTN, PBX
Compatibility	ITU-T Group 3
Resolution	Standard Mode: 200 x 100 dpi
	Fine Mode: 200 x 200 dpi
Compression	MH/MR/MMR/JBIG
Scanning Speed	Less than 5 seconds-per-page (B&W)
	Less than 10 seconds-per-page
	(Full-Color)
Modem Speed	33.6 Kbps with automatic fallback
Transmission Speed	Super G3: 2 seconds-per-page
	(based on ITU-T Test Chart #1 in
	Standard mode)
Memory Backup	1 hour
SAF Memory	2MB
One-Touch/Speed Dials	s 20 locations/200 locations

Auto Redial; Auto Answer (3 - 5 rings); Auto/Manual/Substitute/Authorized Reception; Answering Machine Interface (FAX/TAD); Error Correction Mode; User Codes; Memory/Immediate Transmission; Parallel Memory Transmission; Resolution Adjustment; Image Reduction; Serial Broadcasting (100 locations); Smoothing; Contrast Control; Internet Fax; PC Fax (Windows only)

#### HARDWARE ACCESSORIES

Paper Feed Unit	Paper Size: Letter (8.5" x 11"),
Type TK1010	A4 (8.3" x 11.7")
туретктото	Capacity: 500 sheets

#### **CONSUMABLES**

Yield 2,500 pages*
,,
2,500 pages*
2,500 pages*
2,500 pages*
6,500 pages*
6,000 pages*
6,000 pages*
6,000 pages*
25,000 pages

\*Declared yield values in accordance with ISO/IEC 19798. Actual yields may vary based on types of images printed and other factors.

The Savin SP C242SF ships with a starter All-In-One print cartridge that yields approximately 1,000 pages. All other consumables ship at full yield. For maximum performance and yield, we recommend using genuine Savin parts and supplies.

Specifications subject to change without notice.

#### WARRANTY

The Savin SP C242SF is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for a period of 90 days from the date of purchase or until depleted, whichever comes first. Please refer to warranty documents shipped with the product for more details.





### www.savin.com

Savin Eive Dedrick Place West Caldwell N.I 07006

Savin Five Dedrick Place, West Caldwell, NJ 07006 SMM\* is a registered trademark of Ricoh Americas Corporation. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Savin products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Savin makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or missions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Savin products and services are as set forth in the express warranty statements accompanying them.