

# SAVIN®

## SP C830DN/ SP C831DN

### Color Laser Printer

- Copier
- Printer
- Facsimile
- Scanner



SP C830DN

45  
ppm

monochrome  
and full-color

SP C831DN

55  
ppm

monochrome  
and full-color

## Produce high-quality color with ease

The SAVIN® SP C830DN and SP C831DN are the easy choices for fast, productive, full-color printing. These versatile systems offer incredible image quality and user-friendly customization to enhance efficiencies for light production environments. From the intuitive, full-color touch-screen control panel with standard USB and SD Card slots to advanced security features, flexible media handling capabilities and eco-friendly enhancements, these systems streamline color workflows and improve productivity. Your customers will notice the compelling, attention-grabbing graphics. You'll appreciate the impact on your bottom line. Choose one as your primary system and print everything for your office — or as an integral part of our Managed Document Services (MDS) strategy and help improve printing productivity throughout your organization.

- Print up to 45/55 prints per minute
- Simplify everyday tasks with the touch-screen control panel
- Protect document and data integrity
- Help minimize energy use
- Customize the system to accommodate unique workflows



## Power, versatility and convenience in a sleek, compact design

Enhance full-color workflows

### Manage demanding workloads

Print with incredible speed and efficiency and get started quickly with short warm-up times and fast print speeds. Create an abundance of presentations, reports, brochures, booklets and more at up to 55 pages-per-minute. With a powerful 600 MHz or 1GHz processor, the Savin SP C830DN and SP C831DN can handle incoming data streams with ease to accommodate higher-volume workloads. Plus, these systems come standard with 512 MB RAM and can be upgraded to 1.5 GB RAM for convenient storage of multiple projects.



### Produce high-quality graphics

Deliver graphics-quality output on paper sizes up to 11" x 17" and keep more jobs in-house. With robust 4-bit color technology, the Savin SP C830DN and SP C831DN print with impressive 9,600 x 600 dpi equivalent resolution for exceptional image clarity. The proprietary, oil-free polyester polymerization (PxP) toner delivers smooth gradations for crisper lines and sharper color reproductions. Edit images through the powerful drivers and take advantage of advanced color simulation.



### Operate with ease

Perform tasks at your convenience with customized controls. The 4.3" color touch-screen control panel provides intuitive menu navigation and one-touch access to job and system status and frequently used job lists. Step-by-step, animated guidance and easy-to-see icons ensure easy operation. Users can even preview jobs before printing for optimal accuracy.



### Handle more media more ways

Build a system configuration to accommodate the unique needs of your print environment. From 3.55" x 5.83" postcards and envelopes to saddle-stitched 11" x 17" booklets, the SP C830DN and SP C831DN offer a variety of paper supply options to meet your specific workflow requirements. The systems come standard with two 550-Sheet paper trays and a 100-Sheet Bypass Tray. Optional Paper Feed Units add an additional 1,100 sheets or an optional 1,200-Sheet Side Large Capacity Tray and 2,000-Sheet Large Capacity Tray extend maximum paper supply to 4,400 sheets for higher volume environments.





# Fast, reliable color output for high-volume print environments

## Secure more accountability

Help protect the integrity of documents and data with robust, easy-to-use security features. For example, user authentication requires users to swipe an ID card or submit a password at the control panel to access user-assigned tasks and documents. The 250 GB Hard Disk Drive (HDD optional for the SP C830DN) protects latent images stored at the printer with Data Encryption and DataOverwriteSecurity System (DOSS). With the HDD, a Locked Print feature stores documents with sensitive information until they are released by authorized users at the device. Administrators can also set print quotas to limit user volumes, set print rules and curb unnecessary printing.



## Finish professional documents in-house

Ensure your printed materials make more of an impact. The systems feature multiple finishing options to stack, staple and hole-punch documents as well as create saddle-stitched booklets in-house. These printers may be configured with a user-assignable 4-Bin Mailbox and/or one of two finishers capable of stapling, hole punching, and saddle stitch booklet production. The 3,000-Sheet Finisher is ideal for high-volume environments that require long, unattended print runs and the ability to staple in portrait or landscape orientation. The 2,000-Sheet Booklet Finisher saddle-stitches and folds output sets so booklets are ready for immediate distribution.



## Maximize energy efficiency

The Savin SP C830DN and SP C831DN offer a wide range of eco-friendly features to improve typical energy consumption (TEC). ECO Night Sensor gives you a choice for how you want to conserve energy when the office is empty. Choose whether the printer turns off automatically, or enters Sleep mode, after the lights are off for a preset time period. Advanced fusing technology requires less electricity to warm up for faster first print and recovery times. The Eco-Friendly Indicator on the control panel displays each user's print history and its simulated impact on the environment to encourage more responsible printing.



# Manage image quality, productivity and costs effectively

## Print from more locations

Print when and where it's most convenient. The Savin SP C830DN and SP C831DN feature a USB/SD card slot right on the control panel, so users can print files from portable media with ease. Users can also print using their smartphones and tablets for easy, on-the-go performance. With one simple application download, users gain access to a host of mobile printing functions that streamline workflow even more.



## Reduce total cost of ownership

Discover incredible value with a versatile printer that handles everyday black-and-white documents and high-end color graphics with minimal cost-per-page and maintenance costs. The Savin SP C830DN and SP C831DN are completely user-serviceable to maximize uptime. Individual toner bottles and the high-yield OPC drum unit can be replaced in seconds. Plus, Economy Color Mode reduces the amount of toner automatically — without compromising text quality — for fast color drafts at minimal cost.



## Connect with efficiency

The Savin SP C830DN and SP C831DN offer seamless network connectivity with Standard USB 2.0 and 10/100 Base-TX Ethernet interfaces for peer-to-peer and shared use environments. Dual USB 2.0 host interfaces allow for direct connection to third party external devices, including a magnetic card reader for user authentication and to print from PictBridge-enabled cameras. Plus, the systems include optional Gigabit, Wireless LAN and parallel interfaces to meet your unique network requirements.





# Comprehensive features for more efficient printing



**Savin SP C830DN**



- 1 4-Bin Mailbox (Optional):** Keep documents separate from multiple users with the 4-Bin Mailbox.
- 2 Output Jogger Unit (Optional):** Available with the 3,000-Sheet Finisher, the Output Jogger Unit offsets finished documents for easy retrieval or transfer to off-line finishing equipment like GBC or spiral binders.
- 3 2,000-Sheet Booklet Finisher (Optional):** Produce full-color booklets cost-effectively with the in-line Booklet Finisher. Also available with an optional Hole Punch Unit.
- 4 3,000-Sheet Finisher (Optional):** Take advantage of high-volume, professional-quality, multi-position stapling with the 3,000-Sheet Finisher. Add the optional Hole Punch Unit for even more flexibility.
- 5 Full-Color Touch-Screen LCD Control Panel with Built-in USB/SD Slot:** Navigate from job to job easily via the intuitive angled customizable control panel featuring an integrated USB/SD Card slot for mobile printing using a PictBridge-enabled camera or memory card.
- 6 ECO Night Sensor:** Saves energy by automatically turning the printer off or placing it in Sleep mode after the room goes dark.
- 7 Automatic Duplexing (Standard):** Produce two-sided documents on sturdy media such as flyers, menus, pamphlets, brochures, and newsletters at virtually no loss in productivity.
- 8 PxP Toner Technology:** Provides more vivid colors and smooth gradations for improved text, fine lines, graphics and photographic reproductions.
- 9 250 GB Hard Disk Drive:** Secure documents with DataOverwriteSecurity System (DOSS), data encryption, Locked Print and more. Standard for the SP C831DN. Optional for the SP C830DN.
- 10 Media Flexibility:** Produce high quality full-color and monochrome output ranging in paper size and weight from postcards and envelopes to saddle-stitched 11"x 17" booklets (up to 82 lb. Bond/170 lb. Index through the Bypass Tray) all from a single device.
- 11 Easy Maintenance:** Maximize productivity with supplies that are easy for any user to replace.
- 12 Paper Trays (Standard):** Load up to 1,200 sheets with two standard 550-Sheet Paper Trays and a 100-Sheet Bypass Tray.
- 13 Paper Feed Units (Optional):** Add an optional 550-Sheet Paper Feed Unit for a maximum paper capacity of 1,750 sheets (requires Caster Table, not shown) or two optional 550-Sheet Paper Feed Units for a maximum paper capacity of 2,300 sheets.
- 14 Large Capacity Trays (Optional):** Maximize total paper capacity with the 1,200-Sheet Side Large Capacity Tray and/or the 2,000-Sheet Large Capacity Tray.
- 15 Broad Compatibility:** Quickly integrate these systems with built-in compatibility for PC and Macintosh environments.

# Savin SP C830DN/SP C831DN

## SYSTEM SPECIFICATIONS

### Specifications

<b>Configuration Technology</b>	Desktop Color Laser Beam Printer Laser-beam scanning & electrophotographic printing with dual component toner development, 4-drum tandem method
<b>Operation Panel</b>	4.3" color touch screen with integrated USB 2.0 host port and SD card slot
<b>Printing Speed</b>	SP C830DN: 45-ppm B&W and full-color SP C831DN: 55-ppm B&W and full-color
<b>Warm-Up Time</b>	SP C830DN: 29 seconds or less SP C831DN: 25 seconds or less
<b>First Print Speed</b>	SP C830DN: Black & White: 3.7 seconds or less; Full Color: 5.7 seconds or less SP C831DN: Black & White: 3.4 seconds or less; Full Color: 5.1 seconds or less
<b>Duplex Print Speed</b>	Near 100% productivity for all paper sizes
<b>Print Resolution</b>	300 x 300-dpi (1-bit), 600 x 600-dpi (2-bit) (Default), 600 x 600-dpi (1-bit, 4-bit), 1200 x 1200 dpi (1-bit)
<b>Standard Paper Supply</b>	550 x 2 Paper Tray + 100-Sheet Bypass Tray (1,200 sheets total capacity)
<b>Maximum Paper Supply</b>	4,400 sheets (Standard Trays 1 & 2 + 2,000-Sheet LCT + 1,200-Sheet Side LCT + 100-Sheet Bypass Tray)
<b>Output Capacity</b>	Standard: 500 sheets, face down (8.5" x 11" or smaller); 250 sheets, face down (8.5" x 14" or larger); Maximum: Up to 4,000 sheets with Finisher, Bridge Unit and 4-Bin Mailbox
<b>Paper Sizes</b>	Standard Tray 1: Fixed for Letter (8.5" x 11") (216 x 279mm), A4, A5 Standard Tray 2 and Optional Paper Feed Units: User adjustable for Letter (8.5" x 11"), Legal (8.5" x 14"), Exec (10.5" x 7.25"), Ledger (11" x 17"), A3, A4, A5; Custom: 5.83" x 7.17" – 11.69" x 17" (148 x 182mm – 297 x 432mm) Envelopes: Com10, C5 Bypass Tray: User adjustable for 5.5" x 8.5" – 11" x 17" (140 x 216mm – 279 x 432mm); Custom Sizes: 3.55" x 5.83" – 12" x 49.6" (90 x 148mm – 305 x 1260mm) Envelopes: Com10, Monarch, C5, C6, DL Optional 2,000-Sheet LCT and Optional 1,200-Sheet Side LCT: Fixed for Letter (8.5" x 11") (216 x 279mm), A4 When Duplexing: 3.55" x 5.83" – 11.69" x 17" (90 x 148mm x 279 x 432mm)
<b>Paper Weights</b>	Standard Trays, Optional Paper Feed Units, and Optional 2,000-Sheet LCT: 14 – 68 lb. Bond/140 lb. Index (52 – 256 g/m) Bypass Tray: 14 – 82 lb. Bond/170 lb. Index (52 – 300 g/m) Optional 1,200-Sheet Side LCT: 16 – 58 lb. Bond/120 lb. Index (60 – 216 g/m) Duplex Unit: 14 – 45 lb. Bond/90 lb. Index (62 – 169 g/m)
<b>Paper Types</b>	All Sources: Plain Paper, Recycled Paper, Color Paper, Letterhead, Special Paper 1-3, Card Stock, Bond Paper, Preprinted Paper Envelopes: Com10 and C5 envelopes can be fed using Standard Tray 2, Bypass Tray and Optional Paper Feed Units Bypass Only: Labels, OHR, Coated Paper Envelopes: Com10, Monarch, C5, C6, DL Standard
<b>Automatic Duplex Dimensions (WxDxH)</b>	Base Model: 26.4" x 26.9" x 25.2" (670 x 684 x 640 mm)
<b>Weight</b>	Base Model: Less than 213 lb. (97 kg)
<b>Power Requirements</b>	120 – 127V, 60Hz
<b>Power Consumption</b>	1.1 W (Sleep Mode)
<b>TEC</b>	SP C830DN – 2.033 kWh/week SP C831DN – 2.638 kWh/week
<b>Operating</b>	1,584 W or less; Sleep: 1.2 W or less
<b>Print Controller Specifications (Standard)</b>	
<b>CPU</b>	SP C830DN: Intel Celeron-M 600MHz SP C831DN: Intel Celeron-M 1GHz
<b>Memory</b>	Standard 512 MB RAM/Maximum 1.5 GB RAM
<b>Hard Disk Drive</b>	SP C830DN: Optional 250 GB SP C831DN: Standard 250 GB (both models include Standard Hard Disk Drive Encryption Unit and DataOverwriteSecurity System)
<b>Printer Languages</b>	Standard: PCL 5c, PCL 6, Adobe® PostScript®3, PDF Direct Print, Direct Media Print (LPEG/TIFF) Optional: PictBridge, Genuine IPDS Host Print, XPS (via download), Universal Driver (via download)
<b>Fonts</b>	Standard: PCL: 45 + 13 International, PostScript3/PDF: 136 Optional: IPDS: 108
<b>Standard Interfaces</b>	10/100Base-TX Ethernet, High Speed USB 2.0 Type B, Dual USB 2.0 Host Type A, USB 2.0 Type A/SD Card Slot integrated into Control Panel (for Print From Portable Media)

<b>Optional Interfaces*</b>	Gigabit Ethernet (1000Base-T) Type D, IEEE 802.11a/g Wireless LAN Type L, IEEE 1284/ECP Parallel Interface Type A Standard: TCP/IP (IPv6) Optional: IPX/SPX
<b>Network Protocols</b>	Windows XP, Vista, 7, Server 2003/R2, Server 2008/R2; Citrix Presentation Server 4.5, Citrix XenApp 5.0+; Mac OS X v10.4 – 10.7; SAP R/3; Novell NetWare Server 6.5 (option is required), UNIX (Using Savin UNIX filter); Sun Solaris 2.6/7/8/9/10, HP-UX 10.x/11.x/11i v2/11i v3, SCO OpenServer 5.0.6/5.0.7/6.0, RedHat Linux Enterprise 4/5/6, IBM AIX 5L version 5.3/6.1/7.1
<b>Operating Systems</b>	SmartDeviceMonitor for Admin and Client; SmartDeviceMonitor for Admin Accounting Report Package; Web SmartDeviceMonitor; Web Image Monitor; Remote Communication Gate Type S; @Remote
<b>Software Utilities</b>	SmartDeviceMonitor for Admin and Client; SmartDeviceMonitor for Admin Accounting Report Package; Web SmartDeviceMonitor; Web Image Monitor; Remote Communication Gate Type S; @Remote
<b>Controller and Memory Options</b>	IEEE 1284 Interface Board Type A IEEE 802.11a/g Wireless LAN Type L Gigabit Ethernet Board Type D Camera Direct Print Card Type J VM Card Type U IPDS Unit Type C830 512 MB Memory Unit Type J 1 GB Memory Unit Type O 250 GB Hard Disk Drive Type C830 (SP C830DN only)
<b>Document Server Specifications*</b>	Total HDD Capacity 250 GB (shared with other functions) Max. Stored Documents 3,000 files Max. Pages/Document 1,000 page Max. Stored Page Capacity Approx. 9,000 pages total
	*Standard for SP C831DN; Optional for SP C830DN
<b>Hardware Accessories</b>	
<b>550 x 1 Paper Feed Unit (PB3120)</b>	Paper Capacity 550 sheets Paper Sizes 7.25" x 10.5" – 11" x 17", A3, A4, A5 Envelopes: Com10, C5 Paper Weights 14 – 68 lb. Bond/140 lb. Index (52 – 256 g/m)
<b>550 x 2 Paper Feed Unit (PB3130)</b>	Paper Capacity 1,100 sheets Paper Sizes 7.25" x 10.5" – 11" x 17", A3, A4, A5 Envelopes: Com10, C5 14 – 68 lb. Bond/140 lb. Index (52 – 256 g/m)
<b>2,000-Sheet Large Capacity Tray (LCT) (PB3140)</b>	Paper Capacity 2,000 sheets (1,000 x 2) Paper Sizes 8.5" x 11", A4 Paper Weights 14 – 68 lb. Bond/140 lb. Index (52 – 256 g/m)
<b>1,200-Sheet Side Large Capacity Tray (LCT) (RT3020)*</b>	Paper Capacity 1,200 sheets Paper Sizes 8.5" x 11", A4 Paper Weights 16 – 58 lb. Bond/120 lb. Index (60 – 216 g/m)
	*Requires configuration with 550 x 2 Paper Feed Unit (PB3130) or 2,000-Sheet Large Capacity Tray (PB3140).
<b>Large Cabinet Stand (FAC 52)</b>	The Large Cabinet Stand (FAC 52) must be selected when the printer main unit is to be configured with a Finisher, but not a paper supply option.
<b>Caster Table Type D</b>	The Caster Table Type D is recommended when the main unit is configured with the 550 x 1 Paper Feed Unit (PB3120).
<b>3,000-Sheet Finisher (SR3120)*</b>	Modes Shift Sort, Stack, Staple, Optional Hole Punch Paper Sizes Proof Tray: 5.5" x 8.5" – 11" x 17", A5 – A3 Shift Tray: 5.5" x 8.5" – 11" x 17", A5 – A3 Proof Tray: 14 – 28 lb. Bond (52 – 105 g/m) Shift Tray: 14 – 68 lb. Bond/140 lb. Index (52 – 256 g/m) Stack Capacity Proof Tray: 250 sheets (8.5" x 11" or smaller), 50 sheets (8.5" x 14" or larger) Shift Tray: 3,000 sheets (8.5" x 11"), 1,500 sheets (8.5" x 14" or larger), 500 sheets (5.5" x 8.5")
<b>Staple Capacity</b>	50 sheets (8.5" x 11" or smaller); 30 sheets (8.5" x 14" or larger); 30 sheets (Mixed Sizes: Letter and Ledger) Stack Capacity 8.5" x 11" – 11" x 17", A4 – A3 Staple Paper Sizes 17 – 24 lb. Bond (64 – 90 g/m) Staple Paper Weights 1 staple/3 positions Staple Positions 2 staples/1 position Dimensions (WxDxH) 25.9" x 24.1" x 37.8" (657 x 613 x 960 mm) Weight 119 lb. (54 kg)
<b>Staple Cartridge Capacity</b>	5,000 staples/cartridge
	*Requires configuration with Bridge Unit (BU3060) and 550 x 2 Paper Feed Unit (PB3130), 2,000-Sheet Large Capacity Tray (PB3140), or Large Cabinet Stand (FAC 52)
<b>2,000-Sheet Booklet Finisher (SR3110)*</b>	Modes Shift Sort, Stack, Staple, Saddle Stitch, Optional Hole Punch

<b>Paper Sizes</b>	Proof Tray: 5.5" x 8.5" – 11" x 17", A5 – A3 Shift Tray: 5.5" x 8.5" – 11" x 17", A5 – A3 Booklet Tray: 8.5" x 11", 8.5" x 14", 11" x 17", A4 – A3
<b>Paper Weights</b>	Proof Tray: 14 – 43 lb. Bond / 90 lb. Index (52 – 163 g/m) Shift Tray: 14 – 68 lb. Bond / 140 lb. Index (52 – 256 g/m) Booklet Tray: 17 – 24 lb. Bond (64 – 90 g/m)
<b>Stack Capacity</b>	Proof Tray: 250 sheets (8.5" x 11" or smaller), 50 sheets (8.5" x 14" or larger) Shift Tray: 2,000 sheets (8.5" x 11" or smaller), 1,000 sheets (8.5" x 14" or larger), 500 sheets (5.5" x 8.5") Booklet Tray: 30 sets (2 – 5 sheets/set, all sizes, saddle-stitch); 15 sets (6 – 10 sheets/set, all sizes, saddle-stitch); 10 sets (11 – 15 sheets/set, all sizes, saddle-stitch)
<b>Staple Capacity</b>	Normal Staple: 50 sheets (8.5" x 11" or smaller), 30 sheets (8.5" x 14" or larger and/ or Mixed Sizes) Saddle Stitch: 15 sheets (up to 60 pages)
<b>Staple Paper Sizes</b>	Normal Staple: 8.5" x 11", 8.5" x 14", 11" x 17", A5 – A3 Saddle Stitch: 8.5" x 11", 8.5" x 14", 11" x 17", A5 – A3
<b>Staple Paper Weights</b>	17 – 24 lb. Bond (64 – 90 g/m)
<b>Staple Positions</b>	1 staple/3 positions (Top, Top Slant, Bottom); 2 staples/2 center positions
<b>Staple Cartridge Capacity</b>	Normal Staple: 5,000 staples/cartridge Saddle Stitch: 2,000 staples/cartridge
<b>Dimensions (WxDxH)</b>	25.9" x 24.1" x 37.8" (657 x 613 x 960 mm) Weight 103.8 lb. (47 kg)
	*Requires configuration with Bridge Unit (BU3060) and 550 x 2 Paper Feed Unit (PB3130), 2,000-Sheet Large Capacity Tray (PB3140), or Large Cabinet Stand (FAC 52)
<b>4-Bin Mailbox Type CS3000*</b>	The 4-Bin Mailbox Type CS3000 can be installed by itself or simultaneously with either Finisher, with or without paper supply options.
<b>Number of Bins</b>	4 bins
<b>Capacity Per Bin</b>	125 sheets x Trays = 500 sheets
<b>Paper Size</b>	5.5 x 8.5" – 11" x 17", A3, A4, A5, A6
<b>Paper Weight</b>	16 – 34 lb. Bond (60 – 128 g/m)
<b>Dimensions (WxDxH)</b>	17.3" x 18.7" x 14.8" (440 x 475 x 375 mm)
<b>Weight</b>	17.6 lb. (8 kg)
<b>Punch Unit Type PU3030</b>	The Hole Punch Unit Type PU3030 is optional for both Finishers; installs inside the Finisher.
<b>Punch Paper Sizes</b>	2 holes: 5.5" x 8.5" – 11" x 17", A5 – A3 3 holes: 8.5" x 11", 11" x 17", A4 – A3
<b>Punch Paper Weight</b>	14 – 43 lb. Bond / 90 lb. Index (52 – 163 g/m)
<b>Bridge Unit (BU3060)</b>	The Bridge Unit (BU3060) is a required accessory when the main unit is to be configured with either Finisher. The Bridge Unit transports pages from the printer's standard exit area into a Finisher for online stapling, punching, and/or folding.
<b>Sheet Capacity</b>	250 sheets (8.5" x 11" or smaller), 125 sheets (8.5" x 14" or larger)
<b>Output Jogger Unit Type 9002A</b>	The Output Jogger Unit Type 9002A is optional for the 3,000-Sheet Finisher only. It taps sheets in the Shift Tray into aligned sets for stacking or off-line binding.
<b>Paper Size</b>	5.5" x 8.5" – 11" x 17", A5 – A3
<b>Paper Weight</b>	14 – 68 lb. Bond / 140 lb. Index (52 – 256 g/m)
<b>Shift Capacity</b>	Up to 20 mm
<b>Dimensions (WxDxH)</b>	4.25" x 17.8" x 5.1" (108 x 452 x 130 mm)
<b>Weight</b>	4.4 lb. (2 kg)
<b>Supplies</b>	
<b>Consumables</b>	<b>Yield*</b>
Print Cartridge Black (Type SP C830DNA)	23,500*
Print Cartridge Yellow (Type SP C830DNA)	27,000*
Print Cartridge Magenta (Type SP C830DNA)	27,000*
Print Cartridge Cyan (Type SP C830DNA)	27,000*
Black Drum Unit (Type SP C830DN)	60,000
Color Drum Unit (Type SP C830DN)	60,000 x 3
(Includes Cyan, Magenta & Yellow units)	
Transfer Unit (Type SP C830DN)	200,000
Fusing Unit (Type SP C830DNA)	160,000
Waste Toner Bottle (Type SP C830DN)	40,000
Staple Type K for SR3120 Finisher	5,000/carton
Staple Type K Refill for SR3120/SR3110	15,000
Staple Type S for SR3110 (Saddle Stitch)	5,000/carton
(Uses Type K refill)	
	*Declared yield values in accordance with ISO/IEC 19798.
	For maximum performance and yield, we recommend using genuine Savin parts and supplies.
<b>Warranty</b>	The Savin SP C830DN and SP C831DN is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for a period of 90 days from the date of purchase or until depleted, whichever ever comes first. Please refer to warranty documents shipped with the product for more details.

www.savin.com

Savin, 70 Valley Stream Parkway, Malvern, PA 19355, 877-472-8460  
Savin® and the Savin Logo are registered trademarks of Ricoh Americas Corporation. All other trademarks are the property of their respective owners. ©2012 Ricoh Americas Corporation. All rights reserved. The content of this document, and the appearance, features and specifications of Savin products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Savin makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Savin products and services are as set forth in the express warranty statements accompanying them.

