

Xerox Phaser® 3250

Black-and-White Laser Printer

Compact, business-ready productivity

This powerful little printer is ready to support a single user or a small workgroup with fast, automatic two-sided printing, office-friendly convenience, and outstanding overall value.



More performance, for less


- **Get work done fast**, with a print speed of up to 30 ppm and a first-page-out time less than 9 seconds.
- **Automatic two-sided printing** saves valuable time and paper.
- A network configuration — with both Windows, Mac and Linux compatibility — is truly business-ready.
- The 400 MHz processor ensures all jobs print quickly and accurately, even when they're loaded with graphics.

Convenience, flexibility

- A surprisingly small footprint makes it easy to position within quick reach.
- Standard 32 MB memory can expand to 160 MB for enhanced performance when your workload demands it.
- Add a second 250-sheet paper tray for a total capacity of 500 sheets.
- Print on custom sizes and a wide range of media, from transparencies and cardstock, to envelopes and postcards.
- Power Save and Toner Save modes help you spend less on electricity and consumables.

Always impressive results

- 1200 image quality print resolution adds visual impact to important jobs.
- PostScript® 3™ compatibility (DN configuration only) and PCL® 6 emulation ensure your print jobs are always accurate.
- A 30,000-page monthly duty cycle handles big print volumes with ease.
- Outstanding Xerox quality, reliability and performance are backed by Xerox Service and Support, a standard one-year warranty, and the unmatched Xerox Total Satisfaction Guarantee.



WxDxH:
14.3 x 14.5 x 9.4 in.
364 x 369.4 x 239.2 mm



Phaser® 3250

Black-and-White Laser Printer



	Phaser® 3250D	Phaser® 3250DN
Speed	Up to 30 ppm (Letter) / 28 ppm (A4)	
Duty Cycle	Up to 30,000 pages / month	
Paper Handling Paper input	Multipurpose Tray: 1 sheet; Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm	
	Tray 1: 250 sheets; Sizes: Letter, Legal, Folio, Oficio, A4, JIS B5, ISO B5, Executive, A5, A6	
	Tray 2: 250 sheets; Sizes: Letter, Legal, Folio, Oficio, A4, JIS B5, ISO B5, Executive, A5, A6	
Paper output	150 sheets	
Automatic two-sided output	Standard	
Print First-page-out-time	As fast as 8.5 seconds	
Resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)	
Processor	400 MHz	
Memory (std/max)	32 MB / 160 MB	
Connectivity	USB 2.0	10/100Base-TX Ethernet, USB 2.0
Language support	PCL® 6 and 5e emulations, IBM Pro Printer emulation, Epson emulation, GDI	PostScript® 3™ compatibility, PCL® 6 and 5e emulations, IBM ProPrinter emulation, Epson emulation, GDI
Print features	Watermarks, Poster printing, N-up, Fit to page, Scaling, Overlays, Booklets, Reduce/enlarge, Toner saver, Custom-size pages	
Warranty	One-year Quick Exchange, Xerox Total Satisfaction Guarantee	

Device Management

Printer Setting Utility for Windows, 3250DN adds:
CentreWare® Internet Services, SNMP 1-2, Ethernal, HTTP, TCP/IP (DN configuration)

Print Drivers

Windows® 2000/XP/7/Server 2003/2008/Vista, Mac OS® X version 10.3-10.5, Various Linux® OS including SUSE™ 8.2-9.2, Red Hat® 8-9, Fedora® Core 1-4, Mandrake 9.2-10.1

Font Support

1 bitmap, 45 scaleable, 136 PostScript® fonts

Media Handling

Multipurpose Tray: 16 – 43 lb. bond / 60 – 163 gsm
Media types: Plain paper, envelopes, transparencies, labels, cardstock
Tray 1 and Tray 2 (optional): 16 – 28 lb. bond / 60 – 105 gsm
Media types: Plain paper
Two sided printing: 20 – 24 lb. bond / 75 – 90 gsm

Operating Environment

Temperature: Storage: 32° to 104° F / 0° to 35° C,
Operating: 50° to 90° F / 10° to 32° C
Humidity: 20% to 80%
Sound pressure levels:
Printing: 54 dB(A)
Standby: 29 dB(A)
Warm-up time (from sleep mode): Less than 15 seconds

Electrical

Power: 110–127 VAC, 50/60 Hz or 220–240 VAC, 50/60 Hz
Power consumption: Standby: 70 W
Printing: 400 W
Power save: 11 W
ENERGY STAR® qualified

Dimensions (WxDxH)

14.3 x 14.5 x 9.4 in. / 364 x 369.4 x 239.2 mm
Weight: 26.19 lbs / 11.88 kg
Optional 250-sheet Tray 2: 14.3 x 15.7 x 3.4 in. / 364 x 400 x 86 mm
Weight: 8.09 lbs / 3.67 kg
Package Dimensions (WxDxH):
22.1 x 18.6 x 13.5 in.
562 x 472 x 344 mm

Certifications

Listed UL 60950/CSA C22.2 No. 60950, CE Mark applicable to Directives 2006/95/EC and 2004/108/EC

What Comes In The Box

- Phaser 3250 Printer
- Print Cartridge (2,000 print capacity¹)
- Software and Documentation CD (with User Manual, Quick Installation Guide, Warranty Statement, Registration Card)
- Power cord
- USB cable



Phaser 3250 shown with optional Tray 2

Supplies

Standard-Capacity Print Cartridge¹:	
3,500 std. pages	106R01373
High-Capacity Print Cartridge¹:	
5,000 std. pages	106R01374

¹ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

Options

250-sheet Tray	098N02194
128 MB Phaser Memory	098N02195

Supplies Recycling Program

Consumables for the Phaser 3250 are part of the Xerox Green World Alliance Supplies Recycling Program. For more information, please visit the Green World Alliance website at www.xerox.com/gwa



Call today. For more information, call **1-877-362-6567** or visit us at **www.xerox.com/office**



© 2010 Xerox Corporation. All rights reserved. Contents of this publication may not be reproduced in any form without permission of Xerox Corporation. XEROX®, XEROX and Design®, CentreWare® and Phaser® are trademarks of Xerox Corporation in the U.S. and/or other countries. Adobe® and PostScript® 3™ are registered trademarks or trademarks of Adobe Systems, Incorporated. PCL® is a registered trademark of Hewlett-Packard. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. All other trademarks are the property of their respective manufacturers. The information in this brochure is subject to change without notice. 10/10 610P72964/3B 325BR-01UC